

# FT3500

## BELL 214ST



**Tank Capacity**  
3500L  
(924gal)



**Tank Weight Empty**  
215kgs  
(475lbs)



**Tank Weight Full**  
3715kgs  
(8190lbs)



**Tank Height**  
270mm  
(11")




**Foam Retardant Capacity**  
95L  
(25gal)



**Power Requirements**  
28Vdc 150Amps



**Hover Fill Pump**  
HP2000 2000L  
(528gal) per min  
fills in 35 seconds



**Dimensions**  
Tank length 3000mm  
(9.8 Feet)  
Tank width 1740mm  
(5.7 Feet)



# FEATURES

- Unique Helitak Fire Tank Controller (FTC) controls and records variable application rates, water collection and delivery, and maintenance and operations data telemetry.
- The enhanced connectivity of the FTC allows the pilot to operate the Fire Tank from the FTC interface, iPad or other smart device.
- Carbon fibre shell construction makes for a light weight, extra strength design.
- Hover Pump design prevents water siphoning.
- Fully self-contained with an internal foam tank, control system, and on-board compressors and pneumatic systems.
- Failsafe emergency door operation.
- 25 minute install and removal process – roll under, attached mounting pins and electrical plugs creating a genuine plug and play solution.
- Designed for maximum head pressure for the most effective canopy penetration.



**Manufacturing & Service**  
Sunshine Coast, Queensland, Australia

**Service**  
Camarillo, California, USA

**0400 350 205**  
[sales@helitak.com.au](mailto:sales@helitak.com.au)  
[www.helitak.com.au](http://www.helitak.com.au)

