

FT4250

Airbus Super Puma AS332, H225

(FAA STC: SR04509CH)



Tank Capacity
4250L
(1122gal)



Tank Weight Empty
325kgs
(716lbs)



Tank Weight Full
4575kgs
(9369lbs)



Tank Height
300mm
(12")




Foam Retardant Capacity
205L
(54gal)



Power Requirements
20Kva 110Vac
3 Phase / 35Amps
28Vdc 30Amps



Hover Fill Pump
HP6000 6000L
(1585gal) per min



Dimensions
Tank length 3400mm
(11 Feet)
Tank width 2000mm
(6.5 Feet)

FEATURES

Unique Helitak Fire Tank Controller (FTC) controls and records variable application rates, water collection and delivery, and maintenance and operations data telemetry.

The enhanced connectivity of the FTC allows the pilot to operate the Fire Tank from the FTC interface, iPad or other smart device.

Carbon fibre shell construction makes for a light weight, extra strength design.

Hover Pump design prevents water siphoning.

Fully self-contained with an internal foam tank, control system, and on-board compressors and pneumatic systems.

Failsafe emergency door operation.

25 minute install and removal process – roll under, attached mounting pins and electrical plugs creating a genuine plug and play solution.

Designed for maximum head pressure for the most effective canopy penetration.



Manufacturing & Service
Sunshine Coast, Queensland, Australia

Service
Camarillo, California, USA

0400 350 205
sales@helitak.com.au
www.helitak.com.au

