

FT5000

Sikorsky S-92



Tank Capacity
5000L
(1320gal)



Tank Weight Empty
325kgs
(716lbs)



Tank Weight Full
5325kgs
(11740lbs)



Tank Height
300mm
(12")




Foam Retardant Capacity
200L
(53gal)



Power Requirements
20Kva 110Vac
3 Phase / 50Amps
28Vdc 30Amps



Hover Fill Pump
HP6000 6000L
(1585gal) per min



Dimensions
Tank length 3600mm
(11.6ft)
Tank width 2000mm
(6.5ft)

FEATURES

- Unique Helitak Fire Tank Controller (FTC) controls and records variable application rates, water collection and delivery, and maintenance and operations data telemetry.
- The enhanced connectivity of the FTC allows the pilot to operate the Fire Tank from the FTC interface, iPad or other smart device.
- Carbon fibre shell construction makes for a light weight, extra strength design.
- Hover Pump design prevents water siphoning.
- Fully self-contained with an internal foam tank, control system, and on-board compressors and pneumatic systems.
- Failsafe emergency door operation.
- 25 minute install and removal process – roll under, attached mounting pins and electrical plugs creating a genuine plug and play solution.
- Designed for maximum head pressure for the most effective canopy penetration.

