



TRUE ZERO TURN™ MOWERS



CONTOUR-CUT FRONTMOUNT™ AND M1 MIDMOUNT™ GROUNDS MAINTENANCE SOLUTIONS

NOTHING KNOWS TURF LIKE A GRASSHOPPER

FIRST TO FINISH . . .

No matter where you mow, there's a Grasshopper True ZeroTurn™ mower that's perfect for the jobs you handle every day. You'll make quick work of wide open areas and zip in and out of tight spaces you thought only a walk-behind could reach, thanks to precise, responsive control of zero-turn maneuverability.

BUILT TO LAST.

When we say a Grasshopper mower could be the last mower you'll ever need, we mean it. Because every mower is built to last, with commercial-grade features you won't find in most mowing equipment. When considering your next mower, look for features such as:

- Sentry™ spindle guards protect bearings from debris
- Fused, automotive-style circuits
- Service-friendly design for ease of maintenance
- Kevlar-type belts for extended belt life
- ¼-inch-thick MARBAIN® steel blades for longer blade life
- 5-bolt wheel pattern to handle side loads and curb shocks
- 8-inch spindle flanges with 6-bolt pattern for added strength
- Anvil-edge deck design protects the leading edge
- Dust-proof fork bearings to seal out contaminants
- 5.5-inch-deep decks for superior airflow*
- Double-laminate deck top across entire width of deck

LIMITED WARRANTY†

3 YEAR
COMMERCIAL

4 YEAR
— 800 HRS —
RESIDENTIAL

As a result, your FrontMount™ or MidMount™ mower will work harder, last longer and deliver dependable performance season after season. It will still be delivering carpet-like cuts, while retaining its value as a re-sellable asset when you do decide to trade it in for a new Grasshopper mower.

TEST DRIVE ONE TODAY.

Just test driving a Grasshopper mower will be enough to convince you how maneuverable, efficient and comfortable a mower can be. Our engineers understand what it takes for an operator to stay alert and in control — all day if necessary — and step off feeling fresh and energized. They translate that understanding into features that make mowing easier and more fun than you ever thought possible. So, stepping onto your Grasshopper mower will be something you look forward to.

See for yourself the Grasshopper difference.

Go to grasshopperdealers.com to find an authorized Grasshopper dealer near you.



*4.5-inch on 48-inch FrontMount™ decks. †See warranty card for details



THE SCIENCE BEHIND THE GRASSHOPPER CUT

The science of airflow includes specially-designed chambers that optimize grass-cutting action. A level cut requires that the grass be lifted at the exact moment that the cutting blade comes into contact with it. But like any complex equation, there are many variables that have to be taken into consideration.

AIRFLOW

For example, extra-deep decks allow the cut grass to be cleared out of the chambers in order to maximize the grass lift as the mower moves forward. The special design of the cutting blades in the Grasshopper's GrassMax™ blades works in concert with the air chambers to maximize lift and move the cut grass out of the chambers. These blades are created from MARBAIN® steel and hold their edge longer, thereby requiring fewer sharpenings over the life of the blade. The GrassMax™ blade system includes a selection of six blade styles to address a variety of grass and mowing conditions. Every blade is designed for optimum lift and superior discharge. This design also reduces drag and power loss and contributes to better fuel economy.

DECK CONSTRUCTION

Maintaining proper airflow and a level cut also requires sturdy deck construction. All Grasshopper decks are manufactured with a double laminate steel spindle plane across the entire surface of the deck, not just around the spindles. This design helps keep the blades and spindles perfectly level. The leading edge of these decks incorporates an anvil edge reinforced with specially-formed steel. The geometry of the formed steel is 74 times stronger than flat steel reinforcement on the leading edge. Caster wheels are strategically positioned to enable the blades to lift grass up even after the wheels have driven over them.

SUSPENSION

Suspension means more than having a comfortable seat. Obtaining a manicured cut requires that the cutting deck follow the contours of the ground without bouncing up and down. This bounce will result in a wavy, or uneven cut. The in-frame isolation built into Grasshopper mowers minimizes deck bounce and provides a quick smooth response in turns and while trimming. This results in time savings while achieving that groomed, velvet cut that everyone desires.



UNPARALLELED COMFORT

COVER MORE GROUND IN LESS TIME

Stay focused, alert and comfortable throughout the speed range and be more productive, efficient and profitable. The ergonomic design, smooth vibration-free ride and premium seat reduce fatigue and dissipate jolts and jostles on uneven ground. And if you have crews mowing, the dramatic increase in productivity and reductions in employee turnover, absenteeism and workers' compensation claims can have a big impact on your business.



GET UNMATCHED ERGONOMICS

An iso-mounted, shock-absorbing footrest that prevents leg and knee fatigue, coupled with an iso-mounted seat and integrated MultiPoint Suspension™, banish vibration for a smoother ride. Seats are covered in breathable CoolTemp Cordura® fabric that dissipates heat and won't crack or tear with extended use.



ENJOY THE RIDE

The Premium Comfort seat features padded lumbar support and armrests covered in breathable CoolTemp Cordura® fabric that won't tear or crack. Armrests have steel support. Seat position enhances the center of gravity for added stability. Optional Wide Seat Conversion Kit available.



KICK UP THE COMFORT

An optional Cordura®-covered Premier Suspension Seat provides a custom fit for operators. The backrest tilts and includes adjustable lumbar support. Seat also adjusts to operator weight and slides fore and aft. Adjustable, foldable armrests round out the comfort features.



STEER INTUITIVELY

The Hydra-Smooth™ dampened dual swing-out control levers deliver effortless control of speed and direction. They easily adjust to your reach, and automatically return to neutral from forward or reverse when released. The dual swing-away lever design was introduced to the industry by Grasshopper in 1969.



MAKE IT YOUR OWN

QuikAjust Tilt™ dual levers offers a 9-inch adjustment that works together with the adjustable seat to provide a custom fit for operators of all sizes. Optional extended levers are also available for taller operators.



REDUCE FATIGUE

The operator stays alert and in control with the ergonomically designed operator station. Enjoy maximized visibility with operational controls and adjustable cup holder at your fingertips.

YOUR SAFETY IS OUR PRIORITY.

Our Vigilant Operator Presence System™ combines a standard Roll-over Protection System (ROPS) structure with an adjustable seatbelt for peace of mind.

Hydraulically dampened steering levers deliver a smooth, responsive ride and return to neutral when released from both forward and reverse.

A system of interlock switches shuts down the engine if the operator leaves the seat with the PTO engaged or when the levers are in the operating position.



BUILT TO LAST SEASON AFTER SEASON

Count on flawless performance, even after years of use, because the strength is built in where it counts most. Rugged engines provide reliable power that handles the toughest applications. Add to that a lower-maintenance design, and you've got a mower that lasts, too.

METAL WHERE IT MATTERS



A robotically welded, high-grade U.S.A. steel exoskeletal™ frame and formed steel I-beam reinforcement provide rugged durability without excess weight for a lighter footprint.

HEAVY-DUTY TRANSMISSIONS

Hydrostatic transmissions used in Grasshopper mowers are built to strict specifications and design matched to the power unit to provide that smooth, intuitive feel that only Grasshopper delivers. The transmissions transfer more power to the cutting deck for quieter operation, longer service life and traction through turns for a better-quality cut.

BUILT TO TAKE IT



Aluminized steel fenders resist corrosion. Lower debris-ingestion guards shroud internal components from harsh elements and the hazards of commercial mowing.

Models may be shown with optional equipment.

RELIABLE POWER THAT ENHANCES PERFORMANCE

Before any engine model is offered in a Grasshopper mower, it must pass thousands of hours of testing in all kinds of temperatures and mowing conditions. All mowers are designed to take maximum advantage of the engine's power and deliver more of it to the cutting decks and implements. Engines are positioned at the rear of the power unit in order to provide a cooler environment for both the engine and the operator thanks to the front-to-rear airflow. Fit your operation with choices of V-twin, 3-cylinder, air- or liquid-cooled, gasoline or diesel OHV engines that deliver dependable power at every start.



LESS MAINTENANCE MEANS MORE "UPTIME," LESS "DOWNTIME"

Mechanics say you'll spend less time on maintenance and more time getting the job done. With fewer grease points and easier access to belts and filters, it's easy to keep your mower in peak condition.

- >> Extended service intervals. With its rugged design and fine-particle filtration system, you'll run your mower up to 1,000 hours between transmission oil changes — more than three times longer than other mowers.
- >> Cleaner, cooler operation. High-efficiency, fine-particle filtration protects the transmission while an auxiliary cooling fan on each transmission pump, an original Grasshopper specification requirement, extends service intervals and transmission life.

REDUCE COSTS
— TO AS LOW AS —
7 CENTS
PER HOUR

Design-matched pump-and-wheel-motor drive systems run cooler to extend service life. Using genuine Grasshopper fluid and filters keeps costs as low as 7 cents per hour.



SERVICE-FRIENDLY ENGINES

Horizontal crankshaft engines are accessible and offer rear access to the clutch and a cleaner environment for extended service life.



CLEANING IS A BREEZE

A clean radiator protects your engine from overheating. A removable debris screen on liquid-cooled models simplifies cleaning. An optional cleaning wand uses water pressure to dislodge debris without damaging radiator fins.



SIMPLIFIED SERVICE

Access belts and grease points quickly and easily, thanks to our Access-Eze™ design.



QUICK ACCESS

Simply raise the hood on liquid-cooled models for engine access.

CUT MAINTENANCE
BY
80%
WITH
FEWER LUBRICATION POINTS

With only five lubrication points on MidMount™ models and fewer than 10 on FrontMount™ models, you'll significantly reduce the time you spend on maintenance.

ADVANCED FEATURES FOR SUPERIOR PERFORMANCE

Every component of a Grasshopper mower is designed from the blades up to deliver both long life and enhanced cut quality. DuraMax® decks leave picture-perfect results — even on less than perfect yards.



ENHANCED AIRFLOW

Extra-deep, 5.5-inch deck features specially designed cutting chambers that deliver superior airflow for better cut quality (4.5-inch on 48-inch FrontMount™ decks).



DURABLE DESIGN

The strength of the anvil-edge DuraMax® deck is enhanced by doubling-up with an extra layer of formed steel that bridges front-end components for impact protection. The geometry of the formed steel is 74 times stronger than a strip of flat steel added to the leading edge.



GRASS-GROOMING STRIPING KIT [STANDARD]

Deck-mounted multi-ply rubber belt “combs” grass into crisp, uniform stripes without a cumbersome roller that can catch on obstacles or gouge turf.

ONE DECK

THREE WAYS TO HANDLE CLIPPINGS

Easily convert the same deck from standard side discharge to optional PowerVac™ Collection, or add a Down Discharge™ mulching package. Down Discharge mulching system reroutes airflow and clippings into a vortical pattern reducing the size of grass particles and drives them deep into the turf.

Dedicated rear discharge decks are also available. See pages 11 and 13 for details.



SIDE DISCHARGE

MULCHING SYSTEM

COLLECTION SYSTEM
PowerVac™ Drive

CONTOUR-CUT FRONTMOUNT™ AND M1 MIDMOUNT™ OPTIONS

SIDE DISCHARGE CONTROL KIT

Closed position closes the side of the deck and raises the discharge chute out of the way. Discharge is released from the rear of the deck to keep clippings out of flowerbeds and off

sidewalks. Open position lowers the chute for regular side discharge operation. Available for 52-inch and larger decks. (Does not replace Down Discharge Mulching Kit.)



CLOSED



(Side discharge operation)
OPEN

VERTICAL ROLLER KITS

Trim close without rubbing buildings, chain link fences and landscaping.


Available for 52-inch or larger decks.



DURAMAX[®] DECKS DELIVER ONE-PASS PERFECTION EVERY TIME

As a key element in getting a manicured cut, we've spent years perfecting our cutting decks to achieve superior airflow for a great cut. Yet, knowing that durability is just as important, we didn't settle for the flimsy, stamped steel deck construction you'll find on many competitive mowers.

THE INDUSTRY'S TOUGHEST SPINDLES



1. Massive 8-inch spindle flanges anchored in a 6-bolt pattern spread the force of impact for greater strength in tough mowing applications.
2. Double-layered, formed steel spindle plane is nearly 1-inch thick in stress zones.
3. Sentry™ spindle guards shield the spindle housing and seal lower bearings from moisture, fiber wrap, fishing line and plastic bags, as well as dirt ingestion.
4. Precisely-turned, ground and polished spindle shafts, with non-greaseable double bearings are designed for high-rotational speeds and minimal maintenance, and keep out dirt and moisture without the need for oversized spindles.
5. Split-steel pulleys are stronger than cast iron or stamped pulleys for exceptional durability to withstand wear and prolong belt life.



A CHOICE OF BLADES FOR THE BEST CUT

GrassMax™ blades are specially designed to create the airflow needed for a precision cut in a wide variety of conditions. All six types of GrassMax™ MARBAIN® blades are 1/4-inch thick and are through-hardened to hold their edge longer, delivering a better cut and twice the life of aftermarket blades.



High-Low Mulching
Down Discharge™ mulching



Medium Lift
PowerVac™ collection



Contour
Best manicured cut



High-Lift Notched
Standard side discharge



Extreme High-Lift Notched
Lush or overgrown areas
(23 hp or larger air-cooled models)



Shredder™
Shredding dry leaves



Make sure you have genuine GrassMax™ blades! Look for the Grasshopper logo and part number on the grass side of the blade.



High-Lift Notched blades are also available with LaserEdge™ technology that requires little or no sharpening for the life of the blade.



MIDMOUNT™ MOWERS

A 4-wheel power unit with the cutting deck mounted under the operator seat and forward of the engine. You'll appreciate our MidMount™ mowers for their durability, ease of transport, timesaving maneuverability and one-pass perfection, making them everything you want in a mower and everything you expect from a Grasshopper.

ALL-DAY
COMFORT
MULTI-POINT
SUSPENSION™

- Suspension
- Iso-Mount
- SmartFrame™
- Operator Station
- Stability

Iso-mounted CoolTemp Cordura®-covered Premium seat and armrests with shock-absorbing footrest eliminates vibration.

QuikAjust Tilt™ levers (optional) provide more than nine inches of custom adjustment.



Optional DuraFlex™ Suspension Fork

DuraFlex™ suspension forks (optional) absorb the impact of rough terrain to maintain a level cut and can be set in fixed position for use with PowerVac™ collectors.


(Optional Michelin® X® Tweel® 13-inch front tires are not for use with Dura-Flex™ forks.)

Flexing 3-piece SmartFrame™ provides smooth, shock-dampening operation.

Strategically placed ISO mounts absorb and reduce vibration.

Low-pressure flotation tires (optional) flex with the terrain, absorb shock and dissipate roughness.

12-gallon, single-fill fuel tank located underneath the seat enhances low center of gravity for terrain-hugging comfort.






EASY HEIGHT CONTROL

QuikAjust™ DropPin™ height adjustment raises and lowers the deck with one foot for precision cutting heights from 1 to 5 inches in ¼-inch increments.

Electric height adjustment available for 200 and 300 Series models. Hydraulic height adjustment (standard on 400 Series mowers) is an option for liquid-cooled 300 Series mowers equipped with 61- or 72-inch decks.



Grasshopper

Others

TERRAIN-HUGGING COMFORT

A 12-gallon, single-fill fuel tank lowers the center of gravity compared to other mowers, providing more traction and stability for an enhanced ride.



STANDARD BUMPER

Protects the rear of your mower while preserving easy access and removal of the rear service shield.

DEDICATED 4X REAR DISCHARGE™

The unique, four-spindle design of the optional 4X Rear Discharge™ DuraMax® deck evenly distributes loads of clippings and eliminates windrowing while channeling material out the back and away from the operator and engine. Trim with either side of the deck — versus hand-held trimming — for reduced costs. Available in 48-inch and larger cutting widths.



Scan this code to watch a 4XRD video.

Evenly Controlled Dispersion Field



CHOOSE THE MIDMOUNT™ MOWER THAT BEST FITS YOUR APPLICATION



Air-cooled gasoline engine
747cc displacement
48-, 52- and 61-inch decks



Air-cooled or liquid-cooled
gasoline or diesel engines
896cc to 993cc displacement
52-, 61- and 72-inch decks



Liquid-cooled diesel engine
1.3L displacement
61- and 72-inch decks

CONTOUR-CUT FRONTMOUNT™ MOWERS

A 3- to 6-wheel power unit with the cutting deck mounted forward of the engine and operator's seat, utilizing 1 to 4 tail wheels. Combining True ZeroTurn™ maneuverability with a low-profile, contour-cut outfront deck, Grasshopper FrontMount™ mowers make the most complex jobs quick and easy, increasing productivity.

ALL-DAY
COMFORT
MULTI-POINT
SUSPENSION™

- AntiVibe Power Platform™
- Iso-Mount
- Weight Transfer
- Front Deck Advantages
- Operator Station
- Smoother Ride

Iso-mounted CoolTemp Cordura®-covered USR™ seat and armrests with shock-absorbing footrest eliminate vibration.

QuikAdjust Tilt™ levers provide more than nine inches of custom adjustment.

EQUIPPED WITH
PowerFold

The AntiVibe Power Platform® isolates the engine and T-Drive™ train from the operator platform for an unprecedented vibration-free experience.

Strategically placed ISO mounts absorb and reduce vibration.

Pivoting tail beam system provides smoother ride.

Low-pressure flotation tires flex with the terrain to absorb shock.


A longer wheelbase with weight distributed across five, six or eight tires for a smooth, balanced ride.

The exclusive PowerFold® Electric Deck Lift raises the deck to a near vertical position at the touch of a switch for easy underside maintenance and space-saving storage. The same switch is also used to adjust the cutting height.

Panoramic visibility reduces neck strain while trimming up close because of the low-profile FrontMount™ deck.


MaxTrax® weight transfer system provides terrain-hugging traction.

CHOICE OF TAIL WHEELS:



SINGLE FORK

● 600 Air-Cooled Series



DUAL FORK

○ 600, 700 & 900 Series



WIDE STANCE
SINGLE FORK

● 700 & 900 Series
○ 600 & 700 Air-Cooled Series



WIDE STANCE
DUAL FORK

○ 700 & 900
Liquid-Cooled Series

● Standard ○ Option



Underside Access

Easy Height Adjustment

OUTFRONT REACHABILITY

Low-profile, contour-cut outfront decks reach under fences, shrubs and low-hanging trees and nose in and out of tight spaces with ease. Operator station is positioned to eliminate twisting and turning to monitor mowing. Trim as you mow to virtually eliminate string trimming while saving labor, fuel and time.

POWERFOLD® ELECTRIC DECK LIFT

An industry-first, the exclusive PowerFold® Electric Deck Lift is a standard feature on every FrontMount™ Grasshopper mower. It controls both deck lift and cutting height with a single switch.

When the deck is raised, enjoy space-saving portability and storage thanks to a smaller footprint equal to mid-mounted mowers.

The near vertical position provides easy underside access for cleaning, changing blades, etc.

The same switch adjusts cutting height between 1.25 and 5 inches. Spacers are used to return to a preset height every time in 1/4-inch increments. No need to reposition hitch pins or perform other time-consuming procedures to change cutting heights.



RESPONSIVE CONTROL

Patented T-Drive™ hydrostatic drives on 600 and 700 Series models couple directly to the engine for smooth, responsive control. Routine maintenance is simplified thanks to an uncluttered configuration under the seat.



DEDICATED REAR DISCHARGE

FrontMount™ rear discharge decks evenly distribute clippings out the back, channeling them away from sidewalks, flower beds, parking lots and gravestones without windrowing.



DECK FLOTATION INSERTS

Full flotation inserts provide the optimal degree of lateral deck flotation. This enables the contour-cut, outfront deck to follow the undulations of the terrain and deliver a manicured cut.



HYDRAULIC LIFT

An optional "on-the-go" hydraulic lift for 700 Series FrontMount™ tractors lifts the deck or implement off the ground to clear curbs, trailer ramps and more. Standard on 900 Series models.

CHOOSE THE FRONTMOUNT™ MOWER THAT BEST FITS YOUR APPLICATION



Air-cooled gasoline engines
694cc displacement
48- and 52-inch decks



Air-cooled or liquid-cooled
gasoline and diesel engines
747cc to 993cc displacement
52-, 61- and 72-inch decks



Air-cooled or liquid-cooled
gasoline or diesel engines
962cc to 1.3L displacement
61- and 72-inch decks



MAXTORQUE™ CLEAN DIESEL

POWER, PERFORMANCE, PRACTICALITY AND SUSTAINABILITY

Grasshopper MaxTorque™ diesel mowers will meet your emissions goals while enjoying convenient, cost-effective power and performance. Handle the toughest jobs with minimal fuel use and maintenance, plus EPA Tier 4 Final emissions compliance. No power-robbing after treatment required.

MaxTorque™ takes clean diesel design to the next level, creating a power unit that channels all that torque into a quiet, comfortable ride with nimble handling, fast mowing speed and the superior, groomed cut you expect from a Grasshopper.

See what others are saying about their MaxTorque™ diesel mowers at GrasshopperMower.com/DieselStories

CONSIDER THE BENEFITS OF CLEAN DIESEL

COST-EFFECTIVE PERFORMANCE

Diesel fuel's higher energy density delivers more efficiency without sacrificing power and torque. Compared to propane, diesel delivers over 50% more power per gallon equivalent.



MORE POWER, FEWER EMISSIONS

Clean diesel provides maximum power with fewer emissions in commercial and residential applications, creating lower levels of carbon monoxide and certain greenhouse gases than either propane or gasoline engines.



FUEL-EFFICIENT PRODUCTIVITY

Fuel savings and enhanced productivity more than offset the per-gallon cost of diesel fuel versus others. In fact, you can save up to 650 gallons of fuel over 1,000 hours of use, and increase your potential for revenue.







THE DIFFERENCE IS CLEAR.



How much can you save?
Visit our Fuel Expense and Emissions Calculator at GrasshopperFuelSavings.com to find out.

— EPA —
TIER 4
FINAL
EMISSIONS
COMPLIANT



Sources: *EPA Climate Registry Default Emissions Factors, March 2018. **CARB 2016 Engine Certifications.

CHOOSE THE MODEL THAT'S RIGHT FOR YOU:

MIDMOUNT™

325D — 52-, 61- and 72-inch decks
400D 1.3L — 61- and 72-inch decks

CONTOUR-CUT FRONTMOUNT™

725DT — 52-, 61- and 72-inch decks
900D 1.3L — 61- and 72-inch decks

POWERVAC™ COLLECTION SYSTEMS

A CLEAN SWEEP FOR A MANICURED APPEARANCE

Building on 60 years of airflow research, PowerVac™ Collection Systems are the most powerful and efficient vacuum collection systems available for turf, delivering professional, finished results that will turn your lawn into the showcase of the neighborhood. As the industry standard in collection technology, PowerVac™ ensures a clean sweep through wet grass, tall vegetation, tough weeds, dense leaves and other turf debris with one pass and no overlap.

Quiet, deck-driven systems move a high volume of air to carry virtually any type of debris through the collection tube without a loud, expensive auxiliary motor. A dynamically balanced, trash-ingesting steel impeller compacts debris without clogging, so you can mow longer without emptying the collector.

GREATER CAPACITY

Large-volume metal hoppers for use in large-acreage applications feature tapered bottoms that take advantage of gravity to compact debris and achieve maximum capacity requiring fewer stops to empty the collector

DON'T LEAVE THE SEAT

Power- and lever-actuated metal hoppers allow clippings and debris to be easily emptied from the operator's seat.

SIMPLE MONITORING

The 6-inch diameter, reinforced, transparent hose carries a large volume of debris, while a ClearView™ sight window lets you monitor fill level.

ONE DECK DOES IT ALL

Grasshopper decks are designed to easily convert from standard side discharge to PowerVac™ collection, so there's no need for a dedicated deck when collecting clippings. Just install the Quik-D-Tatch® Vac, connect the collector and go!

SUPERIOR AIRFLOW


GrassMax™ medium-lift blades create perfect airflow to achieve a clean, manicured cut.

TURN ON A DIME

Enjoy maximum productivity with rear-mounted collectors that retain Grasshopper True ZeroTurn™ maneuverability.



PowerVac™ features six-point weight distribution on FrontMount™ models with no counterweight requirements, providing a lighter footprint while collecting.



The optional **Air Dam Control Kit** attaches under the front edge of the deck, in a predetermined location, to minimize dirt and dust blow-out when operating in dry and dusty conditions. Perfect for use with dry dusty leaf vacuum collection.

POWERVAC™ SOLUTIONS



REINFORCED MESH BAGS

Reinforced 4-cu.-ft.-capacity mesh bags in twin or triple configurations offer total capacities up to 12 cu. ft. Bags slide in and out for easy clippings disposal.



METAL HOPPERS

Metal hoppers offer capacities up to 25 cu. ft. and empty from the operator's seat.



QUIK-D-TATCH®

Exclusive Quik-D-Tatch® Vac can be removed in seconds without tools.



Scan this code to view a video on Quik-D-Tatch®.

72 in.

34 in.

HIGHLIFT™ 15B

Empty the 15-cu.-ft. HighLift™ 15B collector from the street or curb directly into truck beds, over trailer sidewalls. Operators can raise the collector 72 inches and extend it back 34 inches from the operator's seat to spread clippings and debris into the center of a truck bed. Available for FrontMount™ 700 and 900 Series models.

Scan this code to view a video on the HighLift™ 15B.



COMMERCIAL-GRADE IMPLEMENTS

FOR YEAR-ROUND VERSATILITY

Attach your choice of implements to a Grasshopper FrontMount™ power unit to create a high-performance, integrated grounds maintenance system that doesn't compromise on performance and retains zero-turn maneuverability. Horizontal crankshaft engines provide superior power transfer to implements, so you can count on powerful performance in all conditions. Best of all, there is only one engine to maintain compared to multiple single-purpose machines, reducing maintenance, labor and parts inventory.



QUIKCONVERTER™ IMPLEMENT SYSTEM

Easily remove and connect decks and implements with our exclusive QuikConverter™ Implement System. With a two-point attachment system featuring two spring-loaded pins, you'll easily equip your Grasshopper for any job in minutes without tools.



Watch a "no tools"
implement installation.

MAKES
INSTALLATION
AND REMOVAL
SIMPLE

TURF CARE TOOLS



EDGE-EZE™

Reduce edging time by up to 75% with Edge-Eze™, which maintains a clean, sharp edge along sidewalks, driveways and roadways to save you valuable time.

Learn more at grasshoppermower.com/edge



TURBINE BLOWER

The PTO-driven Turbine Blower takes advantage of True ZeroTurn™ maneuverability and powerful airflow to clean leaves and debris from congested or wide open areas while cutting time and labor by 50 to 75%.

Learn more at grasshoppermower.com/turbine



AERA-VATOR™ AERATOR

The powerful gyrations of the tines on the PTO-driven Aera-vator™ aerate and loosen compacted soil in ¼ the time and with ¼ the labor of walk-behind units, leaving no cores to clean up. Popular for sports fields because turf is ready for immediate use.

Learn more at grasshoppermower.com/aerate



DRIFT CONTROL SPRAYER

A productive and cost-effective way to apply liquid fertilizers, pesticides and herbicides. The ProLawn shielded sprayer applies small droplets that “stick” to vegetation, minimizing chemical use and reducing time and labor more than 60%.

Learn more at grasshoppermower.com/sprayer



LITTLE BULLY™ DOZER BLADES

Delivering surprising performance, these tough tools harness Grasshopper's True ZeroTurn™ maneuverability to move loose dirt, sand, gravel or snow quickly and easily, saving time and labor.

Learn more at grasshoppermower.com/blades



CLEANSWEEP™ ROTARY BROOMS

PTO-driven rotary brooms sweep dirt and debris away in record time, making it ideal for sidewalks, parking lots — even walking paths and tracks. Powerful performance also cleans up to 8 inches of snow and reduces labor by more than 60%.

Learn more at grasshoppermower.com/brooms



ENHANCED VISIBILITY

A lower panel allows the operator to monitor implement operation.

POWERFUL SNOW REMOVAL CLEARS A PATH TO WORK AND SCHOOL

Take advantage of zero-turn maneuverability to clear sidewalks, driveways and parking lots quickly and easily with no wasted motion, getting in and out of places you thought only a walk-behind could reach. Equipped with one of our powerful snow removal implements, you'll create a complete, high-performance snow removal system that will deliver professional-grade performance season after season. Short-coupled mounting to the power unit positions the weight of the implement onto the drive wheels for superior traction in snow.

For more information, visit ThrowMoreSnow.com | Models may be shown with optional equipment.

SNOW REMOVAL IMPLEMENTS



CLEANSWEEP™ ROTARY BROOMS

Leave a clean, dry path with powerful, PTO-driven 48- and 60-inch rotary brooms which can clear up to 8 inches of snow. Fixed-angle and bidirectional models are available.



DRIFTBUSTER™ SNOWTHROWERS

PTO-driven 48- and 60-inch snowthrowers propel snow up to 30 feet away while maintaining True ZeroTurn™ maneuverability. The discharge spout rotates a full 180 degrees for on-target placement.



LITTLE BULLY™ DOZER BLADES

These durable 48- and 60-inch blades are highly efficient at moving snow. Three styles are available. Operator's seating position directly above the drive wheels enhances traction in deep, heavy snows.



V-PLOW

Ideal for clearing sidewalks, the 60-inch V-plow pushes snow to both sides, clearing a path in one easy pass. It easily punches through snowdrifts and clears a lane through heavy snow.

OPTIONS FOR COMFORT AND PRODUCTIVITY



WINTER CAB Fully-enclosed Winter Cab features all-metal frame, sides and doors that seal out wind and moisture. Features include tempered-glass windows, front and rear LED lights and an electric windshield wiper for enhanced visibility.
Requires counterweight.



STAY COZY A 16,000 BTU heater is available for winter enclosures on liquid-cooled power units.




KEEP YOUR FEET WARM Install a floor heater on liquid-cooled models and keep feet warm while working.



OPTIONAL BEACON LIGHT Enjoy greater visibility with the addition of a yellow beacon light.



GET A GRIP Benefit from enhanced traction on icy or snow-packed surfaces with rugged tire chains. Designed for use with 20" turf tires.



PANTOGRAPH WIPER ARM KIT Dual wiper arms allow the blade to cover more windshield area for enhanced visibility.



SNOW PERFORMANCE PACKAGE Includes a steering lever-mounted joystick that lifts and lowers the snowthrower and rotates the chute 180° from the operator's seat, or angles or lifts rotary brooms or dozer blades with ease.

200 SERIES AIR-COOLED MIDMOUNT™

Reliable economy in a compact package

LIMITED WARRANTY†
3 YEAR
 — UNLIMITED HRS —
COMMERCIAL
4 YEAR
 — 800 HRS —
RESIDENTIAL



ComfortReach™ with “no tools”
2-in. adjustment range

225

48

52

61

747cc, 2-cylinder
Kohler Command
Pro OHV
gasoline engine

● Standard deck ■ DuraMax® deck

Reliable economy delivers a quality cut and powerful, air-cooled performance in a compact package ideal for tight-quarters mowing. Enjoy the maneuverability of a walk-behind without the fatigue, to mow longer and deliver quality results. The horizontal crankshaft configuration adds performance life to the engine.

Design-matched G² hydrostatic transmissions with CoolFan™ hydrostatic pump cooling system and 7 micron absolute filter partnered with wheel motors create a fully hydraulic system for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

Only five Access-Eze™ lubrication points cut maintenance time up to 80%.

5.5-inch deep DuraMax® decks with anviled-edged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple.

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® and coil-spring suspension provides all-day comfort. Electronic fuel gauge/hour meter on the console is standard.

A higher horsepower combined with a compact wheelbase provides a great power-to-size ratio.

ComfortReach™ provides 2 inches of adjustment at the base of the lever for a custom steering fit. No tools required.

The 12.0 gal/45.4 L single-fill fuel tank lowers the center of gravity, providing more traction and stability for an enhanced ride. The standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

Optional four-spindle dedicated rear-discharge decks evenly distribute clippings out back for a smooth cut and no windrowing to provide the quality cut you expect.

Mowing speeds up to 9.5 MPH
and 5.27 acres/hr. based on
61" cutting width*
For more details visit:
grasshoppermower.com/acres



OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- » Down Discharge™ mulching packages
- » Dedicated 4X Rear Discharge™ deck (Pg. 11)
- » Speed-Trimming™ heavy-duty roller (61") (Pg. 8)
- » TrimAide™ Roller (52") (Pg. 8)
- » DuraGuard™ rear bumper (2 bars)
- » DuraFlex™ suspension forks (Pg. 10)
- » LED work lights (Pg. 38)
- » Taller steering levers
- » QuikAjust Tilt™ steering levers with “no tools” 9-inch comfort range (Pg. 5)
- » Big Boy wide-seat conversion kit
- » Premier suspension seat (Pg. 5)
- » Adjustable cup holder
- » Foldable ROPS with seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires (61") (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Front Casters (Pg. 38)
- » Edge-EZE™ edger (Pg. 19)
- » Shielded sprayer (Pg. 19)
- » Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- » Yellow beacon light (Pg. 21)
- » Side discharge control kit (Pg. 8)
- » Air Dam kit — for dry, dusty conditions (Pg. 17)

AIR-COOLED 200 SERIES - SPECIFICATIONS

MODEL - CUTTING WIDTH	225 48"	225 52"	225 61"
ENGINE			
Type/Displacement/Cylinders			
Kohler Command Pro / 45.6 cu. in. (747cc) / V-Twin	●	●	●
Crankshaft/Cooling System			
Horizontal / Air	●	●	●
Fuel/Capacity			
Gasoline - unleaded / 12 U.S. Gal. (45.4 l)	●	●	●
Air Cleaner			
Heavy-duty, remote-mounted engine air cleaner with replaceable element	●	●	●
DECKS			
Construction (Robotic-welded steel)			
Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane 0.313 in. (7.95 mm) thick - more than 25% thicker than 0.25 in. (6.35 mm) - with 7-gauge skirts for geometric strength. Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.	●	●	●
DuraMax® deck		●	●
Blades (MARBAIN®, 1/4-in.)			
(2) 18 in. (45.7 cm), (1) 15 in. (38.1 cm) - high-lift blades standard	●		
(3) 18 in. (45.7 cm) - high-lift blades standard		●	
(3) 21 in. (53.3 cm) - high-lift blades standard			●
Sentry™ Spindle Assemblies			
Sentry™ Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Double bearings, greasable from top of deck. Spindle head designed to eliminate fiber wrap. Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.	●	●	●
Spindle Housing - 8-in. (20.3 cm)-diameter with 6-bolt pattern			
Machined aluminum	●	●	●
QuikAjust™ DropPin™ Height Adjustment			
Foot-controlled height adjustment pedal with pin	●	●	●
Cutting Height Range			
1.0 - 5.0 in. (2.5 - 12.7 cm)	●	●	●
Blade Drive			
Belt drive with single Kevlar® V-belt and idler arm tensioning	●	●	●
STARTER & ELECTRICAL SYSTEM			
Maintenance-Free Battery/Charging Capacity/Starter			
12 volt/15 amp/solenoid shift	●	●	●
Ignition			
Breakerless	●	●	●
Interlock System			
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	●	●	●
ULTIMATE OPERATOR STATION™			
Premium Comfort Seat			
Iso-mounted, high-back, deep-cushioned, foam-padded, Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	●	●	●
Premier Suspension Seat	○	○	○
Operator Protection			
ROPS with seat belt	●	●	●
Suspension			
InFrame™ suspension with iso-mounted seat and footrest	●	●	●
Console-Mounted Instruments			
Low engine oil pressure light, combination electronic fuel gauge/hour meter, parking brake indicator light, ignition switch and push/pull PTO switch. Choke integrated with throttle lever.	●	●	●
Work Lights (Pre-wired)			
LED	○	○	○

MODEL - CUTTING WIDTH	225 48"	225 52"	225 61"
TRANSMISSION & STEERING			
Type			
Design-matched G ² hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 12cc piston-type pumps and high-torque Parker wheel motors.	●	●	●
Filtration/Hydro Fluid			
7 micron absolute, spin-on / Grasshopper CoolTemp Hydra-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals.	●	●	●
Speed			
0 - 8.5 mph (0 - 13.7 kph) forward	●		
0 - 9.0 mph (0 - 14.5 kph) forward		●	
0 - 9.5 mph (0 - 15.3 kph) forward			●
0 - 6.0 mph (0 - 9.7 kph) reverse	●	●	●
Turning Radius			
True zero degree, turns within own length with counter-rotating, independently powered drive wheels.	●	●	●
Steering			
One- or two-handed operation with adjustable Hydra-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.	●	●	●
Brakes			
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	●	●	●
Disc brakes	●	●	●
Clutch			
Heavy-duty electric MagStop™ blade clutch/brake	●	●	●
POWER UNIT TIRE SIZES			
Drive Wheels (4-ply rated): 23 x 9.5-12 turf	●		
Drive Wheels (4-ply rated): 23 x 10.5-12 turf		●	
Drive Wheels (4-ply rated): 24 x 12-12 turf			●
Drive Wheels (4-ply rated): 24 x 12-12 bar tread			○
Front Casters: 13 x 6.5-6; rib tread, pneumatic with greasable, double-sealed bearings to protect from grass wrap	●	●	●
POWER UNIT DIMENSIONS WITH DURAMAX® DECKS			
Mulch or 4XRD Width*/Length: 49.5 in. (125.7 cm) / 76.5 in. (194.3 cm)	●		
Mulch or 4XRD Width*/Length: 53.5 in. (135.9 cm) / 76.5 in. (194.3 cm)		●	
Mulch or 4XRD Width*/Length: 62.5 in. (158.8 cm) / 78.0 in. (198.1 cm)			●
*Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised.			
Add 12.0 in. (30.5 cm) to width for side discharge with deflector down.			
Height (seat back/seat cushion): 46.5 in. (118.1 cm) / 31.0 in. (78.7 cm)	●	●	
Height (seat back/seat cushion): 47.0 in. (119.4 cm) / 31.5 in. (80.0 cm)			●
Height (ROPS): 70.0 in. (177.8 cm)	●	●	●
WEIGHT			
Uncrated** : 1050 lbs. (476.3 kg)	●		
Uncrated** : 1070 lbs. (485.4 kg)		●	
Uncrated** : 1120 lbs. (508.0 kg)			●
**Mulching package kit weights with high-low mulching blades: 48-in. - 25 lbs. (11.3 kg); 52-in. - 29 lbs. (13.2 kg); 61-in. - 36 lbs. (16.3 kg).			

● Standard ○ Option



Featured Model 225 with 52-inch DuraMax® deck

300 SERIES AIR-COOLED MIDMOUNT™

Unexpected power in the straightaways

LIMITED WARRANTY†

3 YEAR
— UNLIMITED HRS —
COMMERCIAL

4 YEAR
— 800 HRS —
RESIDENTIAL

ComfortReach™ with “no tools”
2-in. adjustment range



Power, efficiency and economy – equipped with a heavy-duty, Vanguard Big Block engine, with horizontal crankshaft for longer performance life, giving you intense mowing power in a surprisingly compact design.

Robust, design-matched G² hydrostatic transmissions with CoolFan™ hydrostatic pump cooling system and 7 micron absolute filter partnered with wheel motors create a fully hydraulic system for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

Only five Access-Eze™ lubrication points cut maintenance time up to 80%.

5.5-inch deep DuraMax® decks with anvil-edged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple.

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar and coil-spring suspension provides all-day comfort. The adjustable cup holder makes it convenient to tote along your favorite beverage. Electronic fuel gauge/hour meter on the console is standard.

A higher horsepower combined with a compact wheelbase provides a great power-to-size ratio.

ComfortReach™ provides 2 inches of adjustment at the base of the lever for a custom steering fit. No tools required.

The 12.0 gal/45.4 L single-fill fuel tank lowers the center of gravity, providing more traction and stability for an enhanced ride. The standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

Optional four-spindle dedicated rear-discharge decks evenly distribute clippings out back for a smooth cut and no windrowing to provide the quality cut you expect.

3358
BIG BLOCK

61 72

993cc, V-twin OHV Vanguard Big Block air-cooled gasoline engine

3298
BIG BLOCK

52 61

896cc, V-twin OHV Vanguard Big Block air-cooled gasoline engine

► DuraMax® deck

Mowing speeds up to 10.5 MPH and 6.88 acres/hr. based on 72" cutting width*
For more details, visit:
grasshoppermower.com/acres



OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- » Down Discharge™ mulching packages
- » Dedicated 4X Rear Discharge™ deck (Pg. 11)
- » Speed-Trimming™ heavy-duty roller (61" and 72") (Pg. 8)
- » TrimAide™ Roller (52") (Pg. 8)
- » DuraGuard™ rear bumper (2 bars)
- » DuraFlex™ suspension forks (Pg. 10)
- » LED work lights (Pg. 38)
- » QuikAjust Tilt™ steering levers with “no tools” 9-inch comfort range (Pg. 5)
- » Taller steering levers
- » Big Boy wide-seat conversion kit
- » Premier suspension seat (Pg. 5)
- » Foldable ROPS with seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Front Casters (Pg. 38)
- » Edge-EZE™ edger (Pg. 19)
- » Shielded sprayer (Pg. 19)
- » Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- » Yellow beacon light (Pg. 21)
- » Filter minder (Pg. 38)
- » Side discharge control kit (Pg. 8)
- » Air Dam kit – for dry, dusty conditions (Pg. 17)

Be more productive with the addition of a PowerVac™ Collection System or other implements. Ask for specifications or visit grasshoppermower.com/implements. Models may be shown with optional equipment. *Actual results may vary. †See warranty card for details

AIR-COOLED 300 SERIES - SPECIFICATIONS

MODEL - CUTTING WIDTH	329B 52"	329B 61"	335B 61"	335B 72"
ENGINE				
Type/Displacement/Cylinders				
B&S Vanguard Big Block / 54.7 cu. in. (896 cc) / V-twin	•	•		
B&S Vanguard Big Block / 60.6 cu. in. (993 cc) / V-twin			•	•
Crankshaft / Cooling System				
Horizontal / Air	•	•	•	•
Fuel / Capacity				
Gasoline - unleaded / 12 U.S. Gal. (45.4 l)	•	•	•	•
Air Cleaner				
Heavy-duty, remote-mounted engine air cleaner with replaceable element	•	•	•	•
DURAMAX® DECKS				
Construction (Robotic-welded steel)				
Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane 0.313 in. (7.95 mm) thick – more than 25% thicker than 0.25 in. (6.35 mm) – with 7-gauge skirts for geometric strength. Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.	•	•	•	•
Blades (MARBAIN®, 1/4-in.)				
(3) 18 in. (45.7 cm) – high-lift blades standard	•			
(3) 21 in. (53.3 cm) – high-lift blades standard		•	•	
(3) 25 in. (63.5 cm) – high-lift blades standard				•
Sentry™ Spindle Assemblies				
Sentry™ Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Double bearings, greasable from top of deck. Spindle head designed to eliminate fiber wrap. Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.	•	•	•	•
Spindle Housing – 8-in. (20.3 cm)-diameter with 6-bolt pattern				
Machined aluminum	•	•	•	•
QuikAjust™ DropPin™ Height Adjustment				
Foot-controlled height adjustment pedal with pin	•	•	•	•
Cutting Height Range				
1.0 – 5.0 in. (2.5 – 12.7 cm)	•	•	•	•
Blade Drive				
Belt drive with single Kevlar® V-belt and idler arm tensioning	•	•	•	•
STARTER & ELECTRICAL SYSTEM				
Maintenance-Free Battery/Charging Capacity/Starter				
12 volt/20 amp/solenoid shift	•	•	•	•
Ignition				
Breakerless	•	•	•	•
Interlock System				
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	•	•	•	•
ULTIMATE OPERATOR STATION™				
Premium Comfort Seat				
Iso-mounted, high-back, deep-cushioned, foam-padded, Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	•	•	•	•
Premier Suspension Seat	○	○	○	○
Operator Protection				
ROPS with seat belt	•	•	•	•
Suspension				
InFrame™ suspension with iso-mounted seat and footrest	•	•	•	•
Console-Mounted Instruments				
Low engine oil pressure and parking brake warning lights, combination electronic fuel gauge/hour meter, ignition and push/pull PTO switches. Choke integrated with throttle lever.	•	•	•	•
Work Lights (Pre-wired)				
LED	○	○	○	○

MODEL - CUTTING WIDTH	329B 52"	329B 61"	335B 61"	335B 72"
TRANSMISSION & STEERING				
Type				
Design-matched G ² hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 16 cc piston-type pumps and high-torque Parker wheel motors.	•	•	•	•
Filtration/Hydro Fluid				
7 micron absolute, spin-on / Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals.	•	•	•	•
Speed				
0 – 10.0 mph (0 – 16.1 kph) forward	•			
0 – 10.5 mph (0 – 16.9 kph) forward		•	•	•
0 – 6.0 mph (0 – 9.7 kph) reverse	•	•	•	•
Turning Radius				
True zero degree, turns within own length with counter-rotating, independently powered drive wheels.	•	•	•	•
Steering				
One- or two-handed operation with adjustable Hydra-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.	•	•	•	•
Brakes				
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	•	•	•	•
Disc brakes	•	•	•	•
Clutch				
Heavy-duty electric MagStop blade clutch/brake	•	•	•	•
POWER UNIT TIRE SIZES				
Drive Wheels (4-ply rated): 23 x 10.5-12 turf	•			
Drive Wheels (4-ply rated): 24 x 12-12 turf		•	•	•
Drive Wheels (4-ply rated): 24 x 12-12 bar tread		○	○	○
Front Casters: 13 x 6.5-6; rib tread, pneumatic with greasable, double-sealed bearings to protect from grass wrap	•	•	•	•
POWER UNIT DIMENSIONS WITH DURAMAX® DECKS				
Mulch or 4XRD Width*/Length: 53.5 in. (135.9 cm) / 79.5 in. (201.9 cm)	•			
Mulch or 4XRD Width*/Length: 62.5 in. (158.8 cm) / 81.0 in. (205.7 cm)		•	•	
Mulch or 4XRD Width*/Length: 73.5 in. (186.7 cm) / 84.5 in. (214.6 cm)				•
*Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector down.				
Height (seat back/seat cushion): 47.0 in. (119.4 cm) / 31.5 in. (80.0 cm)	•	•	•	•
Height (ROPS): 70.0 in. (177.8 cm)	•	•	•	•
WEIGHT				
Uncrated*: 1140 lbs. (517.1 kg)	•			
Uncrated**: 1190 lbs. (539.8 kg)		•	•	
Uncrated***: 1280 lbs. (580.6 kg)				•
**Mulching package kit weights with high-low mulching blades: 52-in. – 29 lbs. (13.2 kg); 61-in. – 36 lbs. (16.3 kg); 72-in. – 44 lbs. (20.0 kg)				

• Standard ○ Option



Featured Model 329B with 61-inch DuraMax® deck and optional bar tread tires

300 SERIES LIQUID-COOLED MIDMOUNT™

Torque and power available on demand

LIMITED WARRANTY†
3 YEAR
 — UNLIMITED HRS —
 COMMERCIAL
4 YEAR
 — 800 HRS —
 RESIDENTIAL



ComfortReach™ with "no tools"
2-in. adjustment range

Designed for fuel economy and extended service life for operating efficiency. Equipped with a 3-cylinder Kubota gasoline or EPA Tier 4 Final-compliant diesel engine, so you can tackle even the toughest jobs with the greatest of ease. The engine is mounted with horizontal crankshaft for longer performance life.

Robust, design-matched G² hydrostatic transmissions with CoolFan™ hydrostatic pump cooling system and 7 micron absolute filter partnered with wheel motors create a fully hydraulic system for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

Only five Access-Eze™ lubrication points cut maintenance time up to 80%.

A higher horsepower combined with a compact wheelbase provides a great power-to-size ratio.

5.5-inch deep DuraMax® decks with anviledged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple.

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar and coil-spring suspension provides all-day comfort. The adjustable cup holder makes it convenient to tote along your favorite beverage. Electronic fuel gauge/hour meter on the console is standard.

ComfortReach™ provides 2 inches of adjustment at the base of the lever for a custom steering fit. No tools required.

The 12.0 gal / 45.4 L single-fill fuel tank lowers the center of gravity, providing more traction and stability for an enhanced ride. The standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

Optional four-spindle dedicated rear-discharge decks evenly distribute clippings out back for a smooth cut and no windrowing to provide the quality cut you expect.

329

52 61 72

962cc, 3-cylinder,
MaxTorque™ gasoline
engine

3250

52 61 72

898cc, 3-cylinder,
MaxTorque™
Clean Diesel engine

● Standard deck ■ DuraMax® deck

Mowing speeds up to 10.5 MPH
and 6.88 acres/hr. based on
72" cutting width*
For more details visit:
grasshoppermower.com/acres



OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- » Down Discharge™ mulching packages
- » Dedicated 4X Rear Discharge™ deck (Pg. 11)
- » Speed-Trimming™ heavy-duty roller (61" and 72") (Pg. 8)
- » TrimAide™ Roller (52") (Pg. 8)
- » Hydraulic height adjustment (61" and 72") (Pg. 11)
- » DuraGuard™ rear bumper (2 bars)
- » DuraFlex™ suspension forks (Pg. 10)
- » LED work lights (Pg. 38)
- » QuikAjust Tilt™ steering levers with "no tools" 9-inch comfort range (Pg. 5)
- » Taller steering levers
- » Big Boy wide-seat conversion kit
- » Premier suspension seat (Pg. 5)
- » Foldable ROPS with seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Front Casters (Pg. 38)
- » Edge-EZE™ edger (Pg. 19)
- » Shielded sprayer (Pg. 19)
- » Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- » Yellow beacon light (Pg. 21)
- » Filter minder (Pg. 38)
- » Radiator cleaning wand (Pg. 7)
- » Engine block heater
- » Side discharge control kit (Pg. 8)
- » Air Dam kit — for dry, dusty conditions (Pg. 17)

LIQUID-COOLED 300 SERIES - SPECIFICATIONS

MODEL - CUTTING WIDTH	325D 52"	325D 61"	325D 72"	329 52"	329 61"	329 72"
ENGINE						
Type/Displacement/Cylinders						
Kubota MaxTorque™ / 54.8 cu. in. (898 cc) / 3-cyl.	•	•	•			
Kubota MaxTorque™ / 58.7 cu. in. (962 cc) / 3-cyl.				•	•	•
Crankshaft/Cooling System						
Horizontal / Liquid	•	•	•	•	•	•
Fuel/Capacity						
Diesel - No. 2 / 12 U.S. Gal. (45.4 l)	•	•	•			
Gasoline - unleaded / 12 U.S. Gal. (45.4 l)				•	•	•
Air Cleaner						
Heavy-duty, remote-mounted engine air cleaner with replaceable element	•	•	•	•	•	•
DECKS						
Construction (Robotic-welded steel)						
Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane 0.313 in. (7.95 mm) thick – more than 25% thicker than 0.25 in. (6.35 mm) – with 7-gauge skirts for geometric strength. Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.	•	•	•	•	•	•
DuraMax® deck	•	•	•	•	•	•
Blades (MARBAIN®, 1/4-in.)						
(3) 18 in. (45.7 cm) – high-lift blades standard	•			•		
(3) 21 in. (53.3 cm) – high-lift blades standard		•			•	
(3) 25 in. (63.5 cm) – high-lift blades standard			•			•
Sentry™ Spindle Assemblies						
Sentry™ Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Double bearings, greasable from top of deck. Spindle head designed to eliminate fiber wrap. Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.	•	•	•	•	•	•
Spindle Housing – 8-in. (20.3 cm)-diameter with 6-bolt pattern						
Machined aluminum	•	•	•	•	•	•
QuikAjust™ DropPin™ Height Adjustment						
Foot-controlled height adjustment pedal with pin	•	•	•	•	•	•
Cutting Height Range						
1.0 – 5.0 in. (2.5 – 12.7 cm)	•	•	•	•	•	•
Blade Drive						
Belt drive with single Kevlar® V-belt and idler arm tensioning	•	•	•	•	•	•
STARTER & ELECTRICAL SYSTEM						
Maintenance-Free Battery/Charging Capacity/Starter						
12 volt/40 amp/solenoid shift	•	•	•	•	•	•
Ignition						
Breakerless				•	•	•
Diesel quick heat glow plug	•	•	•			
Interlock System						
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	•	•	•	•	•	•
ULTIMATE OPERATOR STATION™						
Premium Comfort Seat						
Iso-mounted, high-back, deep-cushioned, foam-padded, Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	•	•	•	•	•	•
Premier Suspension Seat	○	○	○	○	○	○
Operator Protection						
ROPS with seat belt	•	•	•	•	•	•
Suspension						
InFrame™ suspension with iso-mounted seat and footrest	•	•	•	•	•	•
Console-Mounted Instruments						
Low engine oil pressure, combination electronic fuel gauge/hour meter, alternator, temperature and parking brake warning lights, engine temperature and volt gauges, ignition and push/pull PTO switches.	•	•	•	•	•	•
Choke integrated with throttle lever				•	•	•
Glow plug	•	•	•			
Work Lights (Pre-wired)						
LED	○	○	○	○	○	○

MODEL - CUTTING WIDTH	325D 52"	325D 61"	325D 72"	329 52"	329 61"	329 72"
TRANSMISSION & STEERING						
Type						
Design-matched G ² hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 16 cc piston-type pumps and high-torque Parker wheel motors.	•	•	•	•	•	•
Filtration/Hydro Fluid						
7 micron absolute, spin-on / Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals.	•	•	•	•	•	•
Speed						
0 – 10 mph (0 – 16.1 kph) forward	•			•		
0 – 10.5 mph (0 – 16.9 kph) forward		•	•		•	•
0 – 6.0 mph (0 – 9.7 kph) reverse	•	•	•	•	•	•
Turning Radius						
True zero degree, turns within own length with counter-rotating, independently powered drive wheels.	•	•	•	•	•	•
Steering						
One- or two-handed operation with adjustable Hydra-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.	•	•	•	•	•	•
Brakes						
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	•	•	•	•	•	•
Disc brakes	•	•	•	•	•	•
Clutch						
Heavy-duty electric MagStop blade clutch/brake	•	•	•	•	•	•
Temperature Sentry/high temperature clutch cut-out	•	•	•	•	•	•
POWER UNIT TIRE SIZES						
Drive Wheels (4-ply rated): 23 x 10.5-12 turf	•			•		
Drive Wheels (4-ply rated): 24 x 12-12 turf		•	•		•	•
Drive Wheels (4-ply rated): 24 x 12-12 bar tread		○	○		○	○
Front Casters: 13 x 6.5-6; rib tread, pneumatic with greasable, double-sealed bearings to protect from grass wrap.	•	•	•	•	•	•
POWER UNIT DIMENSIONS WITH DURAMAX® DECKS						
Mulch or 4XRD Width*/Length: 53.5 in. (135.9 cm) / 82.5 in. (209.6 cm)	•			•		
Mulch or 4XRD Width*/Length: 62.5 in. (158.8 cm) / 84.0 in. (213.4 cm)		•			•	
Mulch or 4XRD Width*/Length: 73.5 in. (186.7 cm) / 87.5 in. (222.3 cm)			•			•
*Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector down.						
Height (seat back/seat cushion): 47.0 in. (119.4 cm) / 31.5 in. (80.0 cm)	•	•	•	•	•	•
Height (ROPS): 69.5 in. (176.5 cm)	•	•	•		•	•
Height (ROPS): 70.0 in. (177.8 cm)				•		
WEIGHT						
Uncrated**: 1310 lbs. (594.2 kg)	•			•		
Uncrated**: 1360 lbs. (616.9 kg)		•			•	
Uncrated**: 1450 lbs. (657.7 kg)			•			•
**Mulching package kit weights with high-low mulching blades. 52-in. – 29 lbs. (13.2 kg); 61-in. – 36 lbs. (16.3 kg); 72-in. – 44 lbs. (20.0 kg)						

• Standard ○ Option



Featured Model 329 with 72-inch DuraMax® deck

400 SERIES LIQUID-COOLED MIDMOUNT™

Full-featured top-of-the-line
MidMount™ mowers

LIMITED WARRANTY†

3 YEAR

— UNLIMITED HRS —
COMMERCIAL

4 YEAR

— 800 HRS —
RESIDENTIAL

QuikAjust Tilt™ levers
with 9-in. adjustment range



400 D 1.3L

61

72

1.3L, 3-cylinder,
liquid-cooled MaxTorque™
clean diesel engine
with horizontal
crankshaft

► DuraMax® deck

Fast and powerful to get the job done on time, every time. Enjoy the power and economy of a Tier 4-compliant, 1.3L Kubota 3-cylinder MaxTorque™ clean diesel engine. The horizontal crankshaft provides longer performance life, plus you'll enjoy the comforts of delivering a picture-perfect cut in less time than you'd expect.

Rugged, design-matched 21cc G² hydrostatic transmissions with CoolFan™ hydrostatic pump cooling system and 7-micron absolute filter partnered with wheel motors create a fully hydraulic system for responsive steering and less maintenance with 1,000-hour fluid change intervals.

Only five Access-Eze™ lubrication points cut maintenance time up to 80%.

Relative to its power and size, the footprint is compact for transport on trailers and through tighter spaces.

5.5-inch deep DuraMax® decks with anviledged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The standard Hydraulic Height Adjustment feature enables cutting height changes with the flip of a switch.

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar and coil-spring suspension provides all-day comfort. An adjustable cup holder makes it convenient to tote along your favorite beverage. Two USB ports are available to charge cell phones and other devices. Electronic fuel gauge/hour meter on the console is standard.

QuikAjust Tilt™ steering levers with "no tools" adjustment provide a 9-inch range for maximum comfort and fit.

The 12.0 gal/45.4 L single-fill fuel tank lowers the center of gravity, providing more traction and stability for an enhanced ride. The standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

Optional four-spindle, dedicated rear-discharge decks evenly distribute clippings out back for a smooth cut without windrowing, providing the quality cut you expect.

Mowing speeds up to 11 MPH
and 7.20 acres/hr. based on
72" cutting width*
For more details visit:
grasshoppermower.com/acres



OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- » Down Discharge™ mulching packages
- » Dedicated 4X Rear Discharge™ deck (Pg. 11)
- » Speed-Trimming™ heavy-duty roller (Pg. 8)
- » DuraGuard™ rear bumper (2 bars)
- » DuraFlex™ suspension forks (Pg. 10)
- » Taller steering levers
- » Big Boy wide-seat conversion kit
- » Premier suspension seat (Pg. 5)
- » Foldable ROPS with seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Front Casters (Pg. 38)
- » Edge-EZE™ edger (Pg. 19)
- » Shielded sprayer (Pg. 19)
- » Side discharge control kit (Pg. 8)
- » Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- » Yellow beacon light (Pg. 21)
- » Radiator cleaning wand (Pg. 7)
- » Engine block heater
- » Air Dam kit – for dry, dusty conditions (Pg. 17)

Be more productive with the addition of a PowerVac™ Collection System or other implements. Ask for specifications or visit grasshoppermower.com/implements.
Models may be shown with optional equipment. *Actual results may vary. †See warranty card for details

LIQUID-COOLED 400 SERIES - SPECIFICATIONS

MODEL - CUTTING WIDTH	400D 61"	400D 72"
ENGINE		
Type/Displacement/Cylinders		
Kubota MaxTorque™ diesel / 77 cu. in. (1.3L) / 3-cyl.	●	●
Crankshaft/Cooling System		
Horizontal / Liquid	●	●
Fuel/Capacity		
Diesel - No. 2 / 12 U.S. Gal. (45.4L)	●	●
Air Cleaner		
Heavy-duty, remote-mounted engine air cleaner with replaceable element and filter minder	●	●
DURAMAX® DECKS		
Construction (Robotic-welded steel)		
Double-layered 10-gauge plus 7-gauge formed-steel laminate spindle plane 0.313 in. (7.95 mm) thick – more than 25% thicker than 0.25 in. (6.35 mm) – with 7-gauge skirts for geometric strength. Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.	●	●
Blades (MARBAIN®, 1/4-in.)		
(3) 21 in. (53.3 cm) – high-lift blades standard	●	
(3) 25 in. (63.5 cm) – high-lift blades standard		●
Sentry™ Spindle Assemblies		
Sentry™ Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Double bearings, greasable from top of deck. Spindle head designed to eliminate fiber wrap. Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.	●	●
Spindle Housing – 8-in. (20.3 cm)-diameter with 6-bolt pattern		
Machined aluminum	●	●
Height Adjustment		
Hydraulic height adjustment	●	●
Cutting Height Range		
1.0 – 5.0 in. (2.5 – 12.7 cm)	●	●
Blade Drive		
Belt drive with single Kevlar® V-belt and idler arm tensioning	●	●
STARTER & ELECTRICAL SYSTEM		
Maintenance-Free Battery/Charging Capacity/Starter		
12 volt/40 amp/solenoid shift	●	●
Ignition		
Diesel quick heat glow plug	●	●
Interlock System		
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	●	●
ULTIMATE OPERATOR STATION™		
Premium Comfort Seat		
Iso-mounted, high-back, deep-cushioned, foam-padded, Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	●	●
Premier Suspension Seat	○	○
Operator Protection		
ROPS with seat belt	●	●
Suspension		
InFrame™ suspension with iso-mounted seat and footrest	●	●
Console-Mounted Instruments		
Low engine oil pressure, combination electronic fuel gauge/hour meter, alternator, two USB charging ports, temperature and parking brake warning lights, engine temperature and volt gauges, ignition, glow plug, hydraulic height adjustment and push/pull PTO switches.	●	●
Work Lights (Pre-wired)		
LED	●	●

MODEL - CUTTING WIDTH	400D 61"	400D 72"
TRANSMISSION & STEERING		
Type		
Design-matched G ² hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 21 cc piston-type pumps and high-torque Parker wheel motors.	●	●
Filtration/Hydro Fluid		
7 micron absolute, spin-on / Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals.	●	●
Speed		
0 – 11.0 mph (0 – 17.7 kph) forward	●	●
0 – 6.0 mph (0 – 9.7 kph) reverse	●	●
Turning Radius		
True zero degree, turns within own length with counter-rotating, independently powered drive wheels.	●	●
Steering		
One- or two-handed operation with adjustable Hydra-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.	●	●
Brakes		
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	●	●
Disc brakes	●	●
Clutch		
Heavy-duty electric MagStop blade clutch/brake	●	●
Temperature Sentry/high temperature clutch cut-out	●	●
POWER UNIT TIRE SIZES		
Drive Wheels (6-ply rated): 26 x 12-12 turf	●	●
Drive Wheels (4-ply rated): 24 x 12-12 bar tread	○	○
Front Casters: 13 x 6.5-6; rib tread, pneumatic with greasable, double-sealed bearings to protect from grass wrap	●	●
POWER UNIT DIMENSIONS WITH DURAMAX® DECKS		
Mulch or 4XRD Width*/Length: 62.5 in. (158.8 cm) / 86.0 in. (218.4 cm)	●	
Mulch or 4XRD Width*/Length: 73.5 in. (186.7 cm) / 89.5 in. (227.3 cm)		●
*Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector down.		
Height (seat back/seat cushion): 47.0 in. (119.4 cm) / 31.5 in. (80.0 cm)	●	●
Height (ROPS): 69.5 in. (176.5 cm)	●	●
WEIGHT		
Uncrated**: 1450 lbs. (657.7 kg)	●	
Uncrated**: 1540 lbs. (698.5 kg)		●
**Mulching package kit weights with high-low mulching blades: 61-in. – 36 lbs. (16.3 kg); 72-in. – 44 lbs. (20.0 kg)		

● Standard ○ Option



Featured Model 400D 1.3L with 72-inch DuraMax® deck

600 SERIES AIR-COOLED FRONTMOUNT™

Reliable economy to go the distance

LIMITED WARRANTY†
3 YEAR
 — UNLIMITED HRS —
 COMMERCIAL
4 YEAR
 — 800 HRS —
 RESIDENTIAL



Standard PowerFold® Electric Deck Lift.
 See Page 13 for more info.

623T

48

52

694cc, Kohler
 Command Pro V-Twin
 OHV gasoline engine

● 33 Series deck ■ DuraMax® deck

A practical solution for your home or business, delivering the agile performance and quality cut only Grasshopper True ZeroTurn™ mowers can provide. Trim while you mow under shrubs and fences and enhance your precision cutting capabilities.

The horizontal crankshaft configuration adds performance life to the engine.

Design-matched T-Drive™ hydrostatic drive systems, with AntiVibe Power Platform®, direct more power to the cutting deck and eliminate vibration. The CoolFan™ hydrostatic pump and filter cooling system partner with wheel motors for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

5.5-inch deep 52-inch DuraMax® contour-cut decks, with anvil-edged design for exceptional durability, and the 4.5-inch deep 48-inch decks easily convert from wide-pattern side discharge to optional mulching or vacuum collection systems.

Change cutting height easily with the flip of the PowerFold® deck switch. Use the same switch to electrically fold up the deck for storage and easy maintenance.

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar support and coil-spring suspension keeps the operator comfortably in control for all-day comfort.

ComfortReach™ provides 2 inches of adjustment at the base of the lever for a custom steering fit.

Quickly attach a wide range of seasonal implements with the exclusive QuikConverter™ Implement System to save time and labor on all your jobs.

Mowing speeds up to 8.5 MPH
 and 4.02 acres/hr. based on
 52" cutting width*
 For more details visit:
grasshoppermower.com/acres



OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- » Down Discharge™ mulching packages
- » Speed-Trimming™ heavy-duty roller (52") (Pg. 8)
- » LED work lights (Pg. 38)
- » Full-flotation deck inserts (Pg. 13)
- » Taller steering levers
- » QuikAjust Tilt™ steering levers with "no tools" 9-in. comfort range (Pg. 5)
- » Big Boy wide-seat conversion kit
- » Premier suspension seat (Pg. 5)
- » Adjustable cup holder
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 22 x 11-12 Airless Turf Tires (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Tail Wheels (Pg. 38)
- » QuikConverter™ implements (Pg. 18)
- » Yellow beacon light (Pg. 21)
- » Multiple tail wheel options (Pg. 12)
- » Performance package including bar tread, low-pressure tires and wide-stance single-fork tail wheels
- » QuikConverter™ implement capability with wiring harness (Pg. 18)
- » PowerFold® height adjustment switch on armrest
- » Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- » Side discharge control kit (Pg. 8)
- » Air Dam kit – for dry, dusty conditions (Pg. 17)

Be more productive with the addition of a PowerVac™ Collection System or other implements. Ask for specifications or visit grasshoppermower.com/implements.
 Models may be shown with optional equipment. *Actual results may vary. †See warranty card for details

AIR-COOLED 600 SERIES - SPECIFICATIONS

MODEL	623T
ENGINE	
Type/Displacement/Cylinders	
Kohler Command Pro / 42.4 cu. in. (694cc) / V-Twin	●
Crankshaft/Cooling System	
Horizontal / Air	●
Fuel/Capacity	
Gasoline - unleaded / 4.0 U.S. Gal. (15.1 l)	●
Air Cleaner	
Heavy-duty, remote-mounted engine air cleaner with replaceable element	●
STARTER & ELECTRICAL SYSTEM	
Maintenance-Free Battery/Charging Capacity/Starter	
12 volt/15 amp/solenoid shift	●
Ignition	
Breakerless	
Interlock System	
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	●
ULTIMATE OPERATOR STATION™	
Premium Comfort Seat	
Iso-mounted, high-back, multi-density, foam-padded Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	●
Premier Suspension Seat	○
Console-Mounted Instruments	
Low engine oil pressure and parking brake indicator lights, digital hour meter, ignition and push/pull PTO switches. Choke integrated with throttle lever.	●
Operator Protection	
Operator Protection Structure (OPS)	●
Work Lights	
LED	○
TRANSMISSION & STEERING	
Type	
T-Drive™ hydrostatic transmission with tandem 12cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, design-matched Parker high-torque wheel motors. AntiVibe Power Platform® reduces vibration for the operator.	●
Transmission Fluid/Filtration	
Grasshopper CoolTemp Hydra-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals. / Integrated, replaceable, high-efficiency, fine-particle filter.	●
Speed	
0 – 8.5 mph (0 – 13.7 kph) forward	●
0 – 5.5 mph (0 – 8.9 kph) reverse	●
Turning Radius	
True zero degree, turns within own length with counter-rotating, independently powered drive wheels. Seat is pivot point.	●
Steering	
One- or two-handed operation with ComfortReach™ adjustable Hydra-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.	●
Brakes	
Dynamic braking through hydrostatic transmission. Compression parking brake	●
Disc brakes	●
Attachment Drive	
Telescoping PTO shaft with two high-speed U-joints, Quik-D-Tatch® coupler and heavy-duty electric MagStop blade clutch/brake.	●
POWER UNIT TIRE SIZES	
Drive Wheels: 20 x 10-8, turf tread	●
Drive Wheels (4-ply rated): 21 x 11-8 bar tread	○
Tail Wheel: Single-Fork, 13 x 6.5-6 rib tread, pneumatic	●
POWER UNIT DIMENSIONS	
Width: 47.0 in. (119.4 cm)**	●
**Add 1.0 in. (2.5 cm) for bar tread tires.	
Length: 61.0 in. (155.0 cm)	●
Height (Operator Protective Structure): 63.0 in. (160.0 cm)	●
Height (seat back): 43.5 in. (110.5 cm)	●
Height (seat cushion): 26.0 in. (66.0 cm)	●
Wheelbase: 46.0 in. (116.8 cm)	●

MODEL	623T	
WEIGHT		
Uncrated: 750 lbs. (340.2 kg)	●	
CONTOUR-CUT DECKS		
Model	3348	3452
Width of cut	48 in. (121.9 cm)	52 in. (132.1 cm)
Width with deflector down	61.5 in. (156.2 cm)	65.5 in. (166.5 cm)
Width with deflector folded up	51.0 in. (129.5 cm)	55.0 in. (139.7 cm)
Width (mulching)	49.5 in. (125.7 cm)	53.5 in. (135.9 cm)
Cutting Height*	1.25 to 5.0 in. (3.2 cm to 12.7 cm)	
PowerFold®	●	●
Compatibility		
623T	●	●
Construction (Robotic-welded steel)		
Tubular 2.25-in. x 4-in. boxed members with 0.25-in. gussets. Geometrically engineered design with 7-gauge skirts withstands the brunt of commercial mowing. (3) Sentry™ spindles and a triple-strength upper deck, over 0.50-in. thick in stress zones.	●	●
Formed double thickness hardened steel truss spindle plane is 0.2391-in. – equal to 3-gauge (6.07 mm)	●	
Formed double thickness hardened steel truss spindle plane is 0.269-in. – 7.6% thicker than 0.25-in. (6.35 mm)		●
DuraMax® deck		●
Blades† (MARBAIN®, 1/4-in.)		
Tempered, alloy steel	(2) 18 in. (45.7 cm) (1) 15 in. (38.1 cm)	(3) 18 in. (45.7 cm)
†High-lift blades standard		
Sentry™ Spindle Assemblies		
Spindle head designed to eliminate fiber wrap. Machined aluminum housing. 2.5 cm (approx. 1 in.) O.D. shaft. Double bearings. Greasable from top of deck. (Deck spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion – 52-in. deck only)		
Spindle Housing – 8-in. (20.3 cm)-diameter with 6-bolt pattern		
Machined aluminum	●	●
Blade Drive		
Maintenance-free gearbox with single Kevlar® V-belt and idler arm tensioning		
Trimability		
(Outside of tire to left trim side)	3.5 in. (8.9 cm)	2.5 in. (6.4 cm)
Power Unit/Deck Length		
Deck (mowing position)	100.0 in. (254.0 cm)	101.0 in. (256.5 cm)
Deck (folded up)	80.0 in. (203.2 cm)	85.5 in. (217.2 cm)
Tire Size (4-ply rated): 9 x 3.5-4 (flat-proof)	●	●
Weight Uncrated		
Side Discharge	290 lbs. (131.5 kg)	370 lbs. (167.8 kg)
Mulching Package††	25 lbs. (11.3 kg)	29 lbs. (13.2 kg)
††Mulching package includes high-low mulching blades		

● Standard ○ Option

* 1.25" is reached with the combination of raising deck forks to top position AND moving tractor mounts lower by one set of holes. 5.0" height is reached using High Mow Kit #503289 for 52" deck.



Featured Model 623T with 52-inch DuraMax® deck

700 SERIES AIR-COOLED FRONTMOUNT™

Unexpected power
when you need it most

QuikAjust Tilt™ levers
with 9-in. adjustment range



LIMITED WARRANTY†
3 YEAR
— UNLIMITED HRS —
COMMERCIAL
4 YEAR
— 800 HRS —
RESIDENTIAL

Standard PowerFold® Electric Deck Lift. See Page 13 for more info.

725 KT

52 61

747cc, Kohler Command Pro V-Twin OHV gasoline engine

**729 BT
BIG BLOCK**

52 61 72

896cc, V-Twin OHV Vanguard Big Block gasoline engine

**735 BT
BIG BLOCK**

61 72

993cc, V-Twin OHV Vanguard Big Block gasoline engine

727T^{EFI}

52 61 72

747cc, V-Twin Kohler Command Pro, Delphi®-based closed-loop, Electronic Fuel Injection gasoline engine

Powerful and efficient with choices of Vanguard Big Block or Kohler EFI engines with horizontal crankshaft for longer performance life.

For enhanced efficiency, consider the 727T EFI with closed-loop electronic fuel injection. A wide range of benefits include decreased fuel use, reliable hot and cold weather starts, reduced engine exhaust emissions and fewer fuel-related service issues.

Versatile and productive, with power to tackle tough jobs and plenty to spare thanks to the use of exclusive design-matched T-Drive™ and T6® hydrostatic drive systems. The tandem-pump drive train is direct-coupled to the engine to transmit more power to the cutting deck or implement. The innovative AntiVibe Power Platform® isolates the engine and drive system from the operator station providing an unprecedented, vibration-free environment eliminating fatigue for the operator.

The CoolFan™ hydrostatic pump and filter cooling system partner with wheel motors for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

5.5-inch deep DuraMax® contour-cut decks with anvil-edged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection systems. A dedicated rear-discharge deck is also available.

Change cutting height easily with the flip of the PowerFold® deck switch. Use the same switch to electrically fold up the deck for storage and easy maintenance.

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar support and coil-spring suspension keeps the operator comfortably in control for all-day comfort.

QuikAjust Tilt™ steering levers with “no tools” adjustment provide a 9-inch range for maximum comfort and fit.

Quickly attach a wide range of seasonal implements with the exclusive QuikConverter™ Implement System to save time and labor on all your jobs. Power units include standard wiring harness for the addition of electric-powered implements.

Mowing speeds up to 10 MPH
and 6.55 acres/hr. based on
72" cutting width*
For more details visit:
grasshoppermower.com/acres



■ DuraMax® deck

OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- » Down Discharge™ mulching packages
- » Dedicated rear-discharge deck (Pg. 13)
- » Speed-Trimming™ heavy-duty roller (Pg. 8)
- » Hydraulic deck lift (Pg. 13)
- » LED work lights (725KT) (Pg. 38)
- » Full-flotation deck inserts (Pg. 13)
- » Taller steering levers
- » Big Boy wide-seat conversion kit
- » Premier suspension seat (Pg. 5)
- » Adjustable cup holder
- » Foldable ROPS with seat belt
- » Turf tires
- » Multiple tail wheel options (Pg. 12)
- » Flat-proof 13 x 6.5-6 tires (Pg. 38)
- » Michelin® X® Tweel® 22 x 11-12 Airless Turf Tires (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Tail Wheels (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Deck Tires (72") (Pg. 38)
- » QuikConverter™ implements (Pg. 18)
- » Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- » Yellow beacon light (Pg. 21)
- » Filter minder (729BT/735BT) (Pg. 38)
- » Air Dam kit – for dry, dusty conditions (Pg. 17)
- » QuikConverter™ implement capability with wiring harness (Pg. 18)
- » PowerFold® height adjustment switch on armrest
- » Side discharge control kit (Pg. 8)
- » Footrest riser (Pg. 5)

Be more productive with the addition of a PowerVac™ Collection System or other implements. Ask for specifications or visit grasshoppermower.com/implements. Models may be shown with optional equipment. *Actual results may vary. †See warranty card for details

AIR-COOLED 700 SERIES - SPECIFICATIONS

MODEL	725KT	727T	729BT	735BT
ENGINE				
Type/Displacement/Cylinders				
Kohler Command Pro / 45.6 cu. in. (747cc) / V-Twin	●			
Kohler Command Pro, Delphi®-based, closed-loop, Electronic Fuel Injection (EFI) / 45.6 cu. in. (747cc) / V-Twin		●		
B&S Vanguard Big Block / 54.7 cu. in. (896cc) / V-Twin			●	
B&S Vanguard Big Block / 60.6 cu. in. (993cc) / V-Twin				●
Crankshaft/Cooling System				
Horizontal / Air	●	●	●	●
Fuel/Capacity				
Gasoline - unleaded / 7.2 U.S. Gal. (27.3 l)	●	●	●	●
Air Cleaner				
Heavy-duty, remote-mounted engine air cleaner with replaceable element	●		●	●
Heavy-duty cyclonic, remote-mounted engine dual air cleaner with replaceable element		●		
STARTER & ELECTRICAL SYSTEM				
Maintenance-Free Battery/Charging Capacity/Starter				
12 volt/15 amp/solenoid shift	●			
12 volt/20 amp/solenoid shift		●	●	●
Ignition				
Breakerless	●	●	●	●
Interlock System				
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	●	●	●	●
ULTIMATE OPERATOR STATION™				
Premium Comfort Seat				
Iso-mounted, high-back, multi-density, foam-padded Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	●	●	●	●
Premier Suspension Seat	○	○	○	○
Console-Mounted Instruments				
Low engine oil pressure and parking brake warning lights, digital hour meter, work light, ignition and push/pull PTO switches. Choke integrated with throttle lever.	●		●	●
Low engine oil pressure, engine code light and parking brake warning lights, digital hour meter, ignition and push/pull PTO switches.		●		
Operator Protection/Convenience				
ROPS with seat belt	●	●	●	●
Adjustable cup holder	○	○	○	○
Work Lights				
LED	○	●	●	●
TRANSMISSION & STEERING				
Type				
T-Drive™ hydrostatic transmission with tandem 12 cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, design-matched Parker high-torque wheel motors.	●			
T6® hydrostatic transmission with tandem 16 cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, design-matched Parker high-torque wheel motors.		●	●	●
AntiVibe Power Platform® reduces vibration for the operator.	●	●	●	●
Transmission Fluid/Filtration				
Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals. / Integrated, replaceable, high-efficiency, fine-particle filter.	●	●	●	●
Speed				
0 – 9.0 mph (0 – 14.5 kph) forward	●			
0 – 10.0 mph (0 – 16.1 kph) forward		●	●	●
0 – 6.0 mph (0 – 9.7 kph) reverse	●	●	●	●
Turning Radius				
True zero degree, turns within own length with counter-rotating, independently powered drive wheels. Seat is pivot point.	●	●	●	●
Steering				
One- or two-handed operation with QuikAdjust Tilt™ dual levers with 9-inch comfort range that automatically return to neutral from either forward or reverse position.	●	●	●	●
Brakes				
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	●	●	●	●
Attachment Drive				
Telescoping PTO shaft with two high-speed U-joints, Quik-D-Tatch® coupler and heavy-duty electric MagStop blade clutch/brake.	●	●	●	●
Wiring harness for electric-powered implements	●	●	●	●

● Standard ○ Option

MODEL	725KT	727T	729BT	735BT
POWER UNIT TIRE SIZES				
Drive Wheels (4-ply rated): 22 x 11-10 bar tread, high flotation	●	●	●	●
Drive Wheels (4-ply rated): 22 x 11-10, turf tread	○	○	○	○
Tail Wheel: Wide-Stance, Single-Fork, 13 x 6.5-6 rib tread, pneumatic (2)	●	●	●	●
Tail Wheel: Single-Fork, 13 x 6.5-6 rib tread, pneumatic	○	○	○	○
POWER UNIT DIMENSIONS				
Width: 50.0 in. (127.0 cm)	●	●	●	●
Length: 67.0 in. (170.2 cm)	●	●	●	●
Height (ROPS): 69.0 in. (175.3 cm)	●	●	●	●
Height (seat back/seat cushion): 46.0 in. (116.8 cm) / 30.5 in. (77.5 cm)		●		
Height (seat back/seat cushion): 47.0 in. (119.4 cm) / 30.5 in. (77.5 cm)	●		●	●
Wheelbase: 51.5 in. (130.8 cm)	●	●	●	●
WEIGHT				
Uncrated: 890 lbs. (403.7 kg)	●			
Uncrated: 915 lbs. (415 kg)		●		
Uncrated: 930 lbs. (421.8 kg)			●	●
DURAMAX® CONTOUR-CUT DECKS				
Model	3452	3661	3472	
Width of cut	52 in. (132.1 cm)	61 in. (154.9 cm)	72 in. (182.9 cm)	
Width with deflector down	65.5 in. (166.5 cm)	74.5 in. (189.2 cm)	85.5 in. (227.3 cm)	
Width with deflector folded up	55.0 in. (139.7 cm)	64.0 in. (162.6 cm)	75.0 in. (190.5 cm)	
Width (mulching)	53.5 in. (135.9 cm)	62.5 in. (158.8 cm)	73.5 in. (186.7 cm)	
Cutting Height*	1.25 to 5.0 in. (3.2 cm to 12.7 cm)			
PowerFold®	●	●	●	
Compatibility				
725KT	●	●		
727T	●	●		●
729BT	●	●		●
735BT		●		●
Construction (Robotic-welded steel)				
Tubular 2.25 in. x 4 in. boxed members with 0.25 in. gussets. Formed double thickness hardened steel (0.269 in. – 7.6% thicker than 0.25 in. (6.35 mm) truss spindle plane and (3) Sentry™ spindles and a triple-strength upper deck, over 1/2 in. thick in stress zones. Geometrically engineered design with 7 gauge skirts withstands the brunt of commercial mowing.				
Blades† (MARBAIN®, 1/4-in.)				
Tempered, alloy steel	(3) 18 in. (45.7 cm)	(3) 21 in. (53.3 cm)	(3) 25 in. (63.5 cm)	
†High-lift blades standard				
Spindle Assemblies				
2.5 cm (approx. 1 in.) O.D. shaft. Double bearings. Greasable from top of deck. Deck spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.				
Spindle Housing – 8 in. (20.3 cm)-diameter with 6 bolt pattern				
Machined aluminum	●	●	●	
Blade Drive				
Maintenance-free gearbox with single Kevlar® V-belt and idler arm tensioning.				
Trimability				
(outside of tire to left trim side)	1.0 in. (2.5 cm)	8.5 in. (21.6 cm)	13.75 in. (34.9 cm)	
Power Unit/Deck Length				
Deck (mowing position)	105.5 in. (268.0 cm)	109.5 in. (278.1 cm)	117.5 in. (298.5 cm)	
Deck (folded up)	88.5 in. (224.8 cm)	91.0 in. (231.1 cm)	104.0 in. (264.2 cm)	
Tire Size (4-ply rated): 9 x 3.5-4 (flat-proof)	●			
Tire Size (4-ply rated): 11 x 4-5 (flat-proof)		●		
Tire Size (4-ply rated): 13 x 6.5-6 (rib tread pneumatic)			●	
Weight Uncrated				
Side Discharge:	370 lbs. (167.8 kg)	420 lbs. (190.5 kg)	545 lbs. (247.2 kg)	
Mulching Package††	29 lbs. (13.2 kg)	36 lbs. (16.3 kg)	44 lbs. (20.0 kg)	
††Mulching package includes high-low mulching blades				
* 1.25" is reached with the combination of raising deck forks to top position AND moving tractor mounts lower by one set of holes. 5.0" height is reached using High Mow Kit #503289 for 52" & 61" decks, or #503287 for 72" deck.				

700 SERIES LIQUID-COOLED FRONTMOUNT™

Power and versatility that expand your capabilities

LIMITED WARRANTY†
3 YEAR
 — UNLIMITED HRS —
 COMMERCIAL
4 YEAR
 — 800 HRS —
 RESIDENTIAL



QuikAdjust Tilt™ levers with 9-in. adjustment range

Standard PowerFold® Electric Deck Lift. See Page 13 for more info.

Designed for speed and durability, offering the powerful performance of a 3-cylinder Kubota gasoline or EPA Tier 4 Final-compliant diesel engine to master a wide range of grounds maintenance jobs and give you more savings opportunities. DuraMax® decks up to 72 inches deliver a manicured cut and let you cover more ground in less time, while a complete line of efficient snow removal and turf renovation implements work year-round.

The horizontal crankshaft configuration adds performance life to the engine.

Design-matched T6® hydrostatic drive systems with AntiVibe Power Platform®, direct more power to the cutting deck and eliminate vibration. The CoolFan™ hydrostatic pump and filter cooling system partner with wheel motors for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

5.5-inch deep DuraMax® contour-cut decks with anvil-edged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection systems. A dedicated rear-discharge deck is also available.

Change cutting height easily with the flip of the PowerFold® deck switch. Use the same switch to electrically fold up the deck for storage and easy maintenance.

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar support and coil-spring suspension keeps the operator comfortably in control for all-day comfort. An electronic fuel gauge/hour meter and two USB charging ports on the console, and an adjustable cup holder to make it convenient to tote along your favorite beverage.

QuikAdjust Tilt™ steering levers with “no-tools” adjustment provide a 9-inch range for maximum comfort and fit.

Quickly attach a wide range of seasonal implements with the exclusive QuikConverter™ Implement System to save time and labor on all your jobs. Power units include standard wiring harness for the addition of electric-powered implements.

729T

52 61 72

962cc, 3-cylinder MaxTorque™ gasoline engine
 T6® hydrostatic transmission

725DT

52 61 72

898cc, 3-cylinder MaxTorque™ Clean Diesel engine;
 T6® hydrostatic transmission

■ DuraMax® deck

Mowing speeds up to 10 MPH and 6.55 acres/hr. based on 72" cutting width*
 For more details visit: grasshoppermower.com/acres



OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- » Down Discharge™ mulching packages
- » Dedicated rear-discharge deck (Pg. 13)
- » Speed-Trimming™ heavy-duty roller (Pg. 8)
- » Hydraulic deck lift (Pg. 13)
- » Full-flotation deck inserts (Pg. 13)
- » Taller steering levers
- » Big Boy wide-seat conversion kit
- » Premier suspension seat (Pg. 5)
- » Foldable ROPS with seat belt
- » Multiple tail wheel options (Pg. 12)
- » Turf tires
- » Michelin® X® Tweel® 22 x 11-12 Airless Turf Tires (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Tail Wheels (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Deck Tires (72") (Pg. 38)
- » Flat-proof 13 x 6.5-6 tires (Pg. 38)
- » QuikConverter™ implements (Pg. 18)
- » Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- » Yellow beacon light (Pg. 21)
- » Filter minder (Pg. 38)
- » QuikConverter™ implements (Pg. 18)
- » Tine-Rake Dethatcher
- » PowerFold® height adjustment switch on armrest
- » Radiator cleaning wand (Pg. 7)
- » Block heater
- » Side discharge control kit (Pg. 8)
- » Air Dam kit – for dry, dusty conditions (Pg. 17)
- » Footrest riser (Pg. 5)

LIQUID-COOLED 700 SERIES - SPECIFICATIONS

MODEL	725DT	729T
ENGINE		
Type/Displacement/Cylinders		
Kubota MaxTorque™ / 54.8 cu. in. (898cc) / 3-cyl.	●	
Kubota MaxTorque™ / 58.7 cu. in. (962cc) / 3-cyl.		●
Crankshaft/Cooling System		
Horizontal / Liquid	●	●
Fuel/Capacity		
Diesel - No. 2 / 8.0 U.S. Gal. (30.3 l)	●	
Gasoline - unleaded / 7.2 U.S. Gal. (27.3 l)		●
Air Cleaner		
Heavy-duty, remote-mounted engine air cleaner with replacement element	●	●
STARTER & ELECTRICAL SYSTEM		
Maintenance-Free Battery/Charging Capacity/Starter		
12 volt/40 amp/solenoid shift	●	●
Ignition		
Breakerless		●
Diesel quick heat glow plug	●	
Interlock System		
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	●	●
ULTIMATE OPERATOR STATION™		
Premium Comfort Seat		
Iso-mounted, high-back, multi-density, foam-padded Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	●	●
Premier Suspension Seat	○	○
Foldable armrests	●	●
Console-Mounted Instruments		
Low engine oil pressure, alternator, temperature and parking brake warning lights, engine temperature and volt gauges, electronic fuel gauge/hour meter, two USB charging ports, work light, ignition, glow plug and push/pull PTO switches.	●	
Low engine oil pressure, alternator, temperature and parking brake warning lights, engine temperature and volt gauges, electronic fuel gauge/hour meter, two USB charging ports, work light, ignition and push/pull PTO switches. Choke integrated with throttle lever.		●
Operator Protection		
ROPS with seat belt	●	●
Operator Convenience		
Adjustable cup holder	●	●
Work Lights		
LED	●	●
TRANSMISSION & STEERING		
Type		
T ⁶ hydrostatic transmission with tandem 16 cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, design-matched Parker high-torque wheel motors.	●	●
AntiVibe Power Platform® reduces vibration for the operator.	●	●
Transmission Fluid/Filtration		
Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals. / Integrated, replaceable, high-efficiency, fine-particle filter.	●	●
Speed		
0 – 10.0 mph (0 – 16.1 kph) forward	●	●
0 – 6.0 mph (0 – 9.7 kph) reverse	●	●
Turning Radius		
True zero degree, turns within own length with counter-rotating, independently powered drive wheels. Seat is pivot point.	●	●
Steering		
One- or two-handed operation with QuikAdjust Tilt™ dual levers with 9-inch comfort range that automatically return to neutral from either forward or reverse position.	●	●
Brakes		
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	●	●
Attachment Drive		
Telescoping PTO shaft with two high-speed U-joints, Quik-D-Tatch® coupler and heavy-duty electric MagStop blade clutch/brake.	●	●
Temperature Sentry/high temperature clutch cut-out	●	●
Wiring harness for electric-powered implements	●	●

MODEL	725DT	729T	
POWER UNIT TIRE SIZES			
Drive Wheels (4-ply rated): 22 x 11-10 bar tread, high flotation	●	●	
Drive Wheels (4-ply rated): 22 x 11-10, turf tread	○	○	
Tail Wheel: Wide-Stance, Single-Fork, 13 x 6.5-6 rib tread, pneumatic (2)	●	●	
POWER UNIT DIMENSIONS			
Width: 50.0 in. (127.0 cm)	●	●	
Length: 67.0 in. (170.2 cm)	●	●	
Height (ROPS): 69.0 in. (175.3 cm)	●	●	
Height (seat back/seat cushion): 46.0 in. (116.8 cm) / 30.5 in. (77.5 cm)	●	●	
Wheelbase: 51.5 in. (130.8 cm)	●	●	
WEIGHT			
Uncrated: 1000 lbs. (453.6 kg)	●	●	
DURAMAX® CONTOUR-CUT DECKS			
Model	3452	3661	3472
Width of cut	52 in. (132.1 cm)	61 in. (154.9 cm)	72 in. (182.9 cm)
Width with deflector down	65.5 in. (166.5 cm)	74.5 in. (189.2 cm)	85.5 in. (227.3 cm)
Width with deflector raised	55.0 in. (139.7 cm)	64.0 in. (162.6 cm)	75.0 in. (190.5 cm)
Width (mulching)	53.5 in. (135.9 cm)	62.5 in. (158.8 cm)	73.5 in. (186.7 cm)
Cutting Height*	1.25 to 5.0 in. (3.2 cm to 12.7 cm)		
PowerFold®	●	●	●
Compatibility			
725DT	●	●	●
729T	●	●	●
Construction (Robotic-welded steel)			
Tubular 2.25 in. x 4 in. boxed members with 0.25 in. gussets. Formed double thickness hardened steel (0.269 in. – 7.6% thicker than 0.25 in. (6.35 mm) truss spindle plane and (3) Sentry™ spindles and a triple-strength upper deck, over 1/2 in. thick in stress zones. Geometrically engineered design with 7 gauge skirts withstands the brunt of commercial mowing.			
Blades† (MARBAIN®, 1/4-in.)			
Tempered, alloy steel	(3) 18 in. (45.7 cm)	(3) 21 in. (53.3 cm)	(3) 25 in. (63.5 cm)
†High-lift blades standard			
Spindle Assemblies			
2.5 cm (approx. 1 in.) O.D. shaft. Double bearings. Greasable from top of deck.			
Deck spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.			
Spindle Housing – 8 in. (20.3 cm)-diameter with 6 bolt pattern			
Machined aluminum	●	●	●
Blade Drive			
Maintenance-free gearbox with single Kevlar V-belt and idler arm tensioning.			
Trimability			
(outside of tire to left trim side)	1.0 in. (2.5 cm)	8.5 in. (21.6 cm)	13.75 in. (34.9 cm)
Power Unit/Deck Length			
Deck (mowing position)	105.5 in. (268.0 cm)	109.5 in. (278.1 cm)	117.5 in. (298.5 cm)
Deck (folded up)	88.5 in. (224.8 cm)	91.0 in. (231.1 cm)	104.0 in. (264.2 cm)
Tire Size (4-ply rated): 9 x 3.5-4 (flat-proof)	●		
Tire Size (4-ply rated): 11 x 4-5 (flat-proof)		●	
Tire Size (4-ply rated): 13 x 6.5-6 (rib tread, pneumatic)			●
Weight Uncrated			
Side Discharge:	370 lbs. (167.8 kg)	420 lbs. (190.5 kg)	545 lbs. (247.2 kg)
Mulching Package††	29 lbs. (13.2 kg)	36 lbs. (16.3 kg)	44 lbs. (20.0 kg)
††Mulching package includes high-low mulching blades			

● Standard ○ Option

* 1.25" is reached with the combination of raising deck forks to top position AND moving tractor mounts lower by one set of holes. 5.0" height is reached using High Mow Kit #503289 for 52" & 61" decks, or #503287 for 72" deck.



Featured Model 729T with 61-inch DuraMax® deck

900 SERIES AIR- AND LIQUID-COOLED FRONTMOUNT™

The ultimate Contour-Cut FrontMount™ performer

QuikAdjust Tilt™ levers with 9-in. adjustment range



LIMITED WARRANTY†
3 YEAR
 — UNLIMITED HRS —
 COMMERCIAL
4 YEAR
 — 800 HRS —
 RESIDENTIAL

Standard PowerFold® Electric Deck Lift.
 See Page 13 for more info.

The 900 Series mowers deliver more power, durability and maneuverability than any mower in its class. They are equipped with a choice of three engines: fuel-efficient, Tier 4-compliant clean diesel; 3-cylinder gasoline; or twin-cylinder, closed-loop, electronic-fuel-injection (EFI) gasoline. Perfect for fleet operations, these mowers combine True ZeroTurn™ maneuverability with a quality cut and versatile performance. DuraMax® decks deliver a manicured cut and let you cover more ground in less time, while a complete line of efficient snow removal and turf renovation implements work year-round.

The horizontal crankshaft configuration with uniform cooling, airflow and internal lubrication adds performance life to the engine.

Robust 21cc G3 pump-and-wheel motor systems are design-matched for Grasshopper mowers. They feature CoolFan™ cooling systems and 7-micron absolute filters. The pumps are driven by a single flat and serpentine, grooved belt. These features ensure smooth and responsive steering, less maintenance and 1,000-hour fluid change intervals.

Excellent weight distribution provides a smoother ride and lighter footprint. A hydraulic deck lift (optional on the 937 EFI) simplifies implement operation and transport.

5.5-inch deep DuraMax® contour-cut decks feature anvil-edged design for exceptional durability and easily convert from wide-pattern side discharge to optional mulching or vacuum collection systems. A dedicated rear-discharge deck is also available.

Change cutting height easily with the flip of the PowerFold® deck switch. Use the same switch to electrically fold up the deck for storage and easy maintenance.

The deep-cushioned Premium Comfort Seat is embroidered with the Grasshopper logo and features CoolTemp Cordura® with lumbar support and coil-spring suspension to keep the operator comfortably in control for all-day comfort. Adjustable cup holders let you tote along your favorite beverage. All models feature an electronic fuel gauge/hour meter on the console and two USB charging ports.

QuikAdjust Tilt™ steering levers with “no tools” adjustment provide a 9-inch range for maximum comfort and fit.

Quickly attach a wide range of seasonal implements with the exclusive QuikConverter™ Implement System to save time and labor on all your jobs. Power units include standard wiring harness for the addition of electric-powered implements.

900 D 1.3L

61 72

1.3L, 3-cylinder, liquid-cooled MaxTorque™ Clean Diesel engine with horizontal crankshaft

932

61 72

962cc, 3-cylinder, liquid-cooled MaxTorque™ gasoline engine with horizontal crankshaft

**937 EFI
BIG BLOCK**

61 72

993cc, V-Twin Vanguard Big Block horizontal crankshaft EFI gasoline engine

Mowing speeds up to 11 MPH and 7.20 acres/hr. based on 72" cutting width*

For more details visit: grasshoppermower.com/acres



► DuraMax® deck

OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- » Down Discharge™ mulching packages
- » Dedicated rear-discharge deck (Pg. 13)
- » Speed-Trimming™ heavy-duty roller (Pg. 8)
- » Hydraulic deck lift (937) (Pg. 13)
- » Taller steering levers
- » Big Boy wide-seat conversion kit
- » Premier suspension seat (Pg. 5)
- » Full-flotation deck inserts (Pg. 13)
- » Foldable ROPS with seat belt
- » Turf tread tires
- » Multiple tail wheel options (Pg. 12)
- » Flat-proof 13 x 6.5-6 tires (Pg. 38)
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Tail Wheels (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Deck Tires (72") (Pg. 38)
- » Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- » Side discharge control kit (Pg. 8)
- » Air Dam kit – for dry, dusty conditions (Pg. 17)
- » Yellow beacon light (Pg. 21)
- » Filter Minder (937) (Pg. 38)
- » PowerFold® height adjustment switch
- » Radiator cleaning wand (900D and 932) (Pg. 7)
- » Engine block heater (900D and 932)
- » Footrest riser (Pg. 5)

900 SERIES AIR- AND LIQUID-COOLED FRONTMOUNT™ - SPECIFICATIONS

MODEL	900D	932	937
ENGINE			
Type/Displacement/Cylinders			
Kubota MaxTorque™ diesel / 77.0 cu. in. (1.3L) / 3-cyl.	●		
Kubota MaxTorque™ gasoline / 58.7 cu. in. (962 cc) / 3-cyl.		●	
Vanguard Big Block, closed-loop, Electronic Fuel Injection (EFI) / 60.6 cu. in. (993cc) / V-twin			●
Crankshaft/Cooling System			
Horizontal with uniform cooling, airflow and internal lubrication / Liquid	●	●	
Horizontal with uniform cooling, airflow and internal lubrication / Air			●
Fuel/Capacity			
Diesel - No. 2 / 8.0 U.S. Gal. (30.3L)	●		
Gasoline - unleaded / 7.2 U.S. Gal. (27.3 l)		●	
Gasoline - unleaded / 14.4 U.S. Gal. (54.5 l) – twin 7.2-gal. (27.3 l) tanks with fuel selector			●
Air Cleaner			
Heavy-duty, remote mounted engine air cleaner with replaceable element and filter minder.	●	●	
Heavy-duty, remote mounted engine air cleaner with replaceable element.			●
STARTER & ELECTRICAL SYSTEM			
Maintenance-Free Battery/Charging Capacity/Starter			
12 volt/20 amp/solenoid shift			●
12 volt/40 amp/solenoid shift	●	●	
Ignition			
Breakerless		●	●
Diesel quick heat glow plug	●		
Interlock System			
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	●	●	●
ULTIMATE OPERATOR STATION™			
Premium Comfort Seat			
Iso-mounted, high-back, multi-density, foam-padded Cordura®-covered, padded foldable arms, padded backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	●	●	●
Premier Suspension Seat	○	○	○
Suspension			
InFrame™ suspension	●	●	●
Console-Mounted Instruments			
Low engine oil pressure, alternator, temperature and parking brake warning lights, engine temperature and volt gauges, electronic fuel gauge/hour meter, two USB charging ports, work light, ignition, glow plug and push/pull PTO switches.	●		
Low engine oil pressure, alternator, temperature and parking brake warning lights, engine temperature and volt gauges, electronic fuel gauge/hour meter, two USB charging ports, work light, ignition and push/pull PTO switches. Choke integrated with throttle lever.		●	
Low engine oil pressure, engine code light and parking brake warning lights, electronic fuel gauge/hour meter, two USB charging ports, work light, ignition and push/pull PTO switches.			●
Operator Protection			
ROPS with seat belt	●	●	●
Operator Convenience			
Adjustable cup holder	●	●	●
Work Lights			
LED	●	●	●
TRANSMISSION & STEERING			
Type			
Rugged, design-matched G3 hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 21 cc piston-type pumps and Parker wheel motors. Single serpentine belt for more efficient power transfer to the drive.	●	●	●
Transmission Fluid/Filtration			
Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals. / 7 micron absolute, spin-on.	●	●	●
Speed			
0 – 11.0 mph (0 – 17.7 kph) forward	●	●	●
0 – 6.0 mph (0 – 9.7 kph) reverse	●	●	●
Turning Radius			
True zero degree, turns within own length with counter-rotating, independently powered drive wheels. Seat is pivot point.	●	●	●
Steering			
One- or two-handed operation with QuikAdjust Tilt™ dual levers with 9-inch comfort range that automatically return to neutral from either forward or reverse position.	●	●	●
Hydraulic Deck/Implement Lift switch integrated in right steering lever.	●	●	○
Brakes			
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	●	●	●

MODEL	900D	932	937
Attachment Drive			
Telescoping, splined PTO shaft with two high-speed U-joints, Quik-D-Tatch® coupler and heavy-duty electric MagStop® blade clutch/brake.	●	●	●
Temperature Sentry/high temperature clutch cut-out	●	●	
Wiring harness for electric-powered implements	●	●	●
POWER UNIT TIRE SIZES			
Drive Wheels (4-ply rated): 24 x 12-12 bar tread, high flotation	●	●	●
Drive Wheels (4-ply rated): 24 x 12-12, turf tread	○	○	○
Tail Wheel: Wide-Stance, Single-Fork, 13 x 6.5-6 rib tread, pneumatic (2)	●	●	●
POWER UNIT DIMENSIONS			
Width: 54.5 in. (138.4 cm)	●	●	●
Length: 70.0 in. (177.8 cm)	●	●	●
Height (ROPS): 69.5 in. (176.5 cm)	●	●	●
Height (seat back/seat cushion): 47.0 in. (119.4 cm)/ 31.5 in. (80.0 cm)	●	●	
Height (seat back/seat cushion): 49.0 in. (124.5 cm)/ 32 in. (81.3 cm)			●
Wheelbase: 54.5 in. (138.4 cm)	●	●	●
WEIGHT			
Uncrated: 1150 lbs. (521.6 kg)		●	
Uncrated: 1100 lbs. (499.0 kg)			●
Uncrated: 1140 lbs. (517.1 kg)			●
DURAMAX® CONTOUR-CUT DECKS			
Model	3661	3472	
Width of cut	61 in. (154.9 cm)	72 in. (182.9 cm)	
Width with deflector down	74.5 in. (189.2 cm)	85.5 in. (227.3 cm)	
Width with deflector raised	64.0 in. (162.6 cm)	75.0 in. (190.5 cm)	
Width (mulching)	62.5 in. (158.8 cm)	73.5 in. (186.7 cm)	
Cutting Height*	1.25 to 5.0 in. (3.2 cm to 12.7 cm)		
PowerFold®	●	●	
Compatibility			
900D	●		●
932	●		●
937	●		●
Construction (Robotic-welded steel)			
Tubular 2.25 in. x 4 in. boxed members with 0.25 in. gussets. Formed double thickness hardened steel (0.269 in. – 7.6% thicker than 0.25 in. (6.35 mm) truss spindle plane and (3) Sentry™ spindles and a triple-strength upper deck, over 1/2 inch thick in stress zones. Geometrically engineered design with 7 gauge skirts withstands the brunt of commercial mowing.			
Blades† (MARBAIN®, 1/4-in.)			
Tempered, alloy steel	(3) 21 in. (53.3 cm)	(3) 25 in. (63.5 cm)	
†High-lift blades standard			
Spindle Assemblies			
2.5 cm (approx. 1 in.) O.D. shaft. Double bearings. Greasable from top of deck.			
Deck spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion. Machined aluminum alloy housing.			
Spindle Housing – 8 in. (20.3 cm)-diameter with 6 bolt pattern			
Machined aluminum	●		●
Blade Drive			
Maintenance-free gearbox with single Kevlar® V-belt and idler arm tensioning.			
Trimability			
(outside of tire to left trim side)	6.25 in. (15.9 cm)	12.25 in. (31.1 cm)	
Power Unit/Deck Length			
Deck (mowing position)	112.5 in. (285.8 cm)	120.5 in. (306.1 cm)	
Deck (folded up)	94.0 in. (238.8 cm)	107.0 in. (271.8 cm)	
Tire Size (4-ply rated): 11 x 4-5 (flat-proof)	●		
Tire Size (4-ply rated): 13 x 6.5-6 (rib tread, pneumatic)		●	
Weight Uncrated			
Side Discharge	445 lbs. (201.8 kg)	545 lbs. (247.2 kg)	
Mulching Package††	36 lbs. (16.3 kg)	44 lbs. (20.0 kg)	
††Mulching package includes high-low mulching blades			
● Standard ○ Option			
* 1.25" is reached with the combination of raising deck forks to top position AND moving tractor mounts lower by one set of holes. 5.0" height is reached using High Mow Kit #503289 for 61" deck, or #503287 for 72" deck.			

DON'T SETTLE FOR LESS THAN GENUINE OEM PARTS

Genuine Grasshopper replacement parts are machined to precise tolerances with the latest robotics and laser technologies. Our suppliers are held to the same rigorous standards.



MAXLIFE™ BELTS

Every MaxLife™ belt is designed to specific material, dimension, shape, construction and pliability standards that ensure superior performance and long life. Simply finding an aftermarket belt of the same length won't deliver the same results.



TIRE SEALANT

Premium twin-fiber tire sealant for drive tires helps avoid leaks and flats from tread punctures for the life of the tires.



COOLTEMP HYDRO-MAX™ TRANSMISSION FLUID

Designed to maximize the service life of critical transmission components and minimize fluid and filter change intervals, CoolTemp Hydro-Max™ fluid allows up to 1,000 hours between fluid changes and delivers maintenance costs as low as 7 cents per hour.



ENGINE FILTERS

Dust is an engine's worst enemy. Using anything other than a genuine OEM filter can allow dust to enter and cause premature wear – and potential engine failure.

DRIVE SYSTEM FILTERS

Grasshopper uses fine-particle filtration systems to extend the service life of your drive system. Most aftermarket filters are designed to capture only half of larger 10 to 40 micron particles.



WEATHER COVER

Weather-resistant, black Cordura® fabric cover with embroidered Grasshopper logo keeps seat and engine area protected during storage or between movings. The cover slips over the ROPS and closes with Velcro to secure the opening.



FILTER MINDER

Alerts the operator when airflow is restricted in the air canister on dual-element air filters.

Available on all models with heavy-duty, remote-mounted, canister-type air cleaners. Standard on 400 and 900 Series model.


ACCESSORIES ENHANCE PERFORMANCE

Ask your dealer about other accessories to maximize the performance of your Grasshopper.



SUNSHADE CANOPY

Diamond-plated aluminum or heavy-duty vinyl Sunshade Canopy mounts on ROPS to limit operator exposure to direct sunlight and heat, reduce eye strain and increase operator comfort while providing plenty of headroom. Optional fan and LED light kits available.



FLAT-PROOF TIRES

Semi-pneumatic, flat-proof tires for MidMount™ front tires or FrontMount™ tail wheels are designed to never go flat.



WORK LIGHTS

LED lights available as an option for all 200/300 Series MidMount™ models and FrontMount™ models 623T and 725KT. Standard on all other models.



MICHELIN® X® TWEEL® TIRES

Optional airless 22 x 11-12 or 24 x 12-12 turf drive tires and 13 x 6.5-6 tail and 72" deck wheels perform like pneumatic tires but without the inconvenience associated with flat tires.

These tires may be used with PowerVac™ Collection Systems subject to weight restrictions.

All specifications and information contained herein are subject to change without notice. Models may be shown with optional equipment. Access-Eze, CleanSweep, ClearView, ComfortReach, CoolFan, CoolTemp Hydro-Max, Down Discharge, DriftBuster, DuraFlex, DuraGuard, Edge-EZE, exoSkeletal, 4X Rear Discharge, FrontMount, GrassMax, HighLift, Hydra-Smooth, InFrame, Little Bully, MaxLife, MaxTorque, MidMount, Multi-Point Suspension, One Pass Perfection, PowerVac, QuikAjust DropPin, QuikAjust Tilt, QuikConverter, Ratchet-Eze, Sentry, SmartFrame, Speed-Trimming, T-Drive, True ZeroTurn, Ultimate Operator Station, Ultimate Suspension Ride, USR and Vigilant Operator Presence System are trademarks and Grasshopper, the Grasshopper logo, AntiVibe Power Platform, DuraMax, First to Finish ... Built to Last, It's So Much Mower, MaxTrax, PowerFold, Quik-D-Tatch and T² are registered trademarks of Morigade Manufacturing, Inc., dba The Grasshopper Company. All other products are trademarks or registered trademarks of their respective holders. For a complete list of trademarks/registered trademarks, visit grasshoppermower.com/legal.

The right deck to fit your application. A wide range of deck sizes helps you tailor your Grasshopper True ZeroTurn™ mower to your needs. Whether you're cutting in tight spaces or making the most of wide open ones, our decks can deliver a great cut right along with the speed and volume you're looking for.



Actual results may vary based on conditions. Visit grasshoppermower.com/acres for details.

		Dedicated Rear Discharge Deck	PowerVac™ Collection System	HighLift™ 158	Remote Vac™	40" AERA-vator™	60" AERA-vator™	Denharcter	48" Snowblowers	48" Rotary Blowers	68" Dazzle Blades	60" V-Blow	60" Snowblowers	60" Rotary Blowers	60" Dazzle Blades	Edge-EZE™ Edger	SprayJet	53" Staked Sprayer	1.33' Staked Turbine Blower	Winter Enclosure (Aluminum Only)	Sunshade Canopy (Aluminum Only)	Winter Enclosure*	
MidMount™	200 Series	●	●														●	●			●		
	300 Series	●	●														●	●			●		
	400 Series	●	●														●	●			●		
FrontMount™	600 Series			●	●	●		●		●							●	●	●		●	●	
	700 Series	●	●	●	●	●	●	●		●			●				●	●	●	●	●	●	●
	900 Series	●	●	●	●	●	●	●		●			●				●	●	●	●	●	●	●

Ask your dealer for specifications on any models or implements or visit grasshoppermower.com/implements. Always consult manual for counterweight requirements when adding an implement.

* Winter enclosure is not for mowing or turf care applications. Heater available on liquid-cooled models.



Committed to the Cut.®

FIRST TO FINISH...BUILT TO LAST.®

Since the first Grasshopper rolled off the line in 1969, our goal has remained the same: to manufacture a mower that will produce a perfect cut day after day and retain its value as a re-sellable asset. By employing a skilled workforce using smart engineering, design-matched components and cutting-edge manufacturing technology, we build long-lasting equipment that stands up to rigorous demands. Call it Midwestern values or just good business sense. At Grasshopper, there's a constant pursuit of perfection. Perfection in the details. Perfection in the cut. It's our passion, because it's your passion, too.

Every mower is designed, engineered and assembled in Moundridge, Kansas, USA, and we run each one before it's shipped as a final quality assurance check. This attention to detail has earned a 99 percent approval rating from Grasshopper owners, and reflects the company's drive to be both innovative and responsive to our customers – turf care professionals, government entities and equipment owners from across America and around the world.

The Grasshopper Company takes pride in designing products and using production methods that respect the environment. Awarded for its pollution prevention practices, Grasshopper's computer-aided design and advanced manufacturing techniques ensure little goes to waste in the creation of Your Next Mower. With our focus on fuel-efficient power units and time-saving operation, you can take pride in creating the aesthetic and ecological advantages that well-maintained lawns are proven to provide.

EXPERIENCE THE DIFFERENCE FOR YOURSELF.

Visit GrasshopperDealers.com to find a dealer near you or schedule a demonstration.



The Grasshopper Company | 105 Old U.S. Highway 81
P.O. Box 637 | Moundridge, KS | 67107 U.S.A.
T: 620-345-8621 | GrasshopperMower.com



Litho in U.S.A. Form 0121-170470 ©2021 The Grasshopper Company

⚠ WARNING: California Proposition 65 Cancer and Reproductive Harm – www.P65Warnings.ca.gov