

SERIES


Images may not be representative of the Australian production model.

Specification Guide

NPR 45/65-175

NPR 45/65-175 CREW

Weight Ratings

GVM	4,500 kg / 6,500 kg
GCM ¹ (with MT)	9,000 kg / 10,000 kg
GCM ¹ (with DT)	8,000 kg
Towing Capacity ¹ (at 4,500kg GVM rating)	4,500 kg

Engine

Power	129 kW @ 2,860 rpm
Torque	430 Nm @ 1,450 - 2,860 rpm

Transmissions

9-speed Dual-clutch Transmission (DT)
6-speed Manual Transmission (MT)

Wheelbase

2,795 mm
3,395 mm
4,260 mm

Key Features

- ADR 80/04 (pPNLT) Compliant
- Automatic Lighting System (ALS)
- Bi-LED Headlamps with Daytime Running Lamps (DRL)
- Driver Suspension Seat (Day cab)
- ECE-R29 cab with side anti-intrusion beams
- Electric Park Brake (EPB) with Auto Brake Hold
- Electronic Stability Control (ESC)
- Full speed Adaptive Cruise Control (F-ACC) (DT only)
- Lane Departure Warning (LDW)



Scan QR code to search, view and download full spec sheets for all Isuzu truck models.



Driveline


Engine

Description	Isuzu 4JZ1-TCH
Type	4 Cylinder
Power	129 kW (175 PS) @ 2,860 rpm
Torque	430 Nm @ 1,450 - 2,860 rpm
Displacement	2,999 cc
Compression Ratio	17.5:1
Bore x Stroke	95 mm x 104 mm
Induction	Electronically controlled variable nozzle turbocharger with air -to air intercooler.
Fuel Injection	Direct injection high pressure common rail system
Emission Standard	ADR 80/04 (pPNLT)
Emission Control	SCR (Selective Catalytic Reduction) DPD (Diesel Particulate Diffuser) EGR (Exhaust Gas Recirculation)
Auxiliary Brake	Vacuum controlled exhaust brake

Transmission

Description: ISUZU MYY-6Z										
Type: 6 speed Manual (MT). Synchromesh on gears 2-6.										
Ratios:										
MT	1	2	3	4	5	6	REV			
	5.97	3.43	2.04	1.37	1.00	0.70	5.70			
Power Take Off Facility: Provision on LHS of transmission case. Drive from counter gear.										
Description: Isuzu MYR-9S										
Type: 9 speed Dual-clutch Transmission (DT) with both fully automatic and clutchless manual operation modes										
Ratios:										
DT	1	2	3	4	5	6	7	8	9	REV
	5.16	3.94	2.86	2.18	1.67	1.30	1.00	0.76	0.58	4.81
Power Take Off Facility: Provision on LHS of transmission case. Drive from counter gear.										

4JZ1-TCH 175PS pPNLT



Clutch

Type: Single plate with auto adjusting hydraulic control and vacuum assistance	
MT	Clutch Plate Diameter: 325 mm
Type: Fully automated dual wet clutch and torque converter (TC) with lock up	
DT	

Performance² (calculated - typical paved road)

		Geared Speed (top gear at peak power engine rpm)	Low Speed Gradeability (lowest forward gear assuming no wheel slip)	Engine Speed (top gear at 100 km/h)
NPR 45-175 MT	At 4,500 kg GVM	122 km/h @ 2,860 rpm	65%	2,339 rpm
NPR 65-175 MT	At 6,500 kg GVM	122 km/h @ 2,860 rpm	45%	2,339 rpm
NPR 45-175 DT	At 4,500 kg GVM	132 km/h @ 2,860 rpm	63%	2,174 rpm
NPR 65-175 DT	At 6,500 kg GVM	132 km/h @ 2,860 rpm	44%	2,174 rpm

Technology & Equipment

Intelligent Safety

ACTIVE SAFETY Advanced Driver Assistance Systems (ADAS)	Advanced Emergency Braking (AEB)
	Anti-lock Braking System (ABS)
	Anti-Skid Regulator (ASR)
	Attention Alert System (AAS)
	Automatic Lighting System (ALS)
	Cab Tilt Warning (CTW)
	Cruise Control (CC)
	Distance Warning System (DWS)
	Electric Park Brake (EPB)
	Electronic Brakeforce Distribution (EBD)
	Electronic Stability Control (ESC)
	Front Cross Traffic Alert (FCTA)
	Full Speed Adaptive Cruise Control (F-ACC) (DT only)
	Intelligent Speed Limiter (ISL) (DT only)
	Intersection Emergency Braking (IEB)
	Intersection Warning System (IWS)
	Lane Departure Warning (LDW)
	Miss Acceleration Mitigation (MAM) (DT only)
	Traffic Movement Warning (TMW)
	Traffic Sign Recognition (TSR) (DT only)
PASSIVE SAFETY Cabin Occupant Safety Systems (COSS)	Door mounted cornering lamps
	Driver and front left hand passenger seatbelt pretensioners
	Driver and front passenger airbags
	ECE-R29 cab with side anti-intrusion beams
	Overhead shelf restraint netting

Accessories³

Towing	Isuzu Genuine Towbar	•
	Isuzu Trailer Wiring Kit	•
	Isuzu Electric Trailer Brake Controller Kit	•
Lights	Driving Lights	•
	Beacons	•
Protection	Isuzu Genuine Bull Bar	•
	Isuzu Seat Covers	•
	Isuzu Floor Mats	•
	Isuzu Dash Mats	•
	Isuzu Weathershields	•
	Isuzu Mudflaps	•
Technology	Isuzu Cameras	•
	Isuzu Tyre Pressure Monitoring	•
	Alarms	•
Aerodynamics	Air Deflectors	•

• Fitted as Standard • Option to Fit

Australia's no.1 truck, made more you.



Colours shown are indicative only, additional costs may apply. Availability on request only for limited models. Check with your local dealer.

Chassis

Steering

Type	Power assisted rack and pinion
Turns Lock To Lock	4.2
Wheel Lock Angle	47.5° (inside wheel) / 39.5° (outside wheel)

Suspension

Front	Type: Coil Springs
	Other Features: Double acting hydraulic shock absorbers
Rear	Type: Multi leaf main,multi leaf helper spring
	Other Features: Double acting hydraulic shock absorbers. Stabiliser bar.

Fuel and AdBlue® Tanks

Diesel Tank	Type	Frame mounted tank
	Capacity ⁴ (L)	100 (D28) 140 (D34,C42)
	Material	Steel
	Features	Lockable Cap
AdBlue® Tank	Type	Frame mounted tank
	Capacity ⁴ (L)	14
	Material	High-Density Polyethylene

Electrical Systems

Voltage (V)	24
Alternator (A)	90
Starter Motor (kw)	3.70
Battery	2 x 80D26L (600 CCA)
CAN bus Provision	FMS Provision

Chassis Frame

Type	Cold rivetted ladder frame
Material	JSH440 steel
Dimension	Side Rail (mm): 180 x 70 x 5.3 Rear frame width (mm): 750

Axle

Front	Description	Isuzu FI026
	Type	Independent wishbone
	Capacity	2,600 kg
Rear	Description	Isuzu R060
	Type	Full floating banjo with four differential pinions
	Capacity	6,000 kg
	Ratio	4.556 (MT) 5.125 (DT)

Wheels & Tyres

Front	Wheels	17.5X6.00 six stud steel
	Tyres	205/75R17.5 124/122M Michelin
	Front Axle Tyre Rating	3,200 kg
Rear	Wheels	17.5X6.00 six stud steel
	Tyres	205/75R17.5 124/122M Michelin
	Rear Axle Tyre Rating	6,000 kg
Spare	Wheels	17.5X6.00 six stud steel
	Tyres	205/75R17.5 124/122M Michelin

Brakes

Type	Ventilated disc/disc with dual circuit hydraulic control,integrated boost assist
Front Diameter (mm)	310
Rear Diameter (mm)	310
Park Brake	Electric Park Brake (EPB),drum mounted on rear of transmission.


Weights & Dimensions

Weights (kg)

Models	Ratings ⁵		Loading Limit ⁵ (at ground)		Cab Chassis Weight ⁶			Order Code
	GVM	GCM	Front	Rear	Front	Rear	Total	
NPR 45/65-175 MT D28	4,500/6,500	9,000/10,000	2,600	6,000	1,733	767	2,500	NS-NPRFC-FAS
NPR 45/65-175 MT D34	4,500/6,500	9,000/10,000	2,600	6,000	1,758	804	2,562	NS-NPRFC-HAS
NPR 45/65-175 MT C42	4,500/6,500	9,000/10,000	2,600	6,000	1,993	819	2,812	NS-NPRGC-LAS
NPR 45/65-175 DT D28	4,500/6,500	8,000	2,600	6,000	1,763	777	2,540	NS-NPRFD-FAS
NPR 45/65-175 DT D34	4,500/6,500	8,000	2,600	6,000	1,788	814	2,602	NS-NPRFD-HAS
NPR 45/65-175 DT C42	4,500/6,500	8,000	2,600	6,000	2,023	829	2,852	NS-NPRGD-LAS

Dimensions⁷ (mm)

Models	WB	OAL	FOH	ROH	CA	RT	ORT	CH	FFH (Unladen)	RFH (Unladen)	EFH (Unladen)	Turning Circle ⁸ (m) Kerb To Kerb
NPR 45/65-175 C42	4,260	7,310	1,110	1,940	2,696	1,525	1,985	2,223	650	787	849	13.8
NPR 45/65-175 D28	2,795	5,248	1,110	1,343	2,222	1,525	1,985	2,236	663	782	839	9.6
NPR 45/65-175 D34	3,395	6,098	1,110	1,593	2,822	1,525	1,985	2,235	662	780	835	11.4



Cabin Features

General Features

AUDIBLE WARNING	Reverse alarm
ENGINE ACCESS	Access hatch under driver's seat and tiltable front passenger seat (Crew cab) Manual cab tilt to 45° with torsion bar assistance (Day cab)
EXTERIOR LIGHTING	Bi-LED Headlamps with LED Daytime Running Lamps (DRL) Front LED fog lamps LED tail lamps Roof mounted clearance lamps
FRONT BUMPER	3-piece resin, body coloured
GRILLE	Silver paint
MIRRORS	Heated and powered exterior main mirrors with flat glass and adjustable convex "spot" mirrors
SECURITY	Passive Entry and Start System (PESS) with remote central locking and immobiliser
STEPS	Heavy duty anti-slip steps
WIPERS	Two speed windscreen wipers with intermittent wipe mode

Driver Control

ENGINE	Cruise control DPD manual regeneration switch Idle speed control
GENERAL CONTROLS	Windscreen wipers (2 speed and intermittent modes), washers, exhaust brake, turn signals
SAFETY SYSTEMS	On/Off and Adjustable safety systems (for more details see owner's manual) ADAS controls
STEERING WHEEL CONTROLS	Multi Information Display controls Multimedia controls (inc. phone)
TRANSMISSION (DT ONLY)	Gear selection control with P-R-N-D and sequential shift positions



Images are not representative of model

Cabin Interior

AIR CONDITIONING	Auto climate control Rear cabin cooler vents
DOOR WINDOWS	Electric control
ENTRY ASSIST GRIPS	Door and roof pillar mounted
INTERIOR LIGHTING	LED lamp
OCCUPANCY	Driver's bucket seat equipped with mechanical suspension and weight adjustment to 130kg (Day cab) Driver's bucket seat (Crew cab) Passenger bench seat with 2 seat capacity Rear bench seat with 4 seat capacity (Crew cab)
POWER OUTLET	24V socket USB port
SEATBELTS	Lap sash seatbelts in all outboard seating positions. Centre seat lap belts.
STEERING COLUMN	Tilt / telescopic adjustable
STORAGE	Overhead cabinet, 2 cup holders, door pockets, centre phone storage pocket

MyISUZU Co-Pilot Audio Visual Unit

OPERATING SYSTEM	Android Automotive
NAVIGATION	Truck tailored GPS based system + Live traffic and map content updates via smartphone link (live feed updates are provided for 3 years)
SCREEN TYPE	10.1" High Definition with capacitive touch
RADIO	AM / FM / DAB+
INTERNAL STORAGE CAPACITY	32GB
SMARTPHONE INTEGRATION	Android Auto/Apple CarPlay compatible (wired) Phone storage pocket USB socket Wi-Fi connectivity

Instrumentation

GENERAL INSTRUMENTATION	Digital odometer with integrated dual tripmeters Engine temperature and fuel/AdBlue® level Speedometer and tachometer Adjustable vehicle speed warning
MULTI INFORMATION DISPLAY	AEB, FCW, DWS, LDW, F-ACC, TMW System activation alerts CTW indicator Hourmeter

Service & Support



ISUZU CARE



Service Agreements

Isuzu Essentials

Isuzu Essentials Plus

Isuzu Total

	Available on new trucks only and paid upfront - up to 72 months or the first 6 scheduled services	Available on new trucks and trucks currently in use - up to 72 months old	For new trucks only, Isuzu Total is our most comprehensive service package
Check and Report Fault Codes	•	•	•
Wheel Bearing Re-pack & Lubricating All Joints	•	•	•
Globes – Stop, Tail, Number Plate, Indicator, Headlight, Interior		•	•
Fan Belts & Coolant Hoses		•	•
Wiper Blades, Relays & Fuses		•	•
Engine, Transmission & Electrical Components			•
Brake & Suspension Components			•
Washer Fluids & Consumables	•	•	•
Labour	•	•	•

Dealer Network

Service & Support	National Isuzu Truck Dealer Network
	Find dealer online



Warranty⁹

Chassis	6 Year Standard Warranty
	250,000 km / Unlimited Hours
Genuine Parts & Accessories	3 Years Standard Warranty (When installed by an Isuzu Trucks Approved Dealership - Including Labor)
Service Intervals	25,000 km or 12 Months or 500 hrs (whichever occurs first)

Roadside Assist

Roadside Assist	6 Year Roadside Support
	24/7 Unlimited Km

¹ Maximum towing capacity applies. Gross Trailer Mass (GTM) should not exceed towing vehicle weight. Limit is subject to government regulatory requirements. To utilise GCM, the vehicle must be fitted with towing equipment suited to meet the required GCM ratings in compliance to local regulations.

² Performance values are theoretically calculated based on the vehicle at GVM. Real world figures may vary based on driving conditions, vehicle configuration, load and environmental factors.

³ Accessory Installer must ensure all fitted accessories comply with local road authority regulations and do not compromise safety or certification requirements (eg: ADR compliance)

⁴ As shown on tank. Volume of fuel/AdBlue® that can be added to a near-empty tank will vary according to operating conditions.

⁵ Vehicle ratings and axle weight limits are subject to government regulatory requirements. Consult your Isuzu dealer to select the correct vehicle for your specific application.

⁶ Manufactures nominal tare mass, includes tools, spare wheel (if standard), 10 Litres of fuel and 10 Litres of AdBlue®. Weights subject to ± 3% tolerance.

⁷ Drawing for reference only. Refer to the Isuzu Body Builder Guide for details.

⁸ Turning circle dimensions are based on manufacturers calculations and may vary under real-world conditions.

⁹ Subject to the conditions outlined in the IAL New Vehicle Warranty. All Isuzu warranties are subject to mandatory prescribed terms under Australian Consumer Law including consumer guarantees. For further information please visit isuzu.com.au or contact your local dealer.

ISUZU AUSTRALIA LIMITED ABN 97 006 962 572 ("IAL"). The information in this specification sheet was correct at time of Publication, all measurements, specifications and equipment are subject to change without notice. Some equipment may have been changed and/or is available at extra cost. IAL may make changes at any time without notice, in prices, colours, materials, equipment and models. IAL makes all reasonable attempts to ensure the availability of all vehicles and equipment. The information in this specification sheet is general in nature. Your Isuzu dealer can confirm all measurements, specifications and vehicle / equipment availability upon request. To the extent permitted by the law, IAL is not liable to any person as result of reliance on the content of this specification sheet. Our National Customer Care Centre provides you access to a team of specialists with years of training. A conversation with an Isuzu specialist is as easy as contacting the team on 1800 035 640 or customercare@isuzu.net.au.

Isuzu Australia Limited

www.isuzu.com.au