



Specifiche

DETAILS	
Piattaforma	Moterra Neo
Nome Modello	Moterra Neo 4 C65403U
Codice Modello	C65403U
KIT TELAIO	
Telaio	Moterra, SmartForm C1 Alloy, 150mm travel, removable downtube battery, injection molded skid plate, 55mm chainline, internal cable routing, 148x12mm thru-axle, UDH hanger, post mount brake, tapered headtube, 18mm two-bolt kickstand mount, integrated rear rack mounts
Forcella	RockShox Yari RC, 150mm, 15x110mm Boost, 42mm offset
Serie sterzo	Integrated Sealed Bearing, 1-1/8" - 1.5
Rear Shock	RockShox Deluxe Select, DebonAir, 2-Pos mode adjust, adjustable rebound
E-SYSTEM	
Motore	Bosch Performance Line CX 250W
Batteria	Bosch PowerTube, 625Wh
Carica batteria	Bosch 4A
Display	Bosch Kiox 300 w/ LED Remote
TRASMISSIONE	
Cambio	Shimano Deore M6100 SGS
Leve cambio	Shimano Deore M6100, 12-speed
Catena	Shimano M6100 Hyperglide, 12-speed
Guarnitura	FSA Bosch E-bike w/ 55mm chainline, 160mm, 34T
Pacco pignoni	Shimano Deore, Hyperglide, 10-51, 12-speed
FRENI	
Freni	Shimano MT420, 4-piston hydraulic disc, 203/203mm Deore RT30 rotors
Leve Freno	Shimano MT420 hydraulic disc

RUOTE	
Cerchi	WTB ST i30 TCS, 32h, tubeless ready
Raggi	DT Swiss Champion
Dimensioni pneumatico	2.6
Dimensione Ruote	29
Mozzi	(F) Shimano MT400, 15x110mm thru-axle / (R) Shimano MT410, 12x148mm thru-axle
Pneumatici	(F) Maxxis Minion DHF, 29x2.6", EXO, tubeless ready / (R) Maxxis Rekon, 29x2.4" (27.5x2.4" - size Small), EXO, tubeless ready
COMPONENTI	
Manubrio	Cannondale 3 Riser, 6061 Alloy, 15mm rise, 8° sweep, 4° rise, 780mm
Attacco Manubrio	Cannondale 3, 3D Forged 6061 alloy, 1-1/8", 31.8, 0°
Impugnatura	Fabric Funguy
Sella	Fabric Scoop Shallow Sport, steel rails
Reggisella	Cannondale DownLow dropper, internal routing, 31.6, 125mm (S, M), 150mm (L-XL)
EXTRA	
Extra 1	Pre-installed light cable. (Note: this model is not compatible with Bosch Range Extender)