



COATINGS SOLUTIONS

HIGH PERFORMANCE

Technical Data Sheet

3919 Airpark Drive STE12
Lakeland, FL 33811

www.coatingsoln.com - Office: 863-450-2192 E-mail: info@coatingsoln.com

Tru Non-Slip Additive

Description:

Clear Non-Slip Additive is an ultra-durable, micronized polymeric aggregate developed for use as an anti-skid additive in 2-part coatings.

Fine Grade recommended in thinner film systems such as Solvent Acrylic Clears and Concrete Stains, Water-Based Epoxy and Water-Based Urethanes

Coarse Grade recommended for high solids epoxy and polyaspartic coatings

Available in Quarts and 1 gallon with measuring scoop.

Mixing

While mixing at low speed sprinkle one scoop per gallon. Stir for 30 seconds. (If more texture is desired second scoop can be added.)

Application:

Immediately pour mixed material on the floor squeegee and back roll. Avoid large nap rollers. 1/4 to 3/16 preferred back roll in both directions to ensure non-slip is uniform.



Store in clean dry area do not freeze

Dispose in accordance with all state local and federal laws

Regulatory

Meets all VOC categories in US and Canada. Not

Approved for California

Contributes to Leed

Warranty:

Material only no labor