INDUCT 20000



NEW
PATENTED
CELL DESIGN

Uses the same ActivePure® Technology used in the Aerus Pure & Clean that was **proven to reduce over 99.9% of the airborne virus that causes COVID-19**[1]

INTENDED USE

The Induct 20000 attaches directly to the HVAC system ductwork to reduce viruses, bacteria, and other contaminants in the ambient air and on surfaces in businesses and homes.

BENEFITS

- Uses the latest version of ActivePure Technology
- Provides continuous surface decontamination and air purification in real time
- Safely removes allergy and asthma triggering contaminants
- Protects your heating and cooling system from potentially dangerous buildup

HOW IT WORKS

- Our proprietary ActivePure Technology uses high-intensity UVC light and a catalytic process to produce super oxide ions and hydro-peroxides that reduce contaminants on surfaces and in the air
- Advanced ActivePure® Technology continuously protects and purifies the environment around you
- Installed by a professional directly to the existing HVAC system ductwork

NOTABLE ACTIVEPURE FACTS

- Primary technology in an FDA-Cleared Class II Medical Device
- Inducted into the Space Technology Hall of Fame in 2017 and is the only Certified Space Technology product in its class
- Ongoing 2-year double-blind study with the Cleveland Clinic
- Used by US Professional Sports Teams and athletes

PROOF IT WORKS

In extensive independent lab testing, ActivePure has been proven to significantly reduce the following contaminants and pathogens:

- Aspergillus Niger
- Avian Flu
- Bacillus Globigii
- Clostridium Difficile
- Candida Albicans
- E. Coli
- Hepatitis A
- Legionella Pneumophila
- Listeria Monocytogenes
- MRSA
- MS2 Bacteriophage RNA Virus
- Murine Norovirus
- Phi-X 174 DNA Virus
- Pseudomonas spp.
- SARS-Cov-2 Coronavirus
- Smoke
- Stachybotrys Chartarum
- Staphylococcus Aureus
- Staphylococcus Epidermis
- Streptococcus spp.
- Swine Flu
- VOCs

SPECIFICATIONS:

Induct 20000 (Ozone Free)	00754 Model: A1033A
Technology	(4) ActivePure® Cells
Electrical*	Input Voltage: 120/277 V 50/60 Hz Current: .54 Amps Max *Conforms to UL STD 1995. Certified to CSA STD C22.2 No. 236.
Mechanical	Distribution via air handler
Dimensions	11" H x 11" W x 17" D (28 cm x 28 cm x 43.2 cm)
Weight	8 lbs. (3.6 kg.)
Operating temp.	< 200˚F (93˚C)
Recommended Maximum Coverage in a Contiguous Space	• Low Density: 9,408 sq. ft. (874 m^2) • Moderate Density: 6,272 sq. ft. (583 m^2) • High Density: 4,704 sq. ft. (437 m^2) For coverage in medical or health care environments, contact Medical@activepure.com
Warranty	Limited 3 year warranty

The ActivePure® Technology built into each Induct 20000 is based on a variation of the technology originally developed for use on the International Space Station and is recognized as the exclusive Certified Space Technology™ in its category.

ActivePure® TECHNOLOGY

2017 Space Technology Hall of Fame Inductee

Proudly Designed, Developed and Engineered In the USA.

www.activepure.com