



## BREEZE 1

Breeze Through Every Mile.

### Lightweight Yet Powerful

- 48 lbs Lightweight, Easy to Lift Up
- 70 miles Max Range
- 750 W Quiet Motor / 65 Nm Torque

### Velotric ComfortMax™

- Upright Riding Posture
- Ergonomic Seat & Grips
- 380 mm Low Step-Through

### Easy Maneuverability

- 750 W Motor (Peak 1150 W)
- Smooth Torque Sensor with Precise Steering
- Tighter Frame for Small Riders

## SIZE

### Step-Through

**Regular** 4'11"–5'8"

**Large** 5'6"–6'4"



● Violet Haze



● Slate Gray



● Satin White



● Classic Scarlet



● Ocean Mist



● Lemans Blue

NEW

## Velotric Edge

### SensorSwap™

Choose from 2 unique sensor modes with a simple click.

#### Torque Mode:

Dodge & Weave without thinking about it with the responsive, natural pedal feel.

#### Cadence Mode:

Glide effortlessly on open roads with a light pedal feel, perfect for long distances.



### Velotric Safer Rides



UL2271, UL2849 tested in UL laboratories.



Battery IPX7 and whole bike IPX6 water resistance.

### ComfortMax™

Every Breeze 1 comes with a customized comfort package to make your riding experience premium.



Adjustable Stem

Upright Riding Posture

Cruiser Handlebar

Comfortable Seat

Ergonomic Grips

380 mm Low Step-Through

# VELOTRIC BREEZE 1 SPECIFICATIONS

Building A Better Ride. 

<b>SIZE GUIDE</b>	Bike Size		Regular/Large			
	Color		Violet Haze, Satin White, Ocean Mist, Classic Scarlet, Slate Gray, Lemans Blue			
	User Height Range		Regular: 4'11"–5'8" Large: 5'6"–6'4"			
<b>FRAMESET</b>	Frame		Triple-Butted Aluminum Alloy			
	Fork		Aluminum Alloy			
<b>ELECTRONICS</b>	Motor		48 V, 750 W, 1050 W Peak, 65 Nm			
	Battery		48 V, 627 Wh, IPX 7, Certificated by UL 2271			
	Cell		18650 Cell, Certified by UL 2580			
	Charger		48 V, 3 A Fast Charger			
	SensorSwap™		Torque/Cadence			
	Display		3.5" Full Color, High Brightness, Bluetooth			
	Usb Port		USB Type-C			
	Throttle		Trigger-Control, Removable			
	Pedal Assist		3 Riding Modes × 5 PAS Levels			
	Front Light		400 Lm High-Output Integrated LED, Adjustable Angle			
	Rear Light		Brake Highlight, Turn Signal			
Water Resistant		IPX7 for Battery; IPX6 for Whole Bike				
<b>SPEED &amp; RANGE</b>	Max Speed (Default)		20 mph			
	Max Speed Adjustable Range		12–28 mph			
	Class		1/2/3			
	Throttle Range		55 miles			
	Pedal Assist Range		70 miles			
<b>DRIVETRAIN</b>	Chainrings		46 T, Narrow Wide Chainring			
	Crankset		Aluminum Alloy, 170 mm			
	Cassette		8-Speed			
	Rear Derailleur		SHIMANO 8-Speed			
	Shift Lever		SHIMANO 8-Speed			
	Chain		KMC 8-Speed			
<b>BRAKE</b>	Brake	Tektro Hydraulic Disc Brake		<b>WHEELS</b>	Rims	Double-Wall Aluminum Alloy
	Rotors	180 mm Front and Rear			Front Hub	NOVATEC Aluminum Alloy, 15×110 mm Thru-Axle
	Brake Levers	Aluminum Alloy, with Power Cutoff			Tire	KENDA 27.5×2.2" Ebike Puncture Resistant Tires
<b>COCKPIT</b>	Handlebar		Aluminum Alloy, Φ31.8 mm, 660 mm(R)/680 mm(L)			
	Grips		Durable Ergonomic Grips, Lockable			
	Stem		Adjustable, Aluminum Alloy			
	Saddle		Velotric Comfortable & Ergonomic Seat			
	Seatpost		Aluminum Alloy, Φ 30.9 mm, 350 mm			
	Clamp		Aluminum Alloy, Quick Release			
<b>SUPPORTS</b>	Pedals		Plastic			
	Kickstand		Aluminum Alloy, Included, Rear Mount			
<b>WEIGHT &amp; LOAD</b>	Bike Weight		48 lbs			
	Rear Rack Load Capacity		66 lbs			
	Max Bike Load Capacity		330 lbs			
<b>CERTIFICATION</b>	UL Certification		UL 2849 Certified Ebike System and UL 2271 Certified Battery Pack			
	ISO Standard		ISO 4210			