

SmartLink Medi-Guardian MKII 4G

The SmartLink Medi Guardian MKII 4G helps you remain independent, knowing that with the press of a button you can summon assistance at any time of the day or night.

The modern slim line design of the SmartLink Medi Guardian MKII 4G allows it to be installed unobtrusively anywhere so it's ready when you need help. To send an alarm you simply press the button on your personal wrist or pendant transmitter, which can be worn at all times, even when in the shower, or outside in the garden.

The SmartLink Medi Guardian MKII 4G has been built to the highest technical standards and has been manufactured to meet both Australian and International quality standards. It can be supplied with additional transmitters, as well as call points that can be fixed around the home as needed.

Unit Specifications

Dimensions	L210 x W130 x D35 mm
Weight	590g (including battery)
Quiescent Current	1mA
9V DC Plug Pack	9V DC 300mA with integral earth
Battery Backup	4.8V 1600mAh Rechargeable Ni-MH
2-Way Radio Receiver	2-way TWR
Range	100 to 300 metres open air (subject to environmental conditions)
Transmitter Frequency	915-928 MHz (Australia & New Zealand)

Features & Benefits

- Programmable over internet data network as well as SMS and computer direct connect
- Software & Firmware upgrades over the Cellular Network (auto or manual)
- Will support LTE as well as 4G Data and 3G voice
- Totally designed and manufactured in Australia using the latest surface mount technology for reliability
- Automatic two-way voice contact in emergencies
- Automatic Telephone Line failure alarm
- Up to 250 hr (10 day) rechargeable Ni-MH battery backup
- Automatic power fail and low battery reporting
- Programmable UHF high security wireless Radio Devices (PIRs, Reeds, Smoke, Inactivity, Dementia, Man-down etc.)
- Backlit Help & Cancel button
- Universal waterproof pendants designed to be easily interchangeable for around the neck, wrist or wall mounted



Conforming Standards

ISO 9001/2000	International Quality Manufacturing Standards
AS4607	Personal Response Systems
AS2201.4 (C2)	Intruder alarm Systems - Wireless
AS4268.2012	Radio Equipment & antenna Systems - Short Range devices

Specifications subject to change at discretion of INS LifeGuard.

WARNING: For safety reasons, only connect equipment with a telecommunications compliance label. This includes customer equipment previously labelled permitted or certified.

