

SCREENING RANGE

HARRIER 220



SCREEN

2.1m (6'9") x 1.1m (3'6") Double deck screen
600mm x 1.1m (2' x 3'6") Feed in area
End tensioned as standard

POWERUNIT

Isuzu engine (21kW / 28.5hp)
Simple to operate
Stage V: Kubota V 1505

OUTPUT POTENTIAL

Up to 80tph / 90 US tph



CONVEYORS

1000mm (40") Wide collection conveyor with 1.93m (6' 4") discharge
500mm (20") Wide midgrade conveyor with 1.18m (3'10") discharge

TRANSPORT

Containerisable
Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	4.36m (14' 4")	1.8m (5' 11")	2.23m (7' 4")

Weight: 3,300kgs (7,275lbs)

SCREENING RANGE

HARRIER 750

SCREEN

4.5m x 2.6m (14'8" x 8'7") Double deck grid
Split level cassettes as standard
Standard grid opening - 150mm (6"); 100mm (4") is optional
Standard bottom deck mesh - 60mm (2.4")

POWERUNIT

Tier 3: Deutz D914 53kW (71Hp) @2300rpm
Tier 4 / Stage IV: Cat C3.4 - 55kW (74Hp) @ 1800rpm
Stage 5: Cat C2.2 - 55Kw (74Hp) @ 2300rpm

OUTPUT POTENTIAL

Up to 600tph / 660 US tph

CONVEYORS

1200mm (48") Wide product conveyor with discharge height of 3.4m (11'2")
Hydraulically folding for transport
Twin drive as standard

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	9.43m (31')	2.82m (9' 3")	3.2m (10' 6")

Weight (standard machine): 19,000kgs (41,890lbs)

