



CRUSHING RANGE

COBRA 230

HOPPER / FEEDER

- 2.6m³ (3.4yd³) Hopper capacity
- Integrated pre-screen for fines removal
- Feeder speed auto-regulates depending on crusher load

IMPACT CRUSHER

- 860mm (34") x 720mm (28.5") Crusher Inlet
- 830mm (33") Wide x 860mm (34") diameter rotor
- 2 High / 2 Low configuration as standard
- Max OSS – 120mm (4.75") upper; 55mm (2.25") lower
- Min CSS – 40mm (1.5") upper; 20mm (0.75") lower
- Hydraulic adjust and hydraulic overload protection as standard

POWERUNIT

- Tier 3 John Deere 6068 194kW (260Hp)
- Tier 4 Final: Volvo D8 210kW (281Hp)
- Stage V: Volvo D8 210kW (281Hp)
- Direct drive to crusher via clutch and V Belts

OUTPUT POTENTIAL

Up to 250tph / 275 US tph

CONVEYORS

- 900mm (36") Wide product conveyor
- Product conveyor discharge height: 3000mm (9' 10")

GENERAL

Intuitive 'Push Button' Control System

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	9.32m (30' 7")	2.43m (8')	2.99m (9' 10")

Weight (with Magnet): Tier 4F: 24,000kgs (52,911lbs)

