

CONTACT US NOW!

Unit 7 Forge Business Centre Palgrave, Diss Norfolk IP22 1 AP

y (in) 💽

Tel: 01379 658721 Fax: 01379 658720 www.cool-tech.co.uk







WATTAGE

LAMP LUMINOUS FLUX

CRI

CCT

RATED VOLTAGE

POWER FACTOR

IP GRADE

OPERATING TEMP

30/50W

150LM/W±5%

Ra>70

2700-6500K

AC 100-240V 277V~,50/60Hz

>0.95

IP66

-40 ℃ ~60 ℃

CT-B300-30W

4,500LM±5%

1.15kg±5%

250x107.4X84mm

CT-B300-50W

7,500LM±5%

1.2kg±5%

250x107.4X84mm



| Installation







Ceiling installation

Suspension installation

Wall mounting

| Application



Tunnel



Mining





Industrial Lighting



Ambient Lighting


| LIGHT Distribution Curve






G5-Type

Underground Mining



Conveyor belt




| Test



Salt SprayTest

The heat sink processed by oxidization and powder spraying so that it has good corrosion resistance



High-LowTemperatureTest

The test equipment opening 2hours, keeping temperature<-40C the lamp working fine. The test equipment opening 4hours keeping temperature>60C, the lamp keep working fine




VibrationTest

Vibration test is a simulation of various vibration condition including transportation, installation and using, to ensure system robustness.




UV AgingTest

The test time is about 720 hours. After test the lamp working regularly, no discoloration appearance, no yellowing of the PC lens.




WithstandVoltageTest

Testing whether the withstand voltage is within the specified value, to avoid sudden voltage surges such as short circuit, operation error, fault, etc, causing breakdown or accidents



Waterproof Test

Every lamp will be tested the water-proof at least 2 spraying so that it has good corrosion resistance. make it very eficient to shorten lead time.



Model	Size of Box	Gross Weight	Size of Carton	Gross Weight	Box Quantity /Carton
B300-30W	280*160*140mm	1.35 KG	820*305*320mm	14.50 kg	10
B300-50W	280*160*140mm	1.40 KG	820*305*320mm	15.00 kg	10

Packaging

