

■ VISCOSIMETRI CANNON FENSKE per LIQ. OPACHI

Viscosimetri per liquidi trasparenti, secondo le norme ASTM-IP, con certificato di

	Serie	Costante approssim. cSt/s	Velocità cinematica cSt
34.0025.00	□ 25	0,02	0,5-2
34.0050.00	□ 50	0,04	0,8-4
34.0075.00	□ 75	0,08	1,6-8
34.0100.00	□ 100	0,015	3-15
34.0150.00	□ 150	0,035	7-35
34.0200.00	□ 200	0,1	20-100
34.0250.00	□ 250	0,17	35-175
34.0300.00	□ 300	0,25	50-250
34.0350.00	□ 350	0,5	100-500
34.0400.00	□ 400	1,2	240-1200
34.0450.00	□ 450	2,5	500-2500
34.0500.00	□ 500	8	1600-8000
34.0600.00	□ 600	20	4000-20000



■ VISCOSIMETRI CANNON FENSKE per LIQ. TRASPARENTI

Viscosimetri per liquidi trasparenti, secondo le norme ASTM-BS-IP, con certificato di taratura a 40°C.

	Serie	Costante approssim. cSt/s	Velocità cinematica cSt
34.0025.01	□ 25	0,02	0,5-2
34.0050.01	□ 50	0,04	0,8-4
34.0075.01	□ 75	0,08	1,6-8
34.0100.01	□ 100	0,015	3-15
34.0150.01	□ 150	0,035	7-35
34.0200.01	□ 200	0,1	20-100
34.0250.01	□ 250	0,17	35-175
34.0300.01	□ 300	0,25	50-250
34.0350.01	□ 350	0,5	100-500
34.0400.01	□ 400	1,2	240-1200
34.0450.01	□ 450	2,5	500-2500
34.0500.01	□ 500	8	1600-8000
34.0600.01	□ 600	20	4000-20000

