


SYNCHRONIZATION OF CYLINDERS:

APPLY GRIP PRESSURE TO CYLINDERS. THE PASSENGER CYLINDER SHOULD ALSO BEGIN TO EXTEND. HOLD PRESSURE TO CYLINDER AT FULL EXTENSION FOR A MINIMUM OF 30 SECONDS. RETRACT CYLINDERS AND REPEAT. THIS WILL FULLY SYNCHRONIZE CYLINDERS.

SHIPPING
DIMENSIONS



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF <INSERT COMPANY NAME HERE>. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF <INSERT COMPANY NAME HERE> IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL $\pm 1/16$
ANGULAR: MACH ± 1 BEND \pm
TWO PLACE DECIMAL ± 0.10
THREE PLACE DECIMAL ± 0.005
MATERIAL
DO NOT SCALE DRAWING

	NAME	DATE	P.O. BOX 248, SABETHA KS. 66534 (785) 284-3674 FAX (785) 284-3931		
DRAWN	CAITLYN	1/6/2016	<div>TRIPLE C</div> <div>INC.</div>		
PART #					
ASM #	HB-HYDRA-TM 2000				
COMMENTS:			SIZE	DWG. NO.	REV
3 PT BALE MOVER			B	70-0100 C	C
			SCALE: 1:16		

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
B	UPDATED TO SHOW CATEGORY 3 HOLES	4/10/2013	
C	ADDED (2) FP-TM2-14 AND CHANGED HITCH PINS TO HD-PH 1.125X7.00	1/6/2016	

