



Belltec Augers



Drill holes fast, where others fail.

Belltec Augers



BD

BD STYLE AUGERS FOR DRILLING IN SOLID ROCK CONDITIONS, SOLID ROCK AND CONCRETE WITHOUT REBAR.

FEATURES: AVAILABLE IN 48" LENGTH FOR HYDRAULIC DRIVES AND 36" FOR TM-48
6", 9", AND 12" DIAMETERS
HEAVY DUTY CAST BORING HEAD
TRIPLE FLIGHTED
3/8" FLIGHTING
EASY CHANGE ROCK TEETH



RAD

RAD STYLE AUGERS FOR DRILLING IN THE TOUGHEST CONDITIONS, SOLID ROCK, CONCRETE, FRACTURED ROCK, FROZEN GROUND AND COMPACTED SOILS.


FEATURES: AVAILABLE IN 48" LENGTH FOR HYDRAULIC DRIVES AND 36" FOR TM-48
8" TO 36" DIAMETERS
HEAVY DUTY 3/4" THICK BORING HEAD
CARBIDE BULLET STYLE TEETH
3/8" THICK FLIGHTING



SRA

SRA STYLE AUGERS FOR DRILLING IN THE TOUGHEST CONDITIONS, SOLID ROCK, CONCRETE, FRACTURED ROCK, FROZEN GROUND AND COMPACTED SOILS.

FEATURES: AVAILABLE IN 48" LENGTH FOR HYDRAULIC DRIVES AND 36" FOR TM-48
4.5" TO 9" DIAMETERS
HEAVY DUTY 3/4" THICK BORING HEAD
CARBIDE BULLET STYLE TEETH
3/8" THICK FLIGHTING



RSA

RSA STYLE AUGERS FOR DRILLING IN DIFFICULT GROUND CONDITIONS, COMPACTED SOILS, HEAVY CLAY, ASPHALT, FROZEN GROUND, AND FRACTURED ROCK.

FEATURES: AVAILABLE IN 48" LENGTH FOR HYDRAULIC DRIVES AND 36" FOR TM-48
4.5" TO 36" DIAMETERS
CAST BORING HEAD
HARDENED DRIVE IN TEETH
HARDENED FISHTAIL PILOT
3/8" THICK FLIGHTING



SDA

SDA STYLE AUGERS FOR STANDARD TO MODERATE DRILLING CONDITIONS, DIRT CLAY AND SMALL FRACTURED ROCK.

FEATURES: AVAILABLE IN 48" AND 54" OVER ALL LENGTHS
6" TO 36" DIAMETERS
FABRICATED BORING HEAD
HARDENED BOLT ON TEETH
HARDENED FISHTAIL PILOT
3/8" THICK FLIGHTING



PUFF

PUFF STYLE AUGERS FOR DRILLING T-POST HOLES IN DIRT, CLAY, COMPACTED SOILS, FROZEN GROUND, FRACTURED ROCK, SOLID ROCK AND CONCRETE.

FEATURES: REPLACEABLE 2" CARBIDE CUTTING HEAD
1-5/8" SOLID STRESS PROOF SHAFT



BELLTEC Industries, Inc.

Post Office Box 270 • Belton, Texas 76513

1-800-242-9410 • Fax 254-939-9408

www.belltec.net • sales@belltec.net