



Belltec H-Series Auger Drives
5 Year Warranty



Drill holes fast, where others fail.

Belltec H-Series Auger Drives

The **Belltec H-Series** hydraulic auger drives are available in three models for systems operating between 10 and 35 GPM and 2000 to 3000 PSI. The H-Series planetary outperforms and has heavier components than any of its competitors. First tubular frame on the market with the largest and strongest cradle. Mounting frame mounts to all modern skid loaders with the universal attach system. The **H-Series** units are ideal for the toughest drilling applications from dirt to solid rock and concrete when paired with the correct H-Series auger.

No Drain Hoses Required

Features

- Heaviest in Class Planetary Gearbox with No Snaps Rings
- Heavy Duty Nut Prevents Shaft Pull Out
- Heavy Duty Motors with High Pressure Seal
- Heavy Duty Hexagon Housing
- 2" Hex or 2.5" Round Output Shaft



Exclusive bolt on 2" hex output shaft significantly reduces costly down time and repair costs if a shaft is bent or broken

MODEL H-200

2.5" ROUND ORDER NUMBER 113066
2" HEX ORDER NUMBER 113001

MAXIMUM OUTPUT TORQUE 2000 FT-LBS
RECOMMENDED FLUID FLOW 10-20 GPM
MAXIMUM PRESSURE-CONTINUOUS 3000 PSI
RECOMMENDED MAX AUGER DIA-DIRT 30 INCHES

OUTPUT SPEED

FLOW GPM	SPEED RPM
10	48
12	55
14	64
16	73
18	82
20	92

OUTPUT TORQUE

PRESSURE PSI	TORQUE Lb-Ft.
2000	1339
2200	1480
2400	1607
2600	1740
2800	1874
3000	2008



Extra large step with non-skid for entering and exiting skid loaders and owners manual canister so the manual stays with the unit at all times

MODEL H-300

2.5" ROUND ORDER NUMBER 113067
2" HEX ORDER NUMBER 113014

MAXIMUM OUTPUT TORQUE 3000 FT-LBS
RECOMMENDED FLUID FLOW 15-30 GPM
MAXIMUM PRESSURE-CONTINUOUS 3000 PSI
RECOMMENDED MAX AUGER DIA-DIRT 36 INCHES

OUTPUT SPEED

FLOW GPM	SPEED RPM
15	47
18	56
22	68
26	81
28	87
30	93

OUTPUT TORQUE

PRESSURE PSI	TORQUE Lb-Ft.
2000	1958
2200	2066
2400	2350
2600	2546
2800	2742
3000	2937



Large cradle holds drive in place and allows for better visibility while in transport position

MODEL H-350

2.5" ROUND ORDER NUMBER 113068
2" HEX ORDER NUMBER 113016

MAXIMUM OUTPUT TORQUE 3000 FT-LBS
RECOMMENDED FLUID FLOW 20-35 GPM
MAXIMUM PRESSURE-CONTINUOUS 3000 PSI
RECOMMENDED MAX AUGER DIA-DIRT 36 INCHES

OUTPUT SPEED

FLOW GPM	SPEED RPM
20	51
24	62
26	67
28	72
30	77
35	90

OUTPUT TORQUE

PRESSURE PSI	TORQUE Lb-Ft.
2000	2388
2500	2985
3000	3582