

PUMP AND CLUTCH IDENTIFICATION INFORMATION

[<--Back](#)

Scroll down to see all pumps and clutches

↓ Pumps "A" Mount ↓

PARKER 315 "A" Mount Pumps (clockwise rotation)					
GPM (at 1600RPM)	Port	Model No.	Center Section Thickness	Cubic Inches	Part No.
5GL	Side	326-9110-236	15/16"	0.62	720203
5GL	Rear	326-9110-115	15/16"	0.62	720170
7GL	Side	326-9110-226	1 1/8"	0.93	720200
7GL	Rear	326-9110-116	2 1/8"	0.93	720172
9GL	Side	326-9110-288	1 1/4"	1.09	720201
9GL	Rear	326-9110-214	1 1/4"	1.09	720173
9GL	Dual	326-9110-307	1 1/4"	1.09	720226
12GL	Side	326-9110-301	1 1/2"	1.40	720212
12GL	Rear	326-9110-215	1 1/2"	1.40	720174
17GL	Side	326-9110-300	2"	2.02	720213
17GL	Rear	326-9110-216	2"	2.02	720213
"A" mount pumps have a 7/8" tapered shaft with a woodruff keyway.					
Model number is stamped on a metal tag on top of the pump.					

Parker PH14 "A" Mount Pumps (clockwise rotation)				
GPM (at 1600RPM)	Port	Model No.	Description	Part No
7GL	Side	304 9110 005	Pump, 7 gpm, 17. CC, PH14	720300
9GL	Side	304 9110 006	Pump, 9 gpm, 19 CC, PH14	720301
12GL	Side	304 9110 003	Pump, 12 gpm, 25 CC, PH14	720294
17GL	Side	304 9110 004	Pump, 17 gpm, 31.8 CC, PH14	720295

Parker 415 High Pressure "A" Mount Pumps						
GPM (at 1600RPM)	Port	Model No.	Center Section Thickness	Cubic Inches	Part No.	Feature No.
9GL	Rear	326-9110-214	1 1/4"	1.09	720286	02-2005
12GL	Rear	326-9110-215	1 1/2"	1.40	720288	02-2105
* Model number is stamped on back half of pump.						

Webster "A" Mount Pumps - Obsolete					
GPM (at 1600RPM)	Port	Model No.	Center Section Thickness	Cubic Inches	Part No.
4GL	Side	058YC	13/16"	0.58	720279
5GL	Side	077YC	15/16"	0.77	720280
7GL	Side	104YC	1 1/8"	1.04	720281
9GL	Side	116YC	1 3/16"	1.16	720282
12GL	Side	155YC	1 7/16"	1.55	720283
17GL	Side	194YC	1 3/4"	1.94	720284
Part number is stamped into side of pump.					

Parker "A" Mount Pumps (Counter-Clockwise) - Obsolete					
GPM (at 1600RPM)	Port	Model No.	Center Section Thickness	Cubic Inches	Part No.
5GL	Rear	326-9112-094	15/16"	0.62	720203
7GL	Rear	326-9112-095	1 1/8"	0.93	720200
9GL	Rear	326-9112-096	1 1/4"	1.09	720173
12GL	Rear	326-9112-097	1 1/2"	1.40	720174
17GL	Rear	326-9112-098	2"	2.02	720212

Rexroth "A" Mt. Pumps (Rear Port - Aluminum) - Obsolete
--

GPM	Model No.	Part No.
7GL	S20S7dhqlr	720026
9GL	S20S9dhqlr	720144
12GL	S20S12dhqlr	720027
17GL	S20S17dhqlr	720028

↓ Pumps "AA" Mount ↓

PARKER 505 "AA" Mount Pumps (Aluminum)				
Cu. In.	Port	Model No.*	C. S. Thickness	Part No.
0.43	Rear	331-9110-207	2"	720214
0.49	Rear	331-9110-145	2 1/8"	720202
0.49	Side	1950263 *	2 1/8"	723010
0.61	Rear	331-9110-002	2 3/8"	720176
0.68	Rear	331-9110-247	2 7/16"	720178
0.73	Rear	331-9110-165	2 9/16"	720206
0.73	Side	1950264 *	2 9/16"	723011
"AA" mount pumps have a 1/2" straight shaft with a square keyway.				
Model number is stamped into side of pump.				
* Side port pumps used to be made from rear port pumps. Now they are Haldex.				

Casappa "AA" Pump				
0.80	Rear	PLP20.13D0-XXS0		720239

↓ Clutches ↓

Warner Electric Clutches					
Model No.	Mount	Ft.-Lbs.	Diameter	Belt	Part No.
1411-42	A	90 (Std.)	7 1/8"	2 V	740037
1466-53	A	120 (HD)	6 7/8 "	2 V	740038
1417-11	A	120	6"	6 gr.	740144
1417-42 *	A	120	6"	8 gr.	740148
1417-49	A	120	6"	10 gr.	742066
1417-24	AA	120	5"	6 gr.	740162
1417-24***	AA	120 (24 volt)	5"	6 gr.	740419
see note **	AA	120	5"	7 gr.	740179
1417-31	AA	120	5"	8 gr.	740183
1417-31***	AA	120 (24 volt)	5"	8 gr.	740420
* 1417-42 was used to replace 1473-69					
** pulley is machined from 6 groove clutch					
*** a 24 volt coil is subbed for the 12 volt coil to make 24 volt clutches					

Ogura Electric Clutches (120 Ft.-Lbs.)				
Mount	Belt	Model No.	Diameter	Part No.
A	8 gr.	MA-MG02D-DE	6"	742009
A	6 gr.	MA-MG01-1V	6"	742016
A	6 gr.	MA-MG01-1V***	6" (24 volt)	742076
AA	8 gr.	MA-MG06-DE	5"	742029
Ogura AA clutches are preassembled.				
*** a 24 volt coil is subbed for the 12 volt coil to make 24 volt clutches				