

JENSEN

OILFIELD

BALE
HANDLERBALE
TRANSPORTTRUCK
BEDSTRUCK
EQUIPMENTWILDFIRE
BEDSCR
BEDSKIRTED
BED

JENSEN Steerman®



Jensen Steerman

The Steerman loading capacity is 2850 lbs*. The free-float system allows for safe and quick unrolling on smooth or uneven terrain and will even function with out-of-round bales.



Jensen Steerman

Standard Equipment

- 11 ga. Floor Plate
- 5" Main Sills; 3" Cross Sills
- Light Package – Maximum Available
- Spinners & Side Rails
- Bulkhead with stop light and work lights mounted in crossbar
- Tool Boxes (2) 15" x 12" x 25"
- Hydraulic quick couplers at rear of bed
- Rear Drop Hitch with 2" Receiver
- Electric Hydraulics (1st option) – Pump,

HOME

CONTACT
USCORPORATE
INFOFIND
US ON
MAPQUEST

FEEDBACK



P. O. Box 1509

14TH AND PACIFIC STREETS

COFFEYVILLE, KS. 67337

1-800-331-3551 TOLL FREE

1-620-251-5700 PHONE

1-620-251-3622 FAX



motor, valve manifold, and batteries mounted inside of tool box

- Live Hydraulics (2nd option) – Reservoir tank and valve manifold mounted inside of tool box
- Control Pendant for full operation inside or outside of cab

Bed Specifications

- 1 Ton - 98" X 9' or 11'
- 1 Ton - 92" x 9' or 11'
- 3/4 Ton - 85" X 8'6"



Hydraulic System Options

- Live Hydraulic sized for system with tail board auxiliary (6 GPM)
- PTO/Hydraulic sized for system with tail board auxiliary (6 GPM)
- Electric/Hydraulic sized for system with tail board auxiliary (3 GPM)

* DO NOT exceed truck axle load rating.

[Oilfield](#) | [Bale Handler](#) | [Bale Transport](#) | [Truck Beds](#) | [Truck Equipment](#) | [Wildfire Beds](#) | [CR Bed](#) | [Skirted Bed](#) | [Contact Us](#) | [Corporate Info](#) | [Feedback](#) | [Home](#)

©2011 Jensen International
Web design and hosting by [MarketAide Services, Inc.](#)