

HYDRA™2000

TRACTOR MOUNT

Specifications & Features

Tractor Requirements

Category II Three-Point
ROPS Equipped Tractor

Hydraulic Requirements

2500 PSI
Pioneer Male Ends

Grip Range

35" to 95" w/o Spinners
18" to 77" w/Spinners
Synchronized Arms

Unit Weight

562# Dry

Lifting Capacity

2000#, Limited to Safe Tractor
Three Point Load Capacity

Warranty

Full 2-Year

		Retail	Dealer
HYDRA TM 2000™	w/Hoses, Plain-Pin Spinners and Mounting Hardware	1840.00	1380.00
TM2000-QCA	Quik-Coupler Mount Adapter	68.00	51.00

HYDRA PHD

POST HOLE DIGGER

Specifications & Features

Applications

HYDRA BED®
Tractor 3-Point
Tractor Loader
Skid Loader

Hydraulic Requirements

2100 to 2500 PSI
4 to 15 GPM

Auger Information

2" Round Drive
2-9/16" Round Drive
Up to 12" Diameter

Warranty: Full 2-Year

Performance

50 RPM to 170 RPM
Up to 530 Ft/Lbs Torque

Unit Weight

107# Dry

		Retail	Dealer
HYDRA PHD™	Power Head w/Hoses and Mounting Hardware	1496.00	1122.00
AG-6	6" Standard Auger	345.00	258.75
AG-9	9" Standard Auger	486.00	364.50
AG-12	12" Standard Auger	540.00	405.00
TPF-2	3-Point Mast for Hydra PHD™	386.00	289.50
FLF-1	Loader Bucket Mounting Adapter	150.00	112.50

Standard Replacement Items

35HF	Dirt Tooth, Hard Faced 1 Side	10.00	7.50
5T30HF	Chisel Tooth, Hard Faced 1 Side	10.68	8.01
4050T	Dirt Tooth, 2009-Newer Augers	7.80	5.63
SB-30HF	3" Screw Bit, Hard Faced – Ag Auger (Pre 2009)	59.00	44.25
SB-35HF	3-1/2" Screw Bit, Hard Faced – PHA Auger (Pre 2006)	63.00	47.25
SB-35TF	3-1/2" Screw Bit, Tri Flow Pilot (PHA '06-'09 and AG 2009-)	36.00	27.00