

# HYDRA™2000

TRACTOR MOUNT

## Specifications & Features

### Tractor Requirements

Category II Three-Point  
ROPS Equipped Tractor

### Hydraulic Requirements

2500 PSI  
Pioneer Male Ends

### Grip Range

35" to 95" w/o Spinners  
18" to 77" w/Spinners  
Synchronized Arms

### Unit Weight

562# Dry

### Lifting Capacity

2000#, Limited to Safe Tractor  
Three Point Load Capacity

### Warranty

Full 2-Year

HYDRA TM 2000™  
TM2000-QCA

w/Hoses, Spinners and Mounting Hardware  
Quik-Coupler Mount Adapter

Retail  
**1840.00**  
**68.00**

# HYDRA PHD

POST HOLE DIGGER

## Specifications & Features

### Applications

HYDRA BED®  
Tractor 3-Point  
Tractor Loader  
Skid Loader

### Hydraulic Requirements

2100 to 2500 PSI  
4 to 15 GPM

### Auger Information

2" Round Drive  
2-9/16" Round Drive  
Up to 12" Diameter

**Warranty:** Full 2-Year

### Performance

50 RPM to 170 RPM  
Up to 530 Ft/Lbs Torque

### Unit Weight

107# Dry

HYDRA PHD™

AG-6

AG-9

AG-12

TPF-2

FLF-1

Power Head w/Hoses and Mounting Hardware

6" Standard Auger

9" Standard Auger

12" Standard Auger

3-Point Mast for HYDRA PHD™

Loader Bucket Mounting Adapter

Retail  
**1496.00**  
**345.00**  
**486.00**  
**540.00**  
**386.00**  
**150.00**

### Standard Replacement Items

35HF

5T30HF

4050T

SB-30HF

SB-35HF

SB-35TF

Dirt Tooth, Hard Faced 1 Side

Chisel Tooth, Hard Faced 1 Side

Dirt Tooth, 2009-Newer Augers

3" Screw Bit, Hard Faced – Ag Auger (Pre 2009)

3-1/2" Screw Bit, Hard Faced – PHA Auger (Pre 2006)

3-1/2" Screw Bit, TriFlow Pilot (PHA '06-'09 and AG 2009-)

**10.00**  
**10.68**  
**7.80**  
**59.00**  
**63.00**  
**36.00**