

# Material Safety Data Sheet



Superior Solutions

Zep Inc.  
1310 Seaboard Industrial Blvd.  
Atlanta, GA 30318  
1-877-I-BUY-ZEP (428-9937)  
www.zep.com

## Section 1. Chemical Product and Company Identification

**Product name** ZEPRIDE  
**Product use** General Purpose Cleaner and Degreaser  
**Product code** 0567  
**Date of issue** 08/11/08 **Supersedes** 02/28/05

## Emergency Telephone Numbers

### For MSDS Information:

Compliance Services 1-877-I-BUY-ZEP (428-9937)

### For Medical Emergency

INFOTRAC: (877) 541-2016 Toll Free - All Calls Recorded

### For Transportation Emergency

CHEMTREC: (800) 424-9300 - All Calls Recorded  
In the District of Columbia (202) 483-7616

## Prepared By

Compliance Services  
1420 Seaboard Industrial Blvd.  
Atlanta, GA 30318

Printing date: 01/15/09



00700

B350

TRIPLE C MFG CO  
902 HIGHWAY K 246  
SABETHA KS 66534

## Section 2. Hazards Identification

### Emergency overview

### WARNING !

CAUSES EYE AND SKIN IRRITATION. HARMFUL IF INHALED OR ABSORBED THROUGH SKIN. HARMFUL IF SWALLOWED.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

\*Hazard Determination System (HDS): Health, Flammability, Reactivity

2

0

0

### Acute Effects

### Routes of Entry

Dermal contact. Eye contact. Inhalation.

#### Eyes

Causes eye irritation. Liquid in eye may cause irritation with possible damage if not rinsed immediately. Inflammation of the eye is characterized by redness, watering and itching.

#### Skin

Causes skin irritation. Prolonged exposure may result in skin burns and ulcerations. Harmful if absorbed through the skin. Skin inflammation is characterized by itching, scaling, reddening or, occasionally, blistering.

#### Inhalation

Avoid breathing vapors, spray or mists. Inhalation of the spray or mist may produce severe irritation of respiratory tract, characterized by coughing, choking or shortness of breath. Over-exposure by inhalation may cause respiratory irritation. Can cause central nervous system (CNS) depression.

#### Ingestion

Harmful if swallowed. May cause burns to mouth, throat and stomach.

### Chronic effects

Overexposure of this product by inhalation or absorption can produce central nervous system depression resulting in headache, nausea and/or dizziness. Contains material which may cause damage to the following organs: blood, kidneys, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Additional Information: See Toxicological Information (Section 11)

## Section 3. Composition/Information on Ingredients

| Name of Hazardous Ingredients   | CAS number | % by Weight |
|---|------------|-------------|
| ETHYLENE GLYCOL MONOBUTYL ETHER; 2-butoxyethanol; butyl cellosolve      | 111-76-2   | 15 - 25     |
| SODIUM METASILICATE; silicic acid (H2-Si-O3) disodium salt; water glass | 6834-92-0  | 1 - 5       |

## Section 4. First Aid Measures

### Eye Contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.

### Skin Contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops.

### Inhalation

Move exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

**Ingestion** Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If affected person is conscious, give plenty of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Section 5. Fire Fighting Measures**

National Fire Protection Association (U.S.A.)



**Flash Point** None.

**Flammable Limits** Not applicable

**Flammability** Non-combustible.

**Fire hazard** In a fire or if heated, a pressure increase will occur and the container may burst. May emit toxic fumes under fire conditions.

**Fire-Fighting Procedures** Use an extinguishing agent suitable for the surrounding fire. Do not release runoff from fire to sewers or waterways.

**Section 6. Accidental Release Measures**

**Spill Clean up** Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Section 7. Handling and Storage**

**Handling** Put on appropriate personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Do not breathe vapor or mist. Use with adequate ventilation. Do not ingest. Do not reuse container. Wash thoroughly after handling. Observe label precautions.

**Storage** Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Store between the following temperatures: 40°F - 120°F (4.4°C - 49°C). Keep out of the reach of children.

**Section 8. Exposure Controls/Personal Protection****Product name**

ETHYLENE GLYCOL MONOBUTYL ETHER; 2-butoxyethanol; butyl cellosolve

**Exposure limits**

ACGIH TLV (United States).

TWA: 20 ppm 8 hour(s). Form:

OSHA PEL (United States). Skin

TWA: 50 ppm 8 hour(s). Form:

SODIUM METASILICATE; silicic acid (H<sub>2</sub>-Si-O<sub>3</sub>) disodium salt; water glass

Supplier Suggested (United States).

CELL: 2 mg/m<sup>3</sup> Form:**Personal Protective Equipment (PPE)**

**Eyes** Splash goggles.

**Body** Wear appropriate protective clothing to prevent skin contact.  
Recommended: Neoprene gloves. Nitrile gloves. Rubber gloves.  
Synthetic apron.

**Respiratory** Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Wear appropriate respirator when ventilation is inadequate.

**Section 9. Physical and Chemical Properties**

**Physical State** Liquid.

**pH** 12.5 - 13.5

**Boiling Point** 104.44°C (220°F)

**Specific Gravity** 1.02

**Solubility** Easily soluble in the following materials: cold water and hot water.

**Color** Clear. Blue. [Dark]**Odor** Mild.**Vapor Pressure** Not determined.**Vapor Density** Not determined.**Evaporation Rate** 1 (Water = 1)**VOC (Consumer)** 120.12 (g/l). 1.9 lbs/gal (22.6%)**Section 10. Stability and Reactivity**

**Stability and Reactivity** The product is stable.

**Incompatibility** Reactive or incompatible with the following materials: oxidizing materials and acids.

**Hazardous Polymerization** Will not occur.

**Hazardous Decomposition Products** carbon oxides (CO, CO<sub>2</sub>)

**Section 11. Toxicological Information****Acute Toxicity**

| Product/ingredient name         | Result                | Species | Dose       | Exposure |
|---------------------------------|-----------------------|---------|------------|----------|
| Ethylene Glycol Monobutyl Ether | LD50 Dermal           | Rabbit  | 680 mg/kg  | -        |
|                                 | LD50 Oral             | Rat     | 1746 mg/kg | -        |
|                                 | LC50 Inhalation Vapor | Rat     | 450 ppm    | 4 hours  |
| Sodium Metasilicate             | LD50 Oral             | Rat     | 1153 mg/kg | -        |
|                                 | LD50 Oral             | Mouse   | 770 mg/kg  | -        |

**Section 12. Ecological Information**

**Environmental Effects** No known significant effects or critical hazards.

**Aquatic Ecotoxicity**

Not available.

**Section 13. Disposal Considerations****Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

**Waste Stream** Code: D002  
Classification: - [Hazardous waste]  
Origin: - [RCRA waste.]

**Section 14. Transport Information**

| Regulatory information | UN number       | Proper shipping name                           | Classes | PG* | Label |
|------------------------|-----------------|--|---------|-----|-------|
| DOT Classification     | Not regulated.  | Not a DOT controlled material (United States). |         |     |       |
| IMDG Class             | Not determined. |  |         |     |       |

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG\* : Packing group

**Section 15. Regulatory Information****U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

**Product name**

Ethylene Glycol Monobutyl Ether

**Clean Water Act (CWA) 307:** No products were found.

**Clean Water Act (CWA) 311:** No products were found.

**Clean Air Act (CAA) 112 regulated toxic substances:** No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

**State Regulations**

**California Prop 65** No products were found.

**Section 16. Other Information**

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

\*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.