

8CYL SEMI STOCK RULES 2026

COMPETITION RULES

1. DRIVERS MUST REMAIN IN THE VEHICLE WITH HELMET, SEATBELT, EYE PROTECTION AND STEERING WHEEL ON UNTIL NOTIFIED BY AN OFFICIAL THAT IS SAFE TO EXIT THE CAR. LONG SLEEVES AND PANTS ARE REQUIRED, FIREPROOF CLOTHING IS SUGGESTED
2. 2. DRIVER ONLY IN TECH LINE IF YOU HAVE MULTIPLE VEHICLES HAVE A CREW MEMBER BRING IT UP TOGETHER OR BRING IT UP AFTER YOURSELF. YOUR CAR WILL BE TECHED ON TRAILER BEFORE UNLOADING, IT MUST BE IN LINE IMMEDIATELY AFTERWARDS
3. TECH CLOSES AT 12PM, DO NOT WAIT TO BE TECHED.
4. DRIVER DOOR HITS ARE ILLEGAL. IF THE HIT IS DEEMED BY AN OFFICIAL TO BE CARELESS OR INTENTIONAL, YOU WILL BE DISQUALIFIED. IF YOU USE YOUR DRIVER'S DOOR AS A DEFENSE, WE WILL NOT ENFORCE THE RULE.
5. NO HOT RODDING IN THE PITS. KEEP IT AT AN IDLE.
6. ANY OPEN DOOR WILL BE CAUSE FOR DISQUALIFICATION. BROKEN SEAT WILL CAUSE FOR DISQUALIFICATION.
7. YOU ARE ALLOWED ONE FIRE. IT WILL BE UP TO TECH AND FIRE DEPT. IF CAR CAN GO TO CONSI.
8. SANDBAGGING IS NOT TOLERATED AND WILL BE STRICTLY ENFORCED. LOCKING UP BRAKES PRIOR TO A HIT FOR ANYTHING OTHER THAN A DRIVERS DOOR HIT WILL BE CAUSE FOR DISQUALIFICATION. THE FANS PAY TO SEE A SHOW, PUT ONE ON FOR THEM!
9. NO TEAMING THIS WILL CAUSE FOR DISQUALIFICATION.
10. YOU MUST MAKE AN AGGRESSIVE HIT EVERY 60 SECONDS.
11. THERE IS NO ALCOHOL IN THE PITS. THIS INCLUDES PIT CREWS. IF YOU OR YOUR CREW IS CAUGHT WITH ALCOHOL, YOU WILL BE DISQUALIFIED.

GENERAL:

1. NO IMPERIALS 1973 OR OLD OR IMPERIAL SUB FRAMES a. NO HEARSEES OR AMBULANCES b. NO TRUCKS OR TRUCK FRAMES c. ANY QUESTIONS ON CAR CHOICE PLEASE ASK.
2. ALL CARS MUST HAVE A NUMBER OR SLOGAN DISPLAYED ON EACH SIDE OF

THE VEHICLE LARGE ENOUGH FOR ANNOUNCER TO READ, A ROOF SIGN IS ALSO HIGHLY RECOMMENDED. NO PROFANITY OR VULGAR SAYINGS. DRIVERS DOOR MUST BE PAINTED ORANGE

3. STOCK MEANS STOCK ALL CARS ARE CONSIDERED STOCK EXCEPT ANYTHING SPECIFIED IN THESE RULES. ALL RUST AND ROT REPAIR MUST BE OK'D BY HEAD OFFICIAL.

4. THIS CLASS IS OPEN TO ANY FWD OR RWD V8 CAR (OTHER THAN WHAT'S LISTED ABOVE).

5. CARS MUST BE STRIPPED PRIOR TO SHOWING UP TO THE EVENT, AIR BAGS MUST BE REMOVED, ALL FLAMMABLE MATERIALS MUST BE REMOVED.

6. YOU ARE ALLOWED 6 4WIRE OR 5/16 CHAIN ON HOOD, 4 ON TRUNK. WIRE OR CHAIN DOORS, 3 PER VERTICAL SEAM ONLY. YOU MAY WELD 3 THREE INCH WELDS PER VERTICAL SEAM EXCEPT FRONT DOOR TO FRONT FENDER SEAM, THESE CAN HAVE ONE 3 INCH WELD AT BOTTOM OF DOOR AND ONE AT TOP OF FENDER. HINGE AREA MUST BE OPEN FOR FIRE DEPT.

7. MOVE THE BATTERY TO THE PASSENGER SIDE FLOORBOARD OR FRONT SEAT AREA. NO MILK CRATES, NO ZIP TIES, NO ZIP SCREWS CAN BE USED. METAL BATTERY BOX, BOLTED TO THE FLOOR. **ONLY 1 BATTERY PER CAR – NO DEEP CYCLE BATTERY ALLOWED**

8. GAS TANK, ONLY FUEL CELL ALLOWED. MUST BE SECURED IN REAR SEAT AREA, NO STOCK TANKS ALLOWED. IF YOU DON'T HAVE ACCESS TO FUEL CELL, CALL WE WILL TRY TO HELP YOU.

9. ANY SHIFTER ALLOWED

10. ANY AIR-FILLED TIRE ALLOWED, DOUBLED, TUBED AND FLAPS ALL OK -**NO HOMEMADE RIMS – MAY CUT OUT 6" CENTER OF RIM AND USE UNIVERSAL LUG PLATES**

11. NO AFTERMARKET PARTS WITH THE EXCEPTION OF ANYTHING NOTED IN THE RULES.

12. TRANSMISSION COOLER ALLOWED. NO CHEAP RUBBER HOSE AND OLD HOSE CLAMPS MUST BE SAFE.

13. FLOOR MOUNTED BRAKE AND GAS PEDAL WILL BE ALLOWED ONLY 4 BOLTS NO LARGER THEN ½ IN HOLDING IT TO THE FLOOR ONLY. BOLTED TO SHEETMETAL ONLY WITH STANDARD 1/2 IN WASHER. ANYTHING EXCESSIVE WILL BE REMOVED.

14. ANY OEM CAR BUMPER OR A 3"X3" 3/16 TUBE CAN BE USED END MUST BE CAPPED WITH A ONE INCH INSPECTION HOLE IN EACH END NO EXCEPTIONS TO THIS. MUST BE STOCK NO ADDED METAL. SEAM WELDING BUMPER IS ALLOWED BUT MUST BE DONE SO IT CAN BE INSPECTED INSIDE BUMPER. YOU CAN WELD A 6"X6" 1/4 PLATE TO END OF THE FRAME RAIL TO MOUNT THE BUMPER TO NOTHING DOWN THE SIDES OF THE FRAME RAILS. BUMPER CAN BOLT TO THE PLATE WITH 4 BOLTS PER SIDE NO LARGER THEN 1/2IN OR BE WELDED DIRECTLY TO THE PLATE. THE SAME RULE APPLIES FOR MOUNTING THE REAR BUMPER. BOTH BUMPERS MUST BE 9 WIRED OR CHAINED ON IN 2 SPOTS, 3/8 CHAIN OR DOUBLE STRAND OF 9 WIRE. CAN NOT GO THREW THE BODY MOUNT **NO REPLICA FAB BUMPERS ALLOWED**

15. CAN REPLACE CORE SUPPORT BOLTS WITH 6 INCH LONG 5/8 BOLT 2 HOCKEY PUCKS AND 2 3"X3" 1/4 THICK WASHERS. ALL OTHER BODY MOUNTS **CAN BE REPLACED WITH 1 HOCKEY PUCK PER MOUNT ONLY USE 5/8 X 6" LONG BOLTS WITH 2 3" X 1/4" WASHERS. NO ADDING BOUND MOUNT LOCATIONS** MUST BE ORIGINAL AND UNTOUCHED. IF MOUNT IS BAD CALL TECH FOR REPAIR OPTION.

16. NO SUSPENSION MODIFICATIONS BESIDES REPLACING AIRBAGS/AIR SHOCKS/STRUTS FOR COIL SPRINGS FROM A CAR. NO TRUCK PARTS, OEM CAR PARTS ONLY. OEM TIE ROD, BALL JOINTS AND STRUTS. ALL CARS MUST EASILY BOUNCE AT TECH.

17. AFTERMARKET STEERING COLUMNS ARE ALLOWED BUT MUST BE SAFE WITH TECH'S OK.

18. BODY CREASING. QUARTERS MUST REMAIN VERTICAL ON FRESH AND PRE-RUN, DO NOT WEDGE THE BACK. SPEAKER DECK MUST REMAIN IN STOCK LOCATION DO NOT REMOVE IT. PRE-RAN CARS WILL HAVE TO PULL QUARTERS UP IF PUSHED DOWN. **2027 NO BODY CREASING WILL BE ALLOWED**

19. NO TUCKING

20. NO ADDED BUMPER SHOCKS.

21. HEADERS WILL BE ALLOWED

22. YOU CAN WELD YOUR REAR CENTER TO MAKE IT POSI

23. ANY MAKE ENGINE COMBINATION ALLOWED MUST BE MOUNTED IN WITH A STOCK OEM RUBBER MOTOR MOUNT. MOUNTS CAN BE WELDED ON TO ENGINE CRADLE/SADDLE WITH ONLY 8 INCHES OF WELD. 03 AND UP FORDS CAN USE A BASIC U-SHAPED MOUNT ONLY ATTACHES TO THE ALUMINUM

CROSSMEMBER IN THE 2 HOLES FOR THE MOTOR MOUNTS, CAN NOT TOUCH THE FRAME RAILS. MESSAGE WITH ANY QUESTIONS IF YOUR NOT SURE.

24. A 4-POINT CAGE WILL BE ALLOWED – FOR DRIVER PROTECTION ONLY! ANYTHING IN EXCESS WILL BE FORCED TO CUT OR LOADED AT JUDGE'S DISCRETION. CAGE BARS CAN BE NO BIGGER THAN 3X3 TUBING, SIDE BARS CAN BE NO LONGER THAN 60 INCHES AND CAN NOT GO ANY FURTHER BACK THEN WHERE THE SEAT MEETS THE KICK PANEL,. CAGE MUST BE 5 INCHES FROM FLOOR AND CENTER OF THE FIREWALL. SIMPLE TANK PROTECTOR ALLOWED, OFF THE BACK BAR MAY CONNECT TO PACKAGE TRAY FOR SUPPORT ONLY, NOT FOR REINFORCEMENT. KEEP IT TIGHT TO THE TANK, DO NOT ABUSE THIS RULE OR WE WILL TAKE IT AWAY.

25. HALO BAR ALLOWED MUST MOUNT OFF THE SEAT BAR AND RUN 90 DEGREES UPRIGHT DO NOT ANGLE THIS YOU WILL HAVE TO REMOVE IT.

26. MUST USE STOCK TRANSMISSION MOUNTS AND STOCK CROSS MEMBER.

27. LEAF SPRINGS. NO MORE THAN 6 STOCK CAR LEAFS, NO MORE THAN 4 BANDS PER SPRING PACK.

28. YOU MAY ADD 4- 4 INCH BY 4 INCH BY ¼ INCH PLATE TO FRAME RAILS FOR REINFORCEMENT. PLATES MUST REMAIN FLAT, NO MANIPULATION ALLOWED, NO BENDING OF PLATES. ALL PLATES MUST BE PAINTED WHITE AND BROUGHT TO TECH'S ATTENTION.

29. NO 9 WIRE TO BE WRAPPED AROUND ANY FRAME AROUND THE CAGE TO THE REAR END TANK PROTECTOR

30. NO LOADING HALO CAGES OF ANY KIND

31. NO STRAPPING, CHAINING OR BOLTING FRONT SUSPENSION A-ARMS, CARS MUST BOUNCE

32. NO CAGING THE RADIATOR

33. STOCK RADIATOR – NO HOMEMADE OR WATER BOXES – NO RADIATOR PROTECTOR OF ANY KIND

34. YOU ARE ALLOWED PULLEY PROTECTOR BUT MUST REMOVE WAY BAR – YOU CANNOT HAVE BOTH

35. NO STEERING BOXES ON 2003 OR NEWER FORDS

NO OFFENSIVE HEADER FLAPS

ALCOHOLIC BEVERAGES ARE PROHIBITED. ANYONE CAUGHT IN VIOLATION OF THE ALCOHOLIC BEVERAGES POLICY WILL BE ASKED TO LEAVE THE PREMISES. ALL VEHICLES WILL BE SUBJECT TO SEARCH UPON ENTRY TO THE GROUNDS. ANYONE THOUGHT TO BE UNDER THE INFLUENCE OF ALCOHOL OR ILLEGAL SUBSTANCE WILL NOT BE PERMITTED ON THE GROUNDS. VIOLATION BY ANY DRIVER OR CREW MEMBER WILL RESULT IN DISQUALIFICATION AND REMOVAL FROM THE GROUNDS.

ANY QUESTIONS CALL TEXT OR FACEBOOK MESSAGE