

IXOLIFT X400 W&WS

ADJUSTABLE WORK PLATFORM

- Simple and safe to use
- Working height up to 4 meters
- Safety compliant alternative to ladders
- Compact sized, easy to move around alone
- Automatic anti-surfing brakes for extra safety
- Patented gas spring powered height adjustment
- Eco friendly, hydraulic oil free, maintenance free
- Options: ATEX rating, Stainless steel version

TECHNICAL SPECIFICATIONS	IXOLIFT X400 W	IXOLIFT X400 WS
Working height		3974 mm
Max working load		150 kg
Max platform height		1974 mm
Min platform height		974 mm
Platform size		526 x 556 mm
Stowed height		1970 mm
Stowed length		1198 mm
Stowed width		728 mm
Total weight		230 kg
Max length with stabilisers out	N/A	1500 mm
Max width with stabilisers out	N/A	1668 mm
Wind rating	0 m/s	12,5 m/s
CE Marking	Machinery Directive 2006/42/EC EN 280:2013 + A1:2015 except §5.6.2 Guardrails based on EN 131-7 §5.6	
ATEX Marking (Optional)	ATEX Directive 2014/34/EU Ex h IIC T6 Gb & Ex h IIC T60°C Db	



PATENTED



Compact size



Automatic brakes



Gas spring powered



Tool tray



IXOLIFT Ltd | Kalkkimäentie 2 | FI-03100 Nummela, FINLAND
+358 20 741 5010 | sales@ixolift.com | www.ixolift.com

IXOLIFT X400 S

ADJUSTABLE WORK PLATFORM

- Simple and safe to use
- Working height up to 4 meters
- Transport wheels for extra mobility
- Safety compliant alternative to ladders
- Automatic anti-surfing brakes for extra safety
- Patented gas spring powered height adjustment
- Eco friendly, hydraulic oil free, maintenance free
- Options: ATEX rating

TECHNICAL SPECIFICATIONS	IXOLIFT X400 S
Working height	3974 mm
Max working load	150 kg
Max platform height	1974 mm
Min platform height	974 mm
Platform size	526 x 556 mm
Stowed height	1970 mm
Stowed length	1198 mm
Stowed width	728 mm
Total weight	150 kg
Max length with stabilisers out	1500 mm
Max width with stabilisers out	1668 mm
Wind rating	0 m/s
CE Marking	Machinery Directive 2006/42/EC EN 280:2013 + A1:2015 except §5.6.2 Guardrails based on EN 131-7 §5.6
ATEX Marking (Optional)	ATEX Directive 2014/34/EU Ex h IIC T6 Gb & Ex h IIIC T60°C Db



PATENTED



Compact size



Automatic brakes



Gas spring powered



Transport Wheels



IXOLIFT Ltd | Kalkkimäentie 2 | FI-03100 Nummela, FINLAND
+358 20 741 5010 | sales@ixolift.com | www.ixolift.com

IXOLIFT X500

PUSH IT OR DRIVE IT HYBRID INVENTION

Drive it or Push it, your choice!

- Automatic brakes
- Low maintenance
- Working height up to 5 meters
- Fits through doorways and in elevators

TECHNICAL SPECIFICATIONS	IXOLIFT X500 E-SP	
Working height	4950 mm	
Max working load	180 kg	
Max platform height	2950 mm	
Platform size	530 x 760 mm	
Guardrail height	1100 mm	
Stowed height	1640 mm	
Stowed length	1200 mm	
Stowed width	760 mm	
Total weight	320 kg	
Driving speed	Raised, 2 km/h	Lowered, 4 km/h
Lifting speed	16 s	
Power source	2pc, 75 Ah, 12V batteries, maintenance free	
Wheels	Polyurethane coating, leaves no marks	
CE Marking	Machinery Directive 2006/42/EC EN 280:2013 + A1:2015	



Decoupling



USB Socket



Self-Propelled



Push Around

2019 / v1.10



IXOLIFT Ltd | Kalkkimäentie 2 | FI-03100 Nummela, FINLAND
+358 20 741 5010 | sales@ixolift.com | www.ixolift.com