

TECHNICAL DATA SHEET

DOC NUMBER:	REVISION:	ISSUE:	DATE:
EMF-TR-002	04	00	22 NOVEMBER 2024

EMPIRE
METAL FABRICATORS
EMFab

EMFAB STEEL WIRE ROPE WITH THIMBLES



STEEL WIRE ROPE DESCRIPTION:

Swr sling 8mm (P-P) 1L c/w NEF-AF-HH & 16mm Turnbuckles Eye and Eye both ends with ID Tags. WLL 0.93 Ton @ Zero Degrees

WHY CHOOSE EMFAB'S ROOF ANCHORS:

Our range of premium lifelines can be used in a variety of conditions, including on rooftops, towers, structures, and walls. Lifelines are important because they provide a means of safety and security for workers in hazardous or high-risk environments. They are used in a variety of industries including construction, offshore drilling and rescue operations. Lifelines can prevent falls, provide a means of rescue and evacuation, and allow workers to move safely and efficiently in challenging environments. Properly installed lifelines can minimise the risk of injury or death, making them a critical component of workplace safety.

STEEL WIRE ROPE SIZE:

Thickness : 8mm

MATERIAL:

Galvanised Wire Rope

MAXIMUM PERMISSIBLE RATE OF DESCENT:

Maximum of 2 Person

MAXIMUM DESCENT DISTANCE:

6 Meters

TEST COMPLIANCE:

18,000lbs.