

TECHNICAL DATA SHEET

DOC NUMBER:	REVISION:	ISSUE:	DATE:
EMF-TR-002	04	00	19 NOVEMBER 2024



EMFAB STEEL WIRE ROPE WITH THIMBLES



→ THIMBLES

STEEL WIRE ROPE DESCRIPTION:

Swr sling 8mm (P-P) 1L c/w NEF-AF-HH and both ends with ID Tags. WLL 0.93 Ton @ Zero Degrees

WHY CHOOSE EMFAB'S ROOF ANCHORS:

With over 30 years of roofing experience amongst EMFab's Top Management, our roof anchor systems are specifically designed for different roof types with our top priority being to provide fall protection for workers who perform tasks at height. They are engineered with precision to ensure maximum safety, and our expert team can install them quickly and efficiently. All our anchors are designed and tested to carry over 15kN weight. Our fall protection equipment complies with OHSА regulations and is designed to keep workers safe while on the job.

STEEL WIRE ROPE SIZE:

Thickness : 8mm

MATERIAL:
Galvanised Wire Rope

MAXIMUM PERMISSIBLE RATE OF DESENT:
Maximum of 2 Person

MAXIMUM DESCENT DISTANCE:
6 Meters

TEST COMPLIANCE:
18,000lbs.