





FOR MORE INFORMATION CONTACT BENECOR DIRECTLY

• 1-844-BENECOR

MOST ITEMS ARE IN-STOCK & SHIP WITHIN 24 HRS

CONTACT BENECOR® FOR PART NUMBERS

NEW PRODUCT XL STANDARD DUTY SERIES

BENECOR® FLEET XL STANDARD-DUTY SERIES DISPENSING & STORAGE SYSTEMS

BENECOR® DEF FLEET XL STANDARD-DUTY & XL STANDARD-DUTYPLUS SYSTEMS DELIVER THE ULTIMATE IN PROVEN DEPENDABLE OUTDOOR DEF DISPENSING & STORAGE.

ENGINEERED FOR THE FLEET CUSTOMER

We specifically engineered our rugged system to withstand the challenging environment of the Fleet customer. Because DEF freezes at 12°F (-11°C), we offer a unique Cold Weather package designed to withstand even the harshest cold weather conditions many Fleet Customers experience.

TURNKEY — NOTHING IS FASTER OR EASIER

Our simple turnkey installation "BENECOR® PLUG & PUMP™" design will have you dispensing DEF fast. Just place the system to your pre-determined site, hookup electricity, fill with DEF and start pumping.

RELIABLE & DURABLE

Our rugged fiberglass based unit is fully tested to help ensure years of trouble-free use. Paired with the durable, high quality products you've come to expect from BENECOR®, our DEF XL Dispensing & Storage Systems are a smart solution built to suit the DEF dispensing and storage needs of the Fleet Customer.

APPLICATION FLEXIBILITY

Your DEF dispensing and storage applications may be different than others which is why BENECOR® offers our DEF XL Dispensing System in two different tanks sizes. In fact, BENECOR® offers the largest tank size (2,100 & 2,600 Gallons with the most compact foot dimensions), of comparable DEF Mini-Bulk Dispensing & Storage Systems on the market.

STANDARDS / APPROVALS

All BENECOR® DEF Standard Duty Dispensing & Storage Systems meet the ISO 22241-3 & 4 standards for the dispensing and storage of DEF.



SIDE DISPENSER | LEFT, RIGHT, LEFT & RIGHT



FRONT DISPENSER

HEIGHT DEPTH WIDTH

1-SIDED - LEFT

THE FOLLOWING MEASUREMENTS INCLUDES ALL XL STANDARD-DUTY SERIES PRODUCTS:

- XL STANDARD-DUTY STORAGE
- XL STANDARD-DUTY & STANDARD-**DUTYPLUS DISPENSING & STORAGE**

SIZE DIMENSIONS

2100 G 49.2"W x 99.8"H x 191.5" D 2600 G 49.2"W x 99.8"H x 233.1" D THE FOLLOWING MEASUREMENTS INCLUDES ALL XL STANDARD-DUTY SERIES SIDE DISPENSER PRODUCTS:

1-SIDED - RIGHT

XL STANDARD-DUTY & STANDARD-**DUTYPLUS DISPENSING & STORAGE**

SIZE DIMENSIONS

2100 G 49.2"W x 99.8"H x 191.5" D 2600 G 49.2"W x 99.8"H x 233.1" D

THE **INDUSTRIES MOST ECONOMICAL** & COMPACT **SYSTEMS STORAGE SYSTEMS COMPATIBLE WITH ALL 3RD PARTY DISPENSERS**

XL STANDARD-DUTY FEATURES () () ()



2-SIDED - LEFT & RIGHT





- BENECOR® 1/2 HP DEF Submersible Pump
- Automatic DEF Stainless Steel Nozzle with Breakaway Swivel
- 20' Hose & All Necessary Hose Hardware
- Integrated Nozzle Boot Switch Relay to Operate Pump

ENCLOSURE

- Pre-Wired & Pre-Piped for Simple Fast & Easy Installation
- Roof Accessibility For Service
- Environmentally Safe 110% Secondary Containment
- Fiberglass Enclosure With Stainless Steel Piping
- UL, cUL Enclosed Electrical Panel & Components
- Forklift Accessible
- Stainless Steel Overfill Prevention Valve
- Lockable Fill Box

XL STANDARD-DUTYPLUS ADDITIONAL FEATURES

- Front Door Protects Nozzle
- 20' Hose Reel

XL STANDARD-DUTY OPTIONAL FEATURES INCLUDE

- BENECOR® DEF Pulse Meter with Digital Display
- External Digital Level Display
- Remote Level Monitoring System (Veeder-Root or others)
- Adjustable base with legs
- Exhaust fan
- Cold Weather Package
- Strobe Light To Warn Against Low Temperature Inside Enclosure
- Low Level Warning Light
- Thermostatically Controlled Heater

IN-STOCK & SHIP WITHIN 24 HRS 1 - 8 4 4 - 2 3 6 - 3 2 6 7

FOR MORE INFORMATION CONTACT BENECOR DIRECTLY

MOST ITEMS ARE

CONTACT BENECOR® FOR PART NUMBERS

