

SPECIFICATION SHEET



Zip **HydroBoil®** on wall water boiler range (4th Generation) 澳洲捷寶牌掛牆式滾水機

Model Code	Capacity (Litres)	Recovery (167ml cups/hour)	Rating (kW)	Voltage	Dimensions W×D×H (mm)	Filled Weight (kg)
403752	3.0	100	1.4	220-240V	300 185 440	12
405752	5.0	140	2.2	220-240V	330 210 473	15
407752	7.5	140	2.2	220-240V	330 210 590	20
415752	15.0	175	2.8	220-240V	405 310 608	33
425752	25.0	175	2.8	220-240V	405 310 788	47
440752	40.0	360	5.4*	220-240V	530 390 850	70

*Two Element Kits used

Identification of New Model Codes Listed

The first digit represents a code of generation

The second and third digits represent the capacity in litres

The fourth digit represents a country code – "7" Foreign

The fifth digit represents the product – "5" HydroBoil on wall water boiler

The last digit represents a code of external casing – "2" White

- Type : twin chamber technology instant boiling water heater
- Boiling chamber : NSF Approval Fortron® 1149 PPS
- New design of cistern chamber : more efficient
- Safety features : in addition to a thermal cutout integral to heating element, an extra thermal cutout is also included to prevent accidental damage in the event of pipe blockage or thermostat failure.
- Tap Safety : available safety options as an accessory
- Insulation : compressed high temperature insulation panels

TECHNICAL INFORMATION

KL001_LOWB Export_v2_03.19

