

GLASS ACOUSTIC



DEMOUNTABLE WALL SYSTEM WITH HIGH ADJUSTABILITY FOR DOUBLE GLAZING WITH SIMPLIFIED INSTALLATION.



PRODUCT FEATURES



Enhanced light penetration
Minimal extrusions
Surface or recessed mounted
20mm (3/4") installation tolerance

Double glazing
Integrated floor to ceiling pivot doors available as frameless, acoustic framed, or solid wood.

STANDARDS

Wall thickness:	108mm (4 1/4")
Minimum panel width:	200mm (8")
Maximum panel width:	1200mm (4')
Maximum panel height:	3500mm (11'6")
Top profile height:	38-66mm (1 1/2"-2 1/2")
Bottom profile height:	38mm (1 1/2")
Sound Rating:	46

GLASS THICKNESS

10 or 12mm (3/8" or 1/2")

STANDARD JOINT

High transparency acoustic I shaped PVC profile

STANDARD WARRANTY

5 years

DOORS



Flush Double Glazed:	108mm (4 1/4")
Double Glazed:	50mm (2")
Single Glazed:	10mm (3/8")
Standard Solid:	50mm (2")
WOD Glass Acoustic:	50mm (2")
Flush Solid:	108mm (4 1/4")