



EASYLIFT OVERHEAD SECTIONAL DOOR

PICTURE 1 & 2 : VIEW FROM OUTSIDE



PICTURE 3 & 4 : VIEW FROM INSIDE



SPARE PARTS OF SECTIONAL DOOR



Spring bumper



Torsion



AAVAQ control panel



AAVAQ motor

STANDARD LIFTING



HIGH LIFTING



VERTICAL LIFTING



TECHNICAL DETAILS

- **Brand:** Easylift
- **Panel Foam:** Polyurethane foam
- **Panel Thickness:** 42mm
- **Panel Skin:** High quality, PPGI galvanized steel 0.45mm
- **Unique Design Panel:** 2pcs reinforcement steel sheet (size: 41mm foam with 0.9mm thick are laid at the hinges installation positions to make door hinges installed with stronger & firmer grip throughout full length with panel)
- **Foam Density:** 45kg/cbm
- **Heat Conductive:** 0.24w/(Mk)
- **Gemlin:** 0.033w/(mk)
- **Heavy-Duty Galvanized Steel Hardware:** available in 2" width and 3" width
- **Track's Thinness:** 2mm
- **Adjustable Brackets Thicknesses:** 2.5mm
- **Bearings and Brackets Thicknesses:** 2.5mm
- **High Quality Nylon Roller:** 2"
- **Shaft:** Solid shaft in galvanized steel, Diameter 25.4mm with key way
- **High Quality Springs:** Oiled spring and galvanize springs are all available



IGT SUPPLIES SDN BHD

35 JALAN TP 7/7, TAMAN PERINDUSTRIAN UEP,
40400 SHAH ALAM, SELANGOR, MALAYSIA.
Tel: 012-3389833 / (60)3-56143343 / (60)3-51914746
E-mail: ivan@igtgroup.com.my / enquiry@igtgroup.com.my
www.igtgroup.com.my