

EASYSHELTER DOCK SHELTER

PROJECT EXAMPLES











IGT SUPPLIES SDN BHD

35 JALAN TP 7/7, TAMAN PERINDUSTRIAN UEP, 40400 SHAH ALAM, SELANGOR, MALAYSIA. Tel: 012-3389833 / (60)3-56143343 / (60)3-51914746 E-mail: <u>ivan@igtgroup.com.my</u> / <u>enquiry@igtgroup.com.my</u> www.igtgroup.com.my

TECHNICAL DETAILS

Brand: EasyShelter

Model: ES343460

• Size:

3400mm(W) x 3400mm(H) x 600mm Depth

• Top Curtain: 1000mm (H)

Side Curtain:

- 600mm

- 3mm thick PVC with reinforce 3700g/m²

- 4 navigation yellow arrow

MECHANICAL LOADING DOOR SEAL MADE OF ALUMINIUM PROFILES FROM THE FRONT FRAME & THE REAR FRAME COMPOSITION, CONNECTED TO EACH OTHER VIA BRACKET

FRAME STRUCTURE WITH REINFORCED POLYESTER FIBER FABRIC WRAP. WHEN THE VEHICLE PARKED IS NOT ACCURATE, THE SIDES AND TOP DOOR SEAL DUE TO SQUEEZE RETRACTED

SPECIFICALLY DESIGNED TO PROVIDE ADDITIONAL FLEXIBILITY DURING THE LOADING & UNLOADING OF VEHICLES OF DIFFERENT SIZES THAT MAKE IT EASIER FOR DRIVERS TO MANOEUVRE, AND AVOID COLLISIONS THAT COULD DAMAGE THE FACILITY AND VEHICLE

THE FACILITY IS INSULATED FROM THE OUTSIDE, WHEN GOODS ARE TRANSFERRED, SAVING ENERGY AND ULTIMATELY MAKING THE WORK AREA MORE COMFORTABLE