

Lighting Specifications

Dimmers	120 x 2kw Dimmer Modules 12 x 5kw Dimmer Modules 40 x 2kw Portable Dimmer Modules	8 x 40 amp 3 Phase + N + E PDL outlets 400 amp 3 phase Stud connection 6 x 40amp 3 Phase + N + E PDL outlets
Power supply for portable dimmers	Dimmer Room Stage	
Patch	425 x 10 amp circuits to various outlets	
Data System	DMX 512 Patching to all technical areas	
Control	Grand MA2 lite	
House Lights	Remote from Stage & Console	
Luminaries	Martin Mac 500 Intelligent lights (hired separately - POA) ETC Source Four LED Series 2 Chauvet COLORado, 2-Quad zoom Tour Selecon 1 kW Pacific Zoom Spot Medium Selecon 1 kW Zoom Spot Narrow 8-16 Selecon 1 kW Zoom Spot Medium 24-40 Selecon 1 kW Zoom Spot Wide 18-34 Selecon 2 kW Fresnel Selecon 1 kW Fresnel Selecon 2 kW PC Luminaire Selecon 1 kW PC Luminaire Par Cans Selecon 4 Cell Cyclorama Top Lighting Selecon Performer Followspots Strand Patt 265 Followspots Selecon 1 kW Floods Adjustable Iris Units Gobo Holders Telescopic Stands Boom Arms	10 32 i6 on ladders / 16 in bridges 24 x6 per LX 14 10 9 43 18 24 6 8 48 2 2 2 8 12 2 2



Lighting Specifications

Spot Bars	Spot Bar Truss Sections 14 metre Multi-Core Cables	5
	16.5 metre Multi-Core Cables	5
	19 metre Multi-Core Cables	5
	21.5 metre Multi-Core Cables	5
	24 metre Multi-Core Cables	5
	26.5 metre Multi-Core Cables	5
	Side Lighting ladders	8
	5 Way Multi-Core Looms	8
	FOH Side Lighting Frames	2
	10 Way Multi-Core Looms	