



SUPTECH
INTERNATIONAL TRADE PTY LTD

Main specifications	BL200L	BL250L	BL250FL
Swing over bed	220mm	250mm	250mm
Swing over carriage	150mm	130mm	140mm
Centers distance	580mm	750mm	720mm
Spindle bore diameter	22mm	27mm	27mm
Spindle taper	MT3	MT4	MT4
Spindle speed range	6 / 170~2000r/min	6 / 140~2000r/min	6 / 140~2000r/min
Metric threads	0.4~3 mm	0.2~3.5 mm	0.2~3.5 mm
Imperial threads	8~28 1/n#	8~56 1/n#	8~56 TPI
Longitudinal travel	70mm	70mm	70mm
Transverse travel	115mm	115mm	115mm
Longitudinal auto feeding	0.05~0.20mm/r	0.05~0.10mm/r	0.05~0.10mm/r
Tailstock taper	MT2	MT2	MT2
Tailstock sleeve travel	40mm	70mm	70mm
Lathe motor power	900W	900W	750W
Machine N.W./G.W.	128/145kg	165/185kg	165/185kg
Machine overall size	110*40*45cm	143*40*48cm	143*42*50cm
Machine packing size	122*57*60cm	148*57*60cm	148*57*60cm

