



Brisbane Fridge and Freezer Seals
07 3849 4126
admin@brisbaneseals.com.au
341a Kelvin Grove Rd, Kelvin Grove
ABN: 126 6848 9272

HOW TO FIT YOUR SEAL

Push in Seal

1. Firstly ensure you have been supplied the correct replacement fridge seal by holding it up against the existing fridge seal. Assuming it matches, if the seal was folded for freight and doesn't sit flat, unfold and lay on the floor for 30min in a warm area to flatten. If flat, move on to step two.
2. Gently pull the existing seal out of the retaining track, being careful not to damage the retainer.
3. Starting with the top two corners, position the seal's arrowhead in the retainer cavity and apply pressure.
4. Once the top two corners are inserted move on to the bottom two corners.
5. Gently press the rest of the seal into the track, ensuring the arrowhead has pushed into the retainer entirely.
6. With the door open, apply VERY LIGHT heat using a hair dryer or low temp heat gun to the face of the seal.
7. Close the door, firmly pressing it shut to allow the magnet to make contact.
8. If there are any gaps visible, apply VERY LIGHT heat using a hair dryer or low temp heat gun to the side of the seal where the gap is visible.
9. Once all sides are sealing (including the bottom) leave the door shut for 1hour to allow the seal to cool down and set in position.