

RICHLAND MICRO DRAINAGE LLC



8105 Malone Rd, Shiloh, OH 44878



(419) 896-3623

www.richlandmicrodrainage.com

MICRO PLOW 2448 SPECIFICATIONS

- Approximate weight: 2,000 lbs.
- Minimum weight requirement: 17,000 lbs.
- Minimum horsepower requirement: 100 HP
- Three-point hitch size category: 3 and 4N
- Boot sizes: 2,3,4 and 6
- Maximum plow depth: 48 in.
- Replaceable shear, cone and poly sides
- Shorter boot lengths for less resistance
- Proportional control valve for accuracy

DON'T MISS OUT ON ALL OF THE BENEFITS!



Begin increasing your crop yields today!
Contact us for more information.

THE BENEFITS OF THE MICRO DRAINAGE CONCEPT

✓ PERPENDICULAR DRAINAGE

- **Installed perpendicular** to water flow
- Using GPS allows you to install this way

✓ SHALLOW DRAINAGE & CLOSER SPACINGS

- **Closer lateral spacing** - 20' or less
- **Shallow depth** – typically about 24" down
- Quicker drainage to field capacity
- More reserve water in dry year
- Quicker in fields after rain
- Less compaction
- Better root development
- Plants are less stressed
- Quicker and higher amounts of organic matter

✓ WHY 2" DRAINAGE PIPE?

- **Less likely to become clogged** - because of narrower spacing, it exceeds the capacity needs
- More velocity and sharper profile keeps silt buildup to a minimum
- More footage on maxi roll
- Easier to install, less horsepower
- Faster ROI, lower equipment investment

