

RICHLAND MICRO DRAINAGE LLC



8105 Malone Rd, Shiloh, OH 44878



(419) 896-3623

www.richlandmicrodrainage.com

CONTRACTORS MICRO PLOW CP-100 SPECIFICATIONS

- Approximate weight: 4,000 lbs.
- Minimum weight requirement: 25,000 lbs.
- Minimum horsepower requirement: 150 HP
- Adapter kits available for tractor and dozer
- Boot sizes: 2,3,4,6 and 8
- Maximum plow depth: 60+ in.
- Replaceable shear, heel, cone, wedge and SS sides
- Shorter boot lengths for less resistance
- Tile cutter/feeder is standard
- Five bank valve kit with controller and joystick for load sensing pressure compensated hydraulic pump

DON'T MISS OUT ON ALL OF THE BENEFITS!



Begin increasing your crop yields today!
Contact us for more information.

THE BENEFITS OF THE MICRO DRAINAGE CONCEPT

✓ PERPENDICULAR DRAINAGE

- **Installed perpendicular** to water flow
- Using GPS allows you to install this way

✓ SHALLOW DRAINAGE & CLOSER SPACINGS

- **Closer lateral spacing** - 20' or less
- **Shallow depth** – typically about 24" down
- Quicker drainage to field capacity
- More reserve water in dry year
- Quicker in fields after rain
- Less compaction
- Better root development
- Plants are less stressed
- Quicker and higher amounts of organic matter

✓ WHY 2" DRAINAGE PIPE?

- **Less likely to become clogged** - because of narrower spacing, it exceeds the capacity needs
- More velocity and sharper profile keeps silt buildup to a minimum
- More footage on maxi roll
- Easier to install, less horsepower
- Faster ROI, lower equipment investment

