

**RICHLAND MICRO DRAINAGE LLC**



8105 Malone Rd, Shiloh, OH 44878



(419) 896-3623

[www.richlandmicrodrainage.com](http://www.richlandmicrodrainage.com)



## MICRO CART MODEL S6 SPECIFICATIONS

- Table: 9' 6"
- Axle rating: 5,200 lb
- Number of axles: 1
- Axle type: torsion
- Tire size: St225/75R15 10Ply radial tire
- Hub size: 6-5.5 trailer hub
- Reel brake: rubber pad

## DON'T MISS OUT ON ALL OF THE BENEFITS!

### 1. FUNCTION AND PERFORMANCE

- Wing on platform folds to handle part rolls
- Torsion axle for smoother ride on rough terrain
- Self-centering to maintain roll in center of platform
- Support arms maintain tile on platform
- Top ring to support maxi roll
- Faster return, lower equipment investment

### 2. AVAILABLE OPTIONS FOR MICRO CART

- Dual axle for more flotation
- Upgrade to self-contained hydraulic unit
- Lights for road transport
- Brakes for extra safety

## THE BENEFITS OF THE MICRO DRAINAGE CONCEPT

### ✓ PERPENDICULAR DRAINAGE

- **Installed perpendicular** to water flow
- Using GPS allows you to install this way

### ✓ SHALLOW DRAINAGE & CLOSER SPACINGS

- **Closer lateral spacing** - 20' or less
- **Shallow depth** – typically about 24" down
- Quicker drainage to field capacity
- More reserve water in dry year
- Quicker in fields after rain
- Less compaction
- Better root development
- Plants are less stressed
- Quicker and higher amounts of organic matter

### ✓ WHY 2" DRAINAGE PIPE?

- **Less likely to become clogged** - because of narrower spacing, it exceeds the capacity needs
- More velocity and sharper profile keeps silt buildup to a minimum
- More footage on maxi roll
- Easier to install, less horsepower
- Faster ROI, lower equipment investment

