LDXTM Series Hose Reels The Ultimate Industrial-Grade Hose Reel



High-Quality Construction, Consistent Performance

Designed with an all-metal frame and specially crafted components; Graco LDX hose reels ensure smooth release and retraction to optimize confidence in cost-conscious smaller garages, independent repair facilities and industrial manufacturing environments.

Large Hose Capacity with Small Profile

Compact design accommodates up to a 50 foot (15 meter) hose to meet a wide variety of application requirements.

Adjustable Arm

Easily change to one of five arm positions to fit your application.

Ball Bearing Swivel

Swivel designed with internal ball bearings reduces friction and ensures smooth operation.

External Swivel Housing

Quickly access swivel seal for faster repairs.

Dual Pedestal Frame

Ribbed metal for increased stability and robustness.

PROVEN QUALITY. LEADING TECHNOLOGY.

Typical Applications

- Industrial manufacturing facilities
- Small maintenance shops
- Tire maintenance shops
- Small fast lubes
- Independent repair facilities

Typical Fluids Handled


- Petroleum- and synthetic-based oils (motor, gear and ATF)
- Air
- Water
- Grease
- Antifreeze
- Windshield washer fluid
- Diesel exhaust fluid (DEF)

Technical Specifications


Operating Temperature Range

opt	stating remperatore nange				
	Air/Water/Antifreeze/Windshield Washer Fluid	14.5°F to 149°F (-26°C to 65°C)			
	DEF	-40°F to 158°F (-40°C to 70°C)			
	Oil	-40°F to 212°F (-40°C to 100°C)			
	Grease	-40°F to 212°F (-40°C to 100°C)			
Wetted Parts					
	Air/Water/Antifreeze/Windshield Washer Fluid Reels	EPDM, stainless steel, fluorocarbon (FKM)			
	DEF Reels	Hybrid polymer, brass, nitrile rubber			
	Oil Reels	Zinc-plated steel, brass, polyurethane, nitrile rubber			
	Grease Reels	Zinc-plated steel, brass, nitrile rubber			
Sound Pressure Level		80 dB(A)			
Sound Power Level		87 dB(A)			
Instruction Manual		3A8216			

Dimensions A 3.5 in (89 mm) B 7.5 in (191 mm) C 4.9 in (125 mm) D 8.7 in (221 mm) E 19.0 in (483 mm) F 9.4 in (239 mm) G 17.5 in (445 mm)



Typical Mounting Configurations



Bench Mount



>>> Ordering Information

LDX Reels

Part Number	Fluid	Hose		Connection Size		Maximum
Fait Nullibei		ID (in)	Length (ft)	Inlet (in)	Outlet (in)	Pressure PSI
HEL010	Air/Water/Antifreeze/Windshield Washer Fluid	3/8	50	3/8 NPT	3/8 NPT	300
HEL015	DEF	1/2	45	1/2 NPT	1/2 NPT	150
HEM004	Oil	1/2	50	1/2 NPT	1/2 NPT	1,500
HEH006	Grease	3/8	50	3/8 NPT	3/8 NPT	4,060

Inlet Kits

Part Number	Fluid
25U369	Air/Water/Antifreeze/Windshield Washer Fluid
25U370	DEF
25U371	Oil
25U372	Grease

©2021 Graco Inc. 353083 Rev. A 9/21 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice. For more information on Graco's intellectual property, see www.graco.com/trademarks.

Contact us today!



Call **800-533-9655** to speak with a Graco representative, or visit **www.graco.com** for more information.