

VITI TESTA CILINDRICA CAVA ESAGONALE

HOLO-KROME UNC - UNF (1960 - 1936 series)

Resistenza a trazione min. 170.000 psi

Durezza Rockwell min. 37

Allungamento min. 8%

d		filetti x pollice		d _k		s		k
diametro filettatura		UNC	UNF	diam. testa Max		chiave		altezza
				1936 s	1960 s	1936 s	1960 s	testa
pollici	mm			mm		pollici		mm
N. 4	2,84	40	48	4,65	4,65	5/64	3/32	2,84
N. 5	3,17	40	44	5,21	5,21	3/32	3/32	3,17
N. 6	3,5	32	40	5,74	5,74	3/32	7/64	3,5
N. 8	4,17	32	36	6,86	6,86	1/8	9/64	4,17
N. 10	4,82	24	32	7,92	7,92	5/32	5/32	4,83
1/4	6,35	20	28	9,52	9,52	3/16	3/16	6,35
5/16	7,93	18	24	11,1	11,9	7/32	1/4	7,92
3/8	9,52	16	24	14,3	14,3	5/16	5/16	9,52
7/16	11,11	14	20	15,9	16,7	5/16	3/8	11,1
1/2	12,7	13	20	19	19	3/8	3/8	12
5/8	15,88	11	18	22,2	23,8	1/2	1/2	15,9
3/4	19,05	10	16	25,4	28,6	9/16	5/8	19
7/8	22,22	9	14	28,6	33,3	9/16	3/4	22,2
1"	25,4	8	12	33,3	38,1	5/8	3/4	25,4

