

MODELO		DESP. DE AIRE		HP/KW		R.P.M		CILINDROS		ETAPAS		PRESIÓN MAX.		CAPACIDAD		PESO
C 750 B		90 Lts/min		0,75 / 0,55		700		1		1		100 Lbs		70 Lts.		54 Kg
C 1000 B		157 Lts/min		1 / 0,75		700		1		1		100 Lbs		95 Lts.		63 Kg
C 1500 A/B		170 Lts/min		1,5 / 1,1		700		2		2		150 Lbs		140 Lts.		90 Kg
C 2000 A/B		235 Lts/min		2 / 1,5		600		2		2		150 Lbs		140 Lts.		102 Kg
C 2000 B/B		275 Lts/min		2 / 1,5		600		2		1		120 Lbs		140 Lts.		95 Kg
C 3000 B/B		400 Lts/min		3 / 2,2		600		2		1		120 Lbs		180 Lts.		110 Kg
C 3000 A/B		360 Lts/min		3 / 2,2		580		2		2		170 Lbs		180 Lts.		137 Kg
C 5500 B/B		780 Lts/min		5,5 / 3		580		2		1		120 Lbs		285 Lts.		160 Kg
C 5500 A/B		625 Lts/min		5,5 / 3		550		2		2		180 Lbs		285 Lts.		235 Kg
C 7500 B/B		1250 Lts/min		7,5 / 5,5		550		2		1		120 Lbs		330 Lts.		250 Kg