

## Air-Water Heat Pump 50/100 kW high temperature



### LW 50/100 HT v2.5

Range of application :

- ▶ external air as energy source
- ▶ for heating, cooling and domestic hot water
- ▶ new construction and refurbishment

- ▶ External temperature based e-TALK controller with mixer and domestic hot water control
- ▶ Fully-automatic operation for heating and cooling
- ▶ Modularly expandable through cascading
- ▶ Phase sequence integrated monitoring
- ▶ Fully hermetic compressor heat pump
- ▶ Utilizes external air as energy source
- ▶ Flow temperature up to 73 °C
- ▶ Extremely silent operation
- ▶ With Refrigerant R513A
- ▶ Refrigerant GWP of 631
- ▶ Security group A1
- ▶ Remote monitoring

Clime average

**Efficiency class**  
**A+++**

Operating point	Heating capacity*	Power consumption (kW)	Current consumption per compressor (A)	Coefficient of Performance** (COP/EER)	Refrigeration capacity (kW)	Cooling capacity (kW)
-----------------	-------------------	------------------------	--	--	-----------------------------	-----------------------

## LW 50 kW HT

A 10/W 35	56,8	10,9	10,3	5,2	45,9	-
A 10/W 55	49,9	15,9	13,5	3,1	34,0	-
A 7/W 35	51,3	10,8	10,2	4,7	40,5	-
A 7/W 55	45,3	15,8	13,4	2,9	29,5	-
A 2/ W 35	43,0	10,7	10,1	4,0	32,3	-
A 2/ W 55	39,5	15,5	13,2	2,5	24,0	-
A -7/ W 35	31,1	9,9	9,5	3,1	21,2	-
A -7/W 55	32,1	14,5	12,7	2,2	17,6	-
A 30/W 7	-	-	-	-	-	-
A35/W7	-	14,0	-	3,1	-	43,8
A35/W16	-	14,2	-	4,3	-	61,6

## LW 100 kW HT

A 10/W 35	113,7	22,1	10,3	5,1	91,6	-
A 10/W 55	100,1	31,1	13,5	3,2	69,0	-
A 7/W 35	102,6	21,1	10,2	4,9	81,5	-
A 7/W 55	90,5	30,5	13,4	3,0	60,0	-
A 2/ W 35	86,0	20,4	10,1	4,2	65,6	-
A 2/ W 55	79,2	30,1	13,2	2,6	49,1	-
A -7/ W 35	61,2	19,8	9,5	3,1	41,4	-
A -7/W 55	61,1	28,3	12,7	2,2	32,8	-
A 30/W 7	-	-	-	-	-	-
A35/W7	-	28,0	-	3,1	-	87,5
A35/W16	-	28,5	-	4,3	-	123,1

## LW 50 kW HT

Clime	$\eta_s$ (%)** 35 °C	$\eta_s$ (%)** 55 °C	sound pressure level in dB/A			soundpower in dB/A
	average	average	1m	5m	10m	
	A+++	A++	60	46	40	67

## LW 100 kW HT

Clime	$\eta_s$ (%)** 35 °C	$\eta_s$ (%)** 55 °C	sound pressure level in dB/A			soundpower in dB/A
	average	average	1m	5m	10m	
	-	-	60	46	40	67

\* all output specifications in accordance with DIN 14 511

\*\* seasonal energy efficiency in heating

LW 50/100 HT v2.5

	50 kW	100 kW
<b>Condenser</b>		
Type	plate heat exchanger	
Recommended volume flow	7.410 l/h	14.830 l/h
Pressure loss at nominal volume	9,4 kPa	3,2 kPa
Max. operating pressure	30 bar	
Max. temperature	150 °C	
Connections heating (external thread, flat sealing)	2"	2 ½"
Max. / min. inlet temperature (heating)	73 °C / 25 °C	
Max. / min. inlet temperature (cooling)	18 °C / 7 °C	

<b>Evaporator</b>		
Type	Finned-tube heat exchanger	
Insulation	PVC- and CFC-free	
Recommended volume flow	6.700 m <sup>3</sup> /h	13.500 m <sup>3</sup> /h
Number of fans	4	8
Max. operating pressure / temperature	45 bar	
Source connections	none	
Max. / min. source inlet temperature (heating)	35 °C / -15 °C	
Max. / min. source inlet temperature (cooling)	40 °C / 20 °C	
Expansion valve	electronical	

<b>Cooling cycle</b>		
Compressor	Scroll, fully hermetic	
Quantity	2 pieces	4 pieces
Insulation cooling cycle	PVC- and FCKW-free	
Refrigerant	R 513 A	
Filling capacity	17,0 kg	23,0 kg
Ester oil content	5,6 liters	11,2 liters
Ester oil	Idemitsu Hermetic Oil FV68S	

<b>Housing</b>			
Dimensions	W	2310 mm	2130 mm
	D	1365 mm	2260 mm
	H	1550 mm	2265 mm
Weight	780 kg	1800 kg	
Material / sound insulation	steel sheet (powder coated) RAL 7016/soundproofed		

LW 50/100 HT v2.5

	50 kW	100 kW
<b>Electrical data</b>		
Nominal voltage (heat pump)	3 Ph / 50 Hz / 400 V	
Nominal voltage (control)	1 Ph / 50 Hz / 230 V	
Compressor startup current (with soft-start)	67,0 A	2x 67,0 A
Max. compressor operating current	60,4 A	2x 60,4 A
Type of protection	IPX 4	

<b>Electrical connections</b>		
Fuse protection slow-blow (compressor 1+2)	D 63 A - 3/4 pol.	D 63 A - 3/4 pol.
Fuse protection slow-blow (compressor 3+4)	-	D 63 A - 3/4 pol.
Fuse protection control/fan	B 16 A 1/2-pol.	
Supply compressor* 1+2	5 x 16 mm <sup>2</sup> flexible	5 x 16 mm <sup>2</sup> flexible
Supply compressor* 3+4	-	5 x 16 mm <sup>2</sup> flexible
Supply control/fan*	3 x 2,5 mm <sup>2</sup> flexible	

\* The width for the supplies is to be configured depending on the laying and length

	50 kW	100 kW
Product-No.	1450 0050	1450 0100

**Accessories (optional):**

Description	Product-No.
EMM electrical cabinet for LW 35kW up to LW 150kW	2200 0120

