

Synthetic Roofing Underlayment



Whether you're stocking warehouses or supplying crews across multiple regions, we deliver the materials you rely on at the scale your business demands

Features

- 10 Times Stronger than regular Type 15# felt.
- Resistant to tear & stretch around fasteners.
- Skid-resistant polymer coating provides traction and a safer working surface.
- Wider offering greater coverage.
- 100% recyclable material, manufactured from recyclable material.
- More effective and lighter in comparison to regular Type 15# felt.
- Won't crack, buckle or warp: Framers Wrap synthetic roofing underlayment will support no-mold, no oil leaching and has no hazardous properties.
- Enhanced UV Resistant.
- Printed nailing pattern and overlap lines for speedy installation.



**PRINT
YOUR LOGO
HERE!**

Attract new customers and increase awareness in your local area! Visit our website for more information.

Specifications	Data	Standards
Size per roll	48" x 250'	-
100% recyclable	Yes	-
Material composition	Polyolefin	-
UV resistance	90 days	-
Breaking strength	152 lb(69 kg)/133 lb(60 kg)	ASTM D5034 MD/CD
Tear Strength	27 lb(12 kg)/ 24 lb(11 kg)	ASTM D4533 MD/CD
Water shower exposure	Pass	ASTM D4869
Permeability	<0.05 Perms	ASTM E96
Mullen burst	103 psi	-
Nominal thickness	10 mils	ASTM D1777
Temperature range	-40°F to 240°F	-
Nominal thickness	Excellent	-



Our Mission

To provide distributors and contractors with reliable, high-quality building materials at competitive bulk rates. Backed by decades of construction industry experience, our team understands what it takes to keep projects moving forward - on time and on budget.

