

DO-160 & MIL-STD-461G

Indirect Lightning Effects Test System

AVI-LV5





This document has been
optimized for electronic media



Smart navigation through technical
specifications. Click the green links.



Accredited Calibration

Quality at EMC PARTNER is based on an ISO 9001 management system. This is the foundation for an ISO 17025 accreditation verified by the Swiss Calibration Service (SCS). SCS No. 146 is the accreditation number of EMC PARTNER AG. Locally accredited but recognized worldwide through affiliation with the ILAC organisation



WHEN GETTING RESULTS MATTERS

THERE IS ONLY ONE CHOICE

Avionics and military testing is all about quality and precision. AVI-LV5 is the answer for these requirements.

A flexible solution that includes:

- › RTCA DO-160G: SECTION 22, Level 5
- › EUROCAE ED-14G: SECTION 22, Level 5
- › MIL-STD-461: CS117 internal & external equipment test levels

Ease of use, advanced functionality and options make AVIL-LV5 the most efficient and technically advanced instrument in this category.

MODERN AND EFFICIENT

THE LATEST SOLUTION FOR INDIRECT LIGHTNING EFFECTS TESTING

AVI-LV5 is the first EMC PARTNER system to fully integrate all waveforms from MIL-STD-461G and RTCA DO-160 (level 1 to level 5) as standard. Combined with only two couplers, AVI-LV5 is a compact and resourceful solution to indirect lightning testing needs.

Ready for custom WF3 CB plugins for additional frequencies (contact sales)

Power blocking devices for generator protection during PIN tests included in generator

Optional transient blocking devices for power supply protection during pin injection tests (direct injection method)

WF 5A voltage and WF 5B included as standard features of AVI-LV5-CB generator

Only two injection transformers for all levels, all waveforms: faster generator performance verification and testing

Adjustable MS subsequent stroke level with EXT-AVI5-MS.
Optional 30 strokes module available with OPT-MS-30

Increased energy available for higher impedance cable bundles

Three-phase LISNs with optional DC voltage extensions available with 5 μ H per line

POWERFUL AND RELIABLE

AVI-LV5 is a compact system that includes all waveforms for RTCA DO-160: Section 22 and MIL-STD-461G: CS117 testing. All event types are available for PIN Injection and Cable Bundle tests.

- › Quad-core processor, 1.2 GHz
- › 1 Gbps Ethernet port for fast communication with computer
- › 7" capacitive touch-screen with refined GUI, proprietary operating system
- › Solid-state switching technology increases reproducibility and reliability
- › TEMA3000-AVI software suite provides sophisticated automation functions
- › Quick and simple firmware and software updates
- › Seamless test bench integration possibilities: with its programmable bi-directional BNC connectors, AVI-LV5 generators are ready for an optimal PLC integration

Technical Specifications

OVERVIEW – SMART SYSTEM CONCEPT

The smart concept of AVI-LV5 allows to extend the system should this be required in the future.

PIN INJECTION


- › AVI-LV5-PIN
- › BD-PIN-FAST
- › BD-PIN-U
- › BD-PIN-G

CABLE BUNDLE

- › AVI-LV5-CB
- › EXT-AVI5-MS
- › OPT-MS-30
- › CN-BT8
- › CN-BT9
- › LISN-5U-32
- › EXT-LISN-DC-270

ACCESSORIES

- › MEAS-AVI
- › TEMA3000-AVI
- › ETHERNET OPT-LINK
- › WARNING LAMP
- › EMERGENCY-STOP



TEST GENERATORS AND EXTENSIONS

AVI-LV5-PIN GENERATOR

AVI-LV5-PIN circuit: WF3, 1 MHz, pin injection

Standards	DO-160G S22, ED-14G S22, other
Coupling mode	direct injection
Voltage, current WF3	frequency: 1 MHz $\pm$ 20 % damping: 25 – 75 % (1st to 5th peak)
Test level	specified at application point
Test level single stroke	20 V – 3200 V, – 0 % / + 10 %
Output impedance	25 Ω
Polarity	positive, negative, alternating
Synchronization	automatic on power peak or 0 – 359°, step 1°
Programmable ramp	Voltage
Power blocking device	built-in
EUT max. AC-voltage	230 V
EUT max. supply frequency	800 Hz
EUT max. DC-voltage	$\pm$ 540 V

AVI-LV5-PIN circuit: WF4, pin injection

Standards	DO-160G S22, ED-14G S22, other
Coupling mode	direct injection
Voltage, current WF4	6.4 μ s $\pm$ 20 % / 69 μ s $\pm$ 20 %
Test level	specified at application point
Test level single stroke	50 V – 1600 V, – 0 % / + 10 %
Output impedance	5 Ω
Polarity	positive, negative, alternating
Synchronization	automatic on power peak (90°, 270°)
Programmable ramp	voltage
Power blocking device	built-in
EUT max. AC-voltage	230 V
EUT max. supply frequency	800 Hz
EUT max. DC-voltage	$\pm$ 540 V

AVI-LV5-PIN circuit: WF5A, pin injection

Standards	DO-160G S22, ED-14G S22, other
Coupling mode	direct injection
Voltage, current WF5A	40 μ s $\pm$ 20 % / 120 μ s $\pm$ 20 %
Test level	specified at application point
Test level single stroke	25 V – 2000 V, – 0 % / + 10 %
Output impedance	1 Ω
Polarity	positive, negative, alternating
Synchronization	automatic on power peak (90°, 270°)
Programmable ramp	voltage
Power blocking device	built-in
EUT max. AC-voltage	230 V
EUT max. supply frequency	800 Hz
EUT max. DC-voltage	$\pm$ 540 V

AVI-LV5-PIN control features

Operating system	EPOS ORION proprietary firmware
Languages	8 menu languages, selectable
User interface	7" capacitive touch display
Connectivity	ethernet 1Gbps, USB, RS485
Synchronization on signals	40 – 800 Hz
Synchronization source	EUT power
Impulse polarity	positive, negative, electronic switching
Automatic ramp	programmable for test level
Trigger out	BNC, max. 6 V
Programmable connectors	6 BNC connectors (inputs/outputs) as follows
Programmable input functions	Trigger input, Start Test, Stop Test, EUT Fail, EUT Mark, Emergency Stop
Programmable input max. voltage	low range: 0 – 1.5 V, high range: 2.3 – 24 V
Programmable output functions	Running State, Safety Circuit State
Programmable output max. U, I	max. 24 V, max. 300 mA
Safety features (standard)	safety circuit, emergency stop button on front panel, red/yellow as per IEC 60947-5-5, IEC 60204-1, ISO 13850
Safety accessories (optional)	WARNING LAMP
	Remote EMERGENCY STOP button

AVI-LV5-PIN supply, weight, dimensions, climatic conditions

Operating voltage	100 V – 240 V (50/60 Hz) ± 10%
Power consumption	ON < 400 VA, standby < 15 VA
Weight	43 kg
W x d x h	45 x 60 x 37 cm
Construction type	19" unit, 8 UH
Temperature range	10 – 35 °C
Humidity	25 – 80 % non-condensing
Air pressure	86 – 106 kPa
Included articles	
Power cord	with country plug
User manual	with conformity declaration
Calibration certificate	factory calibration

AVI-LV5-PIN optional accessories

BD-PIN-FAST	Power supply transient blocking device for WF3 direct PIN tests (2 pieces for separate return lead)
BD-PIN-U	Power supply transient blocking device for WF4 and 5A direct PIN tests. EUT supply with dedicated return
BD-PIN-G	Power supply transient blocking device for WF4 or 5A direct PIN tests. EUT supply with ground return
MEAS-AVI (only 1 kit for PIN and CB)	System verification and basic EUT monitoring kit. Comprises loads, accessories, voltage and current probes. No DSO included. ISO/IEC 17025 calibration of probes and loads included.
TEMA3000-AVI	Control of AVI generators. Includes Library of test routines, Report function, DSO screen dump import and sequence mode. 1 piece per generator required.
ETHERNET-OPT-LINK	10 m optical fibre kit with Ethernet converters. 1 piece per generator required.

AVI-LV5-CB GENERATOR

AVI-LV5-CB circuit: WF1 cable induction

Standards	DO-160G S22, MIL-STD-461G CS117, ED-14G S22
Coupling mode	Cable Induction (CI)
Current waveform WF1	6.4 μ s $\pm$ 20 % / 69 μ s $\pm$ 20 %
Measured	at coupler output
SC current single stroke	100 A – 3200 A, – 0 % / + 20 %
SC current multiple stroke	50 A – 1600 A (first stroke), – 0 % / + 20 %
(requires EXT-AVI5-MS)	25 A – 800 A (subsequent stroke), –0% / +50%
Polarity	positive, negative, alternating
Programmable ramp	current
Requires	CN-BT8

AVI-LV5-CB circuit: WF2 cable induction

Standards	DO-160G S22, MIL-STD-461G CS117, ED-14G S22
Coupling mode	Cable Induction (CI)
Voltage waveform WF2	rise time: < 100 ns pulse duration: 6.4 μ s $\pm$ 20 %
Measured	at coupler output
OC voltage single stroke	50 V – 1600 V, – 0 % / + 20 %
OC voltage multiple stroke	50 V – 1600 V (first stroke), – 0 % / + 20 % 25 V – 800 V (subsequent stroke), –0% / +50%
Polarity	positive, negative, alternating
Programmable ramp	voltage
Requires	CN-BT8

AVI-LV5-CB circuit: WF3, 1 MHz, cable induction

Standards	DO-160G S22, MIL-STD-461G CS117, ED-14G S22
Coupling mode	Cable Induction (CI)
Voltage, current WF3	frequency: 1 MHz $\pm$ 20 % damping: 25 – 75 % (1st to 5th peak)
Measured	at coupler output
OC voltage single stroke	100 V – 3200 V, – 0 % / + 20 %
OC voltage multiple stroke	100 V – 3200 V (first stroke), – 0 % / + 20 % 50 V – 1600 V (subsequent stroke), –0% / +50%
OC voltage multiple burst	60 V – 1920 V, – 0 % / + 20 % (max. 500 pulses)
Polarity	positive, negative, alternating
Programmable ramp	voltage
Requires	CN-BT8

AVI-LV5-CB circuit: WF3, 10 MHz, cable induction

Standards	DO-160G S22, MIL-STD-461G CS117, ED-14G S22
Coupling mode	Cable Induction (CI)
Voltage, current WF3	frequency: 10 MHz $\pm$ 20 % damping: 25 – 75 % (1st to 5th peak)
Measured	at coupler output
OC voltage single stroke	100 V – 3200 V, – 0 % / + 20 %
OC voltage multiple stroke	100 V – 3200 V (first stroke), – 0 % / + 20 % 50 V – 1600 V (subsequent stroke), –0% / +50%
OC voltage multiple burst	60 V – 1920 V, – 0 % / + 20 % (max. 500 pulses)
Polarity	positive, negative, alternating
Programmable ramp	voltage
Requires	CN-BT8

AVI-LV5-CB circuit: WF4 ground injection

Standards	DO-160G S22
Coupling mode	Ground Injection (GI), EUT current max. 30 A
Voltage waveform WF4	6.4 μ s $\pm$ 20 % / 69 μ s $\pm$ 20 %
Measured	at application point
OC voltage single stroke	50 V – 1600 V, – 0 % / + 20 %
OC voltage multiple stroke	25 V – 800 V (first stroke), – 0 % / + 20 %
(requires EXT-AVI5-MS)	12.5 V – 400 V (subseq. stroke), –0% / +50%
Polarity	positive, negative, alternating
Programmable ramp	voltage
EUT max. current	30 A DC - 800Hz

AVI-LV5-CB circuit: WF4 cable induction

Standards	MIL-STD-461G CS117, DO-160G S22, ED-14G S22
Coupling mode	Cable Induction (CI)
Voltage waveform WF4	6.4 μ s $\pm$ 20 % / 69 μ s $\pm$ 20 %
Measured	at coupler output
OC voltage single stroke	50 V – 1600 V, – 0 % / + 20 %
OC voltage multiple stroke	25 V – 800 V (first stroke), – 0 % / + 20 %
(requires EXT-AVI5-MS)	12.5 V – 400 V (subseq. stroke), –0% / +50%
Polarity	positive, negative, alternating
Programmable ramp	voltage
Requires	CN-BT9

AVI-LV5-CB circuit: WF5A ground injection

Standards	DO-160G S22, ED-14G S22, other
Coupling mode	Ground Injection (GI), EUT current max. 30 A
Current waveform WF5A	40 μ s $\pm$ 20 % / 120 μ s $\pm$ 20 %
Measured	at application point
SC current single stroke	150 A – 5000 A, – 0 % / + 20 %
SC current multiple stroke	60 A – 2000 A (first stroke), – 0 % / + 20 %
(requires EXT-AVI5-MS)	30 A – 1000 A (subseq. stroke), –0% / +50%
Polarity	positive, negative, alternating
Programmable ramp	current
EUT max. current	30 A DC - 800Hz

AVI-LV5-CB circuit: WF5A cable induction

Standards	DO-160G S22, MIL-STD-461G CS117, ED-14G S22
Coupling mode	Cable Induction (CI)
Current waveform WF5A	40 μ s $\pm$ 20 % / 120 μ s $\pm$ 20 %
Measured	at coupler output
SC current single stroke	150 A – 5000 A, – 0 % / + 20 %
SC current multiple stroke	60 A – 2000 A (first stroke), – 0 % / + 20 %
(requires EXT-AVI5-MS)	30 A – 1000 A (subseq. stroke), –0% / +50%
Polarity	positive, negative, alternating
Programmable ramp	current
Requires	CN-BT9

AVI-LV5-CB circuit: WF5A voltage

Standards	DO-160G S22, Boeing D6, ED-14G S22
Application	core wire pulsing and similar
Coupling mode(s)	Cable Induction (CI), ground injection GI
Voltage waveform WF5A	40 μ s $\pm$ 20 % / 120 μ s $\pm$ 20 %
Measured	at coupler/generator output
OC voltage single stroke	150 V – 2000 V, – 0 % / + 20 %
OC voltage multiple stroke	150 V – 2000 V (first stroke), – 0 % / + 20 %
(requires EXT-AVI5-MS)	30 V – 400 V (subseq. stroke), –0% / +50%
Polarity	positive, negative, alternating
Programmable ramp	voltage
Requires	CN-BT9 for CI, direct coupling for GI

AVI-LV5-CB circuit: WF5B cable induction

Standards	DO-160G S22, ED-14G S22, other
Coupling mode	Cable Induction (CI)
Current waveform WF5B	50 μ s $\pm$ 20 % / 500 μ s $\pm$ 20 %
Measured	at coupler output
SC current single stroke	150 A – 5000 A, – 0 % / + 20 %
SC current multiple stroke	60 A – 2000 A (first stroke), – 0 % / + 20 %
(requires EXT-AVI5-MS)	30 A – 1000 A (subseq. stroke), –0% / +50%
Polarity	positive, negative, alternating
Programmable ramp	current
Requires	CN-BT9

AVI-LV5-CB circuit: WF6 cable induction

Standards	DO-160G S22, MIL-STD-461G CS117, ED-14G S22
Coupling mode	Cable Induction (CI)
Current waveform WF6	0.25 μ s $\pm$ 20 % / 4 μ s $\pm$ 20 %
Measured	at coupler output
SC current multiple burst	5 A – 160 A
Polarity	positive, negative, alternating
Programmable ramp	current
Requires	CN-BT8

AVI-LV5-CB control features

Operating system	EPOS ORION proprietary firmware
Languages	8 menu languages, selectable
User interface	7" capacitive touch display
Connectivity	ethernet 1Gbps, USB, RS485
Patterns	DO-160 S22, MIL CS117
Optional patterns	Airbus, Boeing patterns require OPT-MS-30
Impulse polarity	positive, negative, electronic switching
Automatic ramp	programmable for test level
Trigger out	BNC, max. 6 V
Programmable connectors	6 BNC connectors (inputs/outputs) as follows
Programmable in-put functions	Trigger input, Start Test, Stop Test, EUT Fail, EUT Mark, Emergency Stop
Programmable in-put max. voltage	low range: 0 – 1.5 V, high range: 2.3 – 24 V
Programmable out-put functions	Running State, Safety Circuit State
Programmable out-put max. U, I	max. 24 V, max. 300 mA
Safety features (standard)	safety circuit, emergency stop button on front panel, red/yellow as per IEC 60947-5-5, IEC 60204-1, ISO 13850
Safety accessories (optional)	WARNING LAMP
	Remote EMERGENCY STOP button

AVI-LV5-CB supply, weight, dimensions, climatic conditions

Operating voltage	100 V – 240 V (50/60 Hz) ± 10%
Power consumption	ON < 400 VA, standby < 15 VA
Weight	200 kg
W x d x h	60 x 72 x 127 cm
Construction type	19" rack, 18 UH with wheels
Temperature range	10 – 35 °C
Humidity	25 – 80 % non-condensing
Air pressure	86 – 106 kPa
Included articles	
Power cord	with country plug
User manual	with conformity declaration
Calibration certificate	factory calibration

AVI-LV5-CB optional accessories

LISN-5U-32 + DC option	3P 5 µH LISN max. 420V AC/50 V DC 32 A per phase or DC. Optional DC 270 V capability. For both DO-160 S22 and MIL-STD-461G CS117
MEAS-AVI (only 1 kit for PIN and CI is sufficient)	System verification and basic EUT monitoring kit. Comprises loads, accessories, voltage and current probes. No DSO included. ISO/IEC 17025 calibration of probes and loads included
TEMA3000-AVI	Control of AVI generators. Includes Library of test routines, Report function, DSO screen dump import and sequence mode. 1 piece per generator required.
ETHERNET-OPT-LINK	10 m optical fibre kit with Ethernet converters. 1 piece per generator required.

EXT-AVI5-MS

Application	extends AVI-LV5-CB for multiple stroke
Subsequent strokes	max. 15 strokes
Weight	200 kg
W x d x h	60 x 72 x 127 cm
Construction type	19" rack, 18 UH with wheels
Supply	100 – 240 V AC 50/60 Hz, max. 450 VA
Requires	AVI-LV5-CB

OPT-MS-30

Application	option for 30 subsequent strokes
Type	hardware upgrade (subsequent on site installation possible only via service dept.)
Requires	EXT-AVI5-MS

ACCESSORIES

BD-PIN-FAST

Standard	DO-160G S22, ED-14G S22
Application	power supply transient blocking device for PIN tests, direct injection method. 2 pieces required for separate return lead 1P
Test level WF3 1 MHz	100 V – 3200 V
EUT supply mode(s)	separate return lead, ground return
EUT supply AC	≤ 230 V L-PE / 32 A @ max. 800 Hz
EUT supply DC	≤ 540 V / 32 A DC
Weight	0.7 kg
Dimensions	10 x 8 x 11 cm
Requires	AVI-LV5-PIN

BD-PIN-U

Standard	DO-160G S22, ED-14G S22
Application	power supply transient blocking device for PIN tests, direct injection method
Test level WF 4	50 V – 1600 V
Test level WF 5A	25 V - 2000 V
EUT supply mode(s)	separate return lead
Lines	L1, L2, L3, N or DC+ and DC-
EUT supply AC	≤ 230 V L-PE / 32 A @ max. 800 Hz
EUT supply DC	≤ 540 V / 32 A DC (floating, symmetrical)
Weight	42 kg
W x d x h	45 x 57 x 19 cm
Construction type	19" unit, 4 UH
Requires	AVI-LV5-PIN

BD-PIN-G

Standard	DO-160G S22, ED-14G S22
Application	power supply transient blocking device for PIN tests
Test level WF 4	50 V – 1600 V
Test level WF 5A	25 V - 2000 V
EUT supply mode(s)	ground return
EUT supply AC	≤ 230 V L-PE, max.10 A @800 Hz, 32 A@60 Hz
Injection method AC	direct injection
EUT supply DC	≤ 540 V / 32 A DC
Injection method DC	ground injection
Weight	18 kg
W x d x h	45 x 57 x 19 cm
Construction type	19" unit, 4 UH
Requires	AVI-LV5-PIN

LISN-5U-32

Standard(s)	DO-160G S22, MIL-STD-461G CS117, ED-14G S22
Application	Line Impedance Stabilization Network (5 μ H)
Inductance	5 μ H per line (for both AC and DC lines)
Capacitance	10 μ F/line included, 2 x ($\geq$ 28 mF) included LISN is calibrated with capacitors connected
Number of lines	4 AC lines (L1 L2, L3, N), 2 DC lines (+ / -)
AC voltage max.	L-L: 420 V @50/60 Hz, L-PE: 240 V @50/60 Hz L-L: 420 V @ 800 Hz, L-PE: 240 V @ 800 Hz
AC current max.	32 A
DC voltage max.	50 V
DC current max.	32 A
Weight	16 kg
W x d x h	45 x 60 x 19 cm
Construction type	19" unit, 4 UH
For generator(s)	AVI-LV5-CB, other (AVI-LV3)

EXT-LISN-DC-270

Standard(s)	DO-160G S22, MIL-STD-461G CS117, ED-14G S22
Application	extends LISN-5U-32 capability up to 270 V DC
Capacitance	2 lines, $\geq$ 28 mF each
Weight	23 kg
W x d x h	45 x 60 x 19 cm
Construction type	19" unit, 4 UH
Special characteristics	built-in safety features

MEAS-AVI

Standards	measurements acc. to DO160G S22, ED-14G S22, MIL CS117 and similar
Application	set of voltage, current probes, load(s) and accessories for indirect lightning generator performance verification and basic EUT monitoring
Voltage probe	bandwidth to cover all DO160 S22 waveforms at all standard test levels
Current probe/cal. load	bandwidth to cover all DO160 S22 waveforms at all standard test levels
Other accessories	according to configuration
For generators	either AVI-LV5-PIN or AVI-LV5-CB
Not included	oscilloscope, more current probes for simultaneous monitoring of several bundles

WARNING-LAMP

Application	red/green signalization lamp
Protection class	IP65, IEC 61140, VDE 0140-1
Mounting support	magnetic support, crewable bracket included
Lamp type	red and green (2 lamps), LED technology
Weight	0.3 kg
Dimensions	30x25x6cm
Included	control cable to TC-ST/generator
For generators	All EMC PARTNER AG generators



EMERGENCY-STOP

Application	remote emergency stop button
Colours	standard red/yellow as in IEC 60947-5-5
Mounting	on table, magnetic support als included
Weight	0.5 kg
Dimensions	78 x 72 x 64 mm
Included	5m cable
For generators	All EMC PARTNER AG generators



INJECTION TRANSFORMERS

CN-BT8

Standards	DO-160G/ ED-14G S22, MIL-STD-461G CS117
Application AVI-LV5-CB	WF 1, 2, 3, 6 all test levels
Application AVI-LV3	WF 1, 2, 3, 5A, 6 up to level 3 (DO-160G S22)
SC current	≥ 3200 A
SC current	≥ 160 A multiple burst
OC voltage	≥ 1600 V
OC voltage WF 3	≥ 3200 V, 1 and 10 MHz
EUT supply CB	<i>only one line: high side or return in coupler</i>
All WFs AVI-LV5-CB	≤ 426 A @ 60 Hz, ≤ 32 A @ 800 Hz <i>high side(s) and return(s) together in coupler</i>
All WFs AVI-LV5-CB	≤ 852 A @ 60 Hz, ≤ 64 A @ 800 Hz
Higher EUT current	contact sales@emc-partner.ch for details
EUT max. supply voltage	own isolation for cable / bundle is required: 1500V DC, 1000V AC 50-60 Hz, 230V @800Hz
Aperture	5.5 x 8 cm
Dimensions	18 x 37.5 x 20 cm
Weight	22 kg
For generators	AVI-LV5-CB, AVI-LV3

CN-BT9

Standards	DO-160G/ ED-14G S22, MIL-STD-461G CS117
Application AVI-LV5-CB	WF 4, 5A current, 5A voltage, 5B all test levels
SC current	≥ 5000 A WF 5A/5B current
OC voltage	≥ 1600 V WF 4 voltage, WF 5A voltage
EUT supply CB	<i>only one line: high side or return in coupler</i>
WF 4, 5A current, 5B	≤ 426 A @ DC - 60 Hz, ≤ 32 A @ 800 Hz
WF 5A voltage	≤ 213 A @ DC - 60 Hz, ≤ 16 A @ 800 Hz <i>high side(s) and return(s) together in coupler</i>
WF 4, 5A current, 5B	≤ 852 A @ DC - 60 Hz, ≤ 64 A @ 800 Hz
WF 5A voltage	≤ 426 A @ DC - 60 Hz, ≤ 32 A @ 800 Hz
Higher EUT current	contact sales@emc-partner.ch for details
EUT max. supply voltage	own isolation for cable / bundle is required: 1500V DC, 1000V AC 50-60 Hz, 230V @800Hz
Aperture	6 x 13 cm
Dimensions	61 x 63 x 35 cm (coupler), 65 x 130 x 114 cm (with cart)
Weight	260 kg (coupler), 369 kgs (with cart)
For generators	AVI-LV5-CB

REMOTE CONTROL

TEMA3000-AVI

Application	software control for AVI-LV5 generators
Includes	
TEMA3000 BASIC	remote control, single tests
TEMA3000-SEQUENCE	linking multiple single tests
TEMA3000-REPORT	generates reports for single tests/sequences
TEMA3000-LIBRARY	pre-programmed DO-160 S22, CS117 routines
TEMA3000-DSO	DSO control for AVI-LV3, AVI-LV5 generators
License plan	one license required for each generator

ETHERNET-OPT-LINK

Application	galvanic isolation between computer AVI-LV5 generators
Type	optical fibre kit with Ethernet converters
Length	10 meters
For generators	AVI-LV5-PIN , AVI-LV5-CB (one piece per generator)

Tradition meets Technology

Over 25 years devoted to combining
latest technologies into the best products.



100% Swiss made products



Specific EMC test requirements ?

Search & find your required test equipment by application, standard or test type

www.emc-partner.com



EMC PARTNER

PRODUCT APPLICATION RANGE

CONSUMER & INDUSTRIAL ELECTRONICS

Transient Test Systems for conducted EMC tests on electronic equipment. ESD, EFT, surge, ring wave, DOW, dips, magnetic field, common and differential mode. Compliant to IEC, EN and ANSI standards.



AEROSPACE ELECTRONICS

Impulse generators and couplers for avionic applications. Single stroke, multiple stroke and multiple burst according to RTCA / DO-160, EUROCAE / ED-14 and aircraft manufacturer standards.



Component Testing

Voltage and current Impulse generators for design and production testing of varistors, gas discharge tubes, surge protective devices, X / Y capacitors and specialist impulse generators for semiconductor tests.



DEFENCE ELECTRONICS

Complete test solutions for MIL-STD-461 requirements CS06, CS106, CS115, CS116, CS117 and CS118.



TELECOM & data line testing

Voltage and current impulse generators, CDNs, power contact, power induction equipment for exchange and customer equipment according to ITU, IEC, EN and ETSI requirements.



ENERGY & UTILITY EQUIPMENT

High current CDNs combined with transient test equipment fulfil requirements to test renewable and classical energy distribution network and monitoring equipment.



CUSTOMER ServiceS

Customer support throughout an equipment's lifetime is central to the EMC PARTNER AG philosophy. Directly from our ISO accredited facility in Switzerland or through our network of services centres, we provide support wherever you



For further information please do not hesitate to contact your local EMC PARTNER AG representative.
Visit our website for more information and contact details.

www.emc-partner.com



Swiss headquarters

EMC PARTNER AG
Baselstrasse 160
CH - 4242 Laufen

Phone +41 61 775 20 30
Fax +41 61 775 20 59
Email sales@emc-partner.ch
Web www.emc-partner.com

Your local representative

Information and specifications in this document are an indication of capability only. V.3.7 Subject to change without notice. EMC PARTNER AG publishes only the English version of this document. Translation into other languages is not guaranteed to be a true representation of content or specification.

© by EMC PARTNER AG. No changes or reproduction without permission of EMC PARTNER AG allowed.