



Technical Specifications

Product Code & Model Name:

- Baltic 1600 - Heat assist laminator

Max. Working Temperature:

- Up to 120°C

Laminating Speed:

- Variable speed (up to 6m per min)

Maximum Laminating Width:

- 1600mm

Maximum Mounting Thickness:

- Opens up to 35mm

Assembled Dimensions (mm):

- 2000 (L) x 630 (W) x 1235 (H)

Baltic Heat Assist Laminator 1600

The Baltic is our premium laminator, engineered with heavy-duty components to meet the demands of high-volume operations. It is equipped with five mandrels and features an extra-wide roller opening, ideal for mounting applications. Additionally, the machine includes an LED nip pressure gauge to ensure precise and consistent pressure control.

Key Features:

- 5 interchangeable mandrels, including a build-in rewind unit
- Single opening mechanism
- Two emergency stop buttons for enhanced safety
- Adjustable heat, speed, nip pressure & tension
- Heavy-duty castors with brakes for stability
- Roller Diameter 120mm
- Cold laminator with heat assist
- Maximum temperature of 120°C
- Rollers open to 35mm
- Simple plug-and-play setup - no wiring required
- 15 amp, 3-pin earthed power plug
- Nip pressure visible on LED panel
- Infrared nip safety sensor
- Safety covered foot pedal
- Forward & reverse functions
- RCM Certified

The Baltic combines automation, safety, and precision –perfect for high-efficiency wide-format workflows.

5 years structural warranty and 3 years parts*