WilencoDENMARK

HEAT ASSIST LAMINATOR 1650





Technical Specifications

Product Code & Model Name:

• CLMD - Denmark Heat Assist Laminator

Top Roll Heat Assist:

Up to 50°C

Laminating Speed:

· Variable speed (up to 7m per min)

Maximum Laminating Width:

· 1650mm

Maximum Mounting Thickness:

Opens up to 10mm

Feed Tray Height (Including Stand):

• 916mm

Assembled Dimensions (mm):

• 1860 (L) x 570 (W) x 1300 (H)



Optional Extras

- Rewind Unit
- Printed Media
 Mandrel Kit

Denmark Heat Assist Laminator 1650

The Denmark Laminator is the ideal solution for medium to large-scale operations, offering exceptional reliability, ease of use, and consistent performance. Engineered for efficiency, it guarantees up to 50 meters of flawless lamination without creasing*. Its user-friendly design features cambered silicone rollers that enhance pressure application and significantly reduce silvering.

Key Features:

- Lamination width: 1650mm
- · Integrated heat-assist functionality
- · Lower mandrel with dual-ended brake
- Dual 84mm diameter cambered silicone rollers
- Two emergency stop buttons for enhanced safety
- · Supplied with a mobile stand for easy mobility
- · Foot pedal for hands-free operation
- 76mm mandrels
- Forward and reverse operation modes
- Roller guard with integrated safety sensor switch
- Opens up to 10mm with a convenient single-lever mechanism
- RCM Certified

Perfectly suited for businesses requiring consistent, high-quality lamination with minimal downtime.

5 year parts & structure warranty**