

CVi42[®]

v.6.3

Client Server Installation and Configuration Guide

cvi42

CLIENT SERVER INSTALLATION AND CONFIGURATION GUIDE

May 2025



Manufactured by
Circle Cardiovascular Imaging Inc.
Suite 1800, 707 – 8th Ave SW
Calgary, Alberta
Canada T2P 1H5

Telephone: 1 (403) 338-1870

Support: support@circlecvi.com

<http://www.circlecvi.com>



© Copyright 2024 Circle Cardiovascular Imaging Inc.

cvi42 is a registered trademark of Circle International Corporation in Canada and/or other countries.

The information contained herein is subject to change without notice. The only warranties for Circle products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be constructed as constituting an additional warranty. Circle shall not be liable for technical or editorial errors or omissions contained herein.

1.	<i>Installing and configuring cvi42 Server</i>	6
1.1.	Server Installation	7
1.1.1.	Services Installed	17
1.2.	Optimizing System Performance	18
1.3.	Activating cvi42 Licensing	18
1.3.1.	Activating Your Installation	18
1.4.	Server Configuration	22
1.5.	Enabling TLS in cvi42	22
1.6.	User Management	23
1.6.1.	Local user management	23
1.6.2.	AD/LDAP user management	25
1.6.3.	Role management	26
1.5.4.	User Account Linking	29
1.5.5.	Assigning ADAS 3D User Role	29
1.6.6.	Assigning the TruPlan User Role	30
1.7.	Configure Antivirus Software	30
1.8.	Configure DICOM Networking (PACS Connections)	31
1.9.	Server Configuration (cvi42serverconfig.ini explained)	33
1.10.	General Properties	33
1.11.	PPU Properties	36
1.12.	DICOM Network	36
1.13.	AD/LDAP Integrated Password Authentication	37
1.14.	Server-side processing configuration (Node42)	38
1.15.	Gateway Configuration (cvi42_gateway.ini)	39
1.16.	Webclient Service Configuration (cvi42_webclient_service.ini)	40
1.17.	Webclient Manager Configuration (cvi42_worker_manager.ini)	40
2	<i>cvi42 Configuration Portal</i>	41
3	<i>Housekeeping</i>	45
3.7.	Overview	46
3.7.4.1	Rule matching	46
3.7.5	Rule execution	46
3.8.	Rules	46
3.8.4	Criteria	47
3.8.5	Actions	49
3.8.6	Recurrence	50

3.9	Rule Editor	51
3.9.4	Simulation	52
3.10	Settings	54
4	<i>cvi42 Default Roles</i>	56
5	<i>cvi42 Network Communications Matrix</i>	57
6	<i>cvi42 and TruPlan client installation</i>	58
6.7	Silent installation of cvi42 client.....	58
6.8	Client Installation (including TruPlan).....	59
6.9	Configure cvi42 client to connect to the Server	64
7	<i>cvi42 Web Module</i>	67
7.7	Overview.....	67
7.8	Setting up TLS support	68
8	<i>Command-line Integration</i>	68
8.7	Overview.....	68
8.8	Client and Server Integration Workflow	69
8.9	Command Line Parameters	70
8.10	Launching cvi42	70



IMPORTANT: **cvi42** is software designed to be deployed and run within a secure environment. The security of the software and the environment in which it is run is the responsibility of the customer. Please ensure that the server and clients where **cvi42** is deployed are up to date with security patches, behind a secure firewall, and contain up to date antivirus software. The responsibility for data encryption at rest on installing and configuring a full disk encryption system such as Microsoft BitLocker.

1. Installing and configuring cvi42 Server

This guide is designed for a fresh installation and activation of **cvi42** Server.



IMPORTANT: For all updates from 5.14 or earlier, customers will need to schedule a guided update with Circle's Customer Support Team at support@circlecvi.com



PRE-REQUISITE: When installing **cvi42** on Windows N, you should have **Media Feature Pack** installed on your Windows before installing **cvi42**.

There are two methods to install **Media Feature Pack**:

1. From Windows Settings:
<https://support.microsoft.com/en-us/windows/media-feature-pack-for-windows-n-8622b390-4ce6-43c9-9b42-549e5328e407>
2. Downloading and installing it manually:
<https://www.microsoft.com/en-us/software-download/mediafeaturepack>

After installation, you should restart your PC to install **cvi42**.

1.1. Server Installation




IMPORTANT: By accessing this link https://www.circlecvi.com/docs/product-support/cvi42_System_Requirements_6.1.pdf, you can find the Minimum System Requirements for a **cvi42** Server Installation with up to 4 concurrent users. For advice on larger deployments please contact Circle's Technical Support Team at support@circlecvi.com.




IMPORTANT: Before starting installation of **cvi42** Server, please make sure you exclude ports used by the **cvi42** Server from Microsoft Windows dynamic range by running the command as administrator:

```
netsh int ipv4 add excludedportrange startport=49696 numberofports=2  
protocol=tcp store=persistent
```

For the **cvi42** Server Installation, you may select **cvi42 Server** option during installation, where you can select from a list of components to install:





Save installer package for IT-scheduled client upgrades, when checked, the installer will copy the installation package (.msi) to a specific sub-folder on the **cvi42 Server Data** folder (UpgradeAgentService\installer), so the IT Administrator can trigger client upgrades.

cvi42 WebClient Server is to support the **cvi42 Web Viewer**. When selected, this component is installed on the same machine as **cvi42 Server**. In the current architecture, there is only one instance of **cvi42 WebClient Server** to one or more instances of **cvi42 WebClient Worker** (explained below).


cvi42 WebClient Worker works in conjunction with **cvi42 WebClient Server** to support **cvi42 Web Viewer**. When selected, during the installation of **cvi42 Server**, this component is installed on the same machine as **cvi42 Server**.



IMPORTANT: *IT-scheduled client upgrades* feature allows IT Administrators to update clients remotely. If you have already an automated method for updating clients, this feature is not recommended for you. Please contact Circle's Customer Support Team at support@circlevi.com to obtain more information about ***IT-scheduled client upgrades***.

When **cvi42** is installed, the Server-side processing component (Node42), is installed together, on the same machine.

click **Next**.



cvi42 Setup

Select Installation Folders

These are the folders where cvi42 will place its files.

To use the default directories for installation, click "Next" to proceed. To select different directories, enter them below or click "Browse".

The data that supports the cvi42 Server and Report features can go quite large. It may be preferable to install these data sets in alternate drives.


cvi42 Program Files:

cvi42 Data Files:

cvi42 Report Data Files:

Select the installation and data folders and then click **Next**.

When **cvi42 WebClient Server** or **cvi42 WebClient Worker** is selected, this dialogue will be presented:




The image shows a Windows-style dialog box titled "cvi42 Setup". Inside, the section "Server Connection Settings" is active, with the instruction "Configure the cvi42 WebClient Server's connection info". The cvi42 logo is in the top right. There are three input fields: "cvi42 Server FQDN:" with the value "cvi42.server", "cvi42 WebClient Worker ID:" with the value "cvi42-webclient-worker-1", and "cvi42 WebClient Worker Capacity:" with the value "5". At the bottom are three buttons: "< Back", "Next >" (highlighted with a blue border), and "Cancel".

cvi42 Server FQDN should be the IP/FQDN of the machine where **cvi42 Server** is being installed.

cvi42 WebClient Worker ID can be any alphanumeric identification for the **cvi42 WebClient Worker** instance. This ID is used by the **cvi42 WebClient Server** when communicating to the **cvi42 WebClient Worker**.

cvi42 WebClient Worker Capacity is an internal setting for future functionality, it should be left as the default for now.



cvi42 Setup

Server Connection Settings

Configure the cvi42 Enterprise Server's connection info

cvi42

Reporting Server Port:	4280
cvi42 Server Client Port:	49696
cvi42 Server Admin Port:	49697
cvi42 Configurator Port:	4299
cvi42 Server Side Processing Port:	4298
cvi42 WebClient HTTP Port:	4293
cvi42 WebClient Service Listener Port:	4289
cvi42 WebClient Worker Manager Port:	4292


< Back **Next >** Cancel




IMPORTANT: If you intend to change any of **cvi42** Server ports, please be aware that this needs to be aligned in the **cvi42** client deployment.

Ensure that all ports are available on the computer, otherwise services will fail to start.

To check if a port is being used on Windows the *Resource Monitor* can be used:



The ports can be found on Network tab, by looking at the Local Port column under TCP connections.



cvi42 Setup

cvi42 Server Credentials

Create a password for the cvi42 Server

Username

Password


Confirm

Password must be at least 6 characters

Advanced Installer

< Back Next > Cancel

The admin password must be set during the installation, enter it and click **Next**.




When **cvi42 | Report** is selected for installation, installer will prompt for additional configuration.

Basic (SQLite database) requires no additional configuration.

Advanced, requires to setup a a Microsoft SQL database connection.

The SQL scripts that will be required to install the Microsoft SQL database will be created during installation and will be stored in the **cvi42** Program Files folder that you defined in the **Select Installation Folder** part of this setup, e.g. **D:\Program Files\cvi42\report\scripts**



The image shows a screenshot of the 'cvi42 Setup' window. The window has a title bar with a close button (X) in the top right corner. Below the title bar, the text 'Reporting' is displayed in bold, followed by 'Configure Reporting' in a smaller font. To the right of this text is a large green 'cvi42' logo. The main area of the window contains two configuration options: 'Default Paper Size' with a dropdown menu set to 'letter', and 'Timezone' with a list box containing several options. The 'Timezone' list box has a scrollbar on the right, and 'America/Edmonton' is selected and highlighted in blue. At the bottom of the window, there are three buttons: '< Back', 'Next >', and 'Cancel'. The 'Next >' button is highlighted with a blue dashed border.

cvi42 Setup

Reporting
Configure Reporting

Default Paper Size: letter


Timezone:

- America/Creston
- America/Cuiaba
- America/Curacao
- America/Danmarkshavn
- America/Dawson
- America/Dawson_Creek
- America/Denver
- America/Detroit
- America/Dominica
- America/Edmonton

< Back Next > Cancel

Select the **Default Paper Size** and **Timezone** for the **cvi42 | Report**, and click **Next**.

If **Advanced (Requires Microsoft SQL Server)** is selected, the installer will prompt for **Microsoft SQL Server** connection configuration:



cvi42 Setup

Database Connection

Configure the Reporting database connection

Database Server Hostname: CVI42-SERVER\SQLEXPRESS

Database Name: REPORT42DB

Database Server Login: Report42WebClient


Database Server Password:

< Back Next > Cancel

click **Next**.



IMPORTANT: While **cvi42** works with Microsoft SQLEXPRESS, Circle recommends to use a fully licensed and supported Microsoft SQL Server.



Click **Install** to complete the installation.

1.1.1. Services Installed

When all server components are installed, the following services will be running:

Service Display Name	Role
cvi42 Gateway	Server configuration web interface
cvi42 License Server	License management
cvi42 Report Go Server	Report service layer
cvi42 Report Server	Report UI (Apache Web Server)
cvi42 Server	Service layer
cvi42 Webclient Manager	Web Module service layer
cvi42 Webclient Service	Web Module User Interface

1.2. Optimizing System Performance



IMPORTANT: In order to protect patient information, any drive directory which receives DICOM data should not be indexed.

Open the Start menu and type "Indexing", select indexing Options.


Select the "Modify" option and untick any drive directory which receives DICOM data.

1.3. Activating cvi42 Licensing

The typical way to activate **cvi42** is by obtaining an Activation Key from Circle CVI Support Team.

1.3.1. Activating Your Installation

Launch **cvi42** client on the server machine:



- The default **User ID** is "admin", and the password has been setup during installation.
- Enter the User ID/Password information and click **Login**. **cvi42** will proceed to check for a valid license and display the license request dialogue.

?
×

cv42 - License

License Status

No server activation license available.
Please add or request a new license.

Available Licenses

Product	Start date	Expiry date	Maintenance Expiry	License holder	Status	Count	Machine ID	License file

Import...
Update

Activate License Key


Click here and enter your activation key
Activate

Request Offline License

Click here to enter your customer details and request activation of your license from Circle CVI if this computer is not able to connect to the internet.
Request...

OK
Cancel


- Enter the Activation Key in the field **Activate License Key** and click **Activate**. If you are connected to the internet, you will see the list of Available Licenses filled in with all the licenses associated with your Activation Key:



If activation is successful, you should get a confirmation message.

By clicking **OK**, the application will open.

For any error during the activation, an error message will be presented in red color. The error message should be reported to Circle CVI Support Team, who can assist you with the problem:






IMPORTANT: If you are logged into Windows with a non-Administrator account, try to start the **cvi42** client as an administrator, by right-click on **cvi42.exe** and choose *Run As Administrator*. When you have successfully imported the license, exit the **cvi42** client, and restart **cvi42.exe** by double-clicking, as usual.



IMPORTANT: For Pay-Per-Use (PPU) licensing a reliable connection to Circle's PPU servers is required. The connection to Circle's PPU servers will be encrypted, all data will be hashed and salted, and no PHI will be transferred.

1.3.1.1. Offline Activation Method

When access to the internet is restricted, offline license can be requested to Circle CVI Support Team by sending a license request file. After installing **cvi42**, request file can be generated by log into **cvi42** and clicking Request in the License dialogue:



Add license details, Activation Key field is not mandatory.

Check **ADAS3D License Request** if you need a license for ADAS3D as well.

Click **Export...** button to export the request file to disk. Close the dialog box afterwards.

Click **Import...** when receiving the license file from Circle Support Team to activate **cvi42**.

1.4. Server Configuration

To access **cv42** Server Configuration options, you must login as an admin on the admin port (49697) and access Preferences -> Config from the menu bar (or press F12).

1.5. Enabling TLS in cv42



IMPORTANT: **cv42** accepts PEM (.pem, .crt, and .key) and PKCS #12 (.p12 and .pfx) formatted certificates and private keys.



IMPORTANT: It's recommended that you do not use a self-signed certificate, unless you have your own certificate authority implemented in your environment.

Importing Key Pair

Before using an encrypted connection for the first time in **cv42**, you must install a valid certificate/private key pair to the server. This can either be achieved by:

- *Importing Key Pair using **cv42** client user interface connecting to **cv42** Server on the admin port*
- Or manually placing the required files in the %PROGRAMDATA%\cv42 folder of the **cv42** Server


The file will need to be partitioned into separate certificate and private key files.

1. Log into a **cv42** client with **cv42** administrator credentials through the administrative port and open the preferences menu
2. Select **Server Admin**
3. Import both certificate and private key files using the client UI, as shown below



IMPORTANT: If you are using a self-signed certificate, please ensure it has been imported into the client machines trust store before completing this step as **cv42** will prevent you from importing certificates it does not trust.

4. Next, select **Export Keypair to Server**. If this operation is successful, you will see a dialogue box confirming the files have been saved to the server.





IMPORTANT: When a new Keypair is exported to the server, **cvi42** Server **must** be restarted in order to load the imported keypair. Clicking in Export Keypair to Server, does not restart the **cvi42** Server.




IMPORTANT: If **cvi42** Server has been setup for secure connection, please make sure the **cvi42** client is configured for secure connections.

Configuring an Encrypted Connection

Once TLS has been enabled on the **cvi42** Server, a secure server connection can be configured. Follow the steps outlined in section 6.9, to either add a new connection or modify an existing one.

1. Select "Connect as TLS". This will disable the Server Port field and enable the TLS Server Port field.
2. Specify the TLS Server Port. NOTE the default TLS Server Port is 4391.
3. Once saved, if successful the following dialogue box will be displayed.




1.6. User Management

There are basically two user management options in **cvi42**:


- Local user management
- AD/LDAP user management

1.6.1. Local user management

From the **cvi42** Server Configuration options, select `Server Admin` option.



- Click the "Add..." button, to add a new account. The *New user* dialogue will be displayed.




- Fill in all the user details and check the roles to be assigned to the new user.
- Click *OK* to finish.

1.6.2. AD/LDAP user management


From the **cvi42** Server Configuration options, select **LDAP Admin** option for setting up the configuration for Active Directory (AD) or LDAP integrated password authentication. This feature allows users to log into **cvi42** with their existing user credentials assigned by their organization's IT team.

To connect to an AD or LDAP server, **cvi42** needs the following information.

- **Enable LDAP**– When checked this checkbox enables the configured LDAP for user authentication and authorization.
- **Primary Server, Secondary Server** – IP address or fully qualified domain name for the AD or LDAP server.
- **Use TLS/SSL to connect**– When checked, the LDAP connection will be made over TLS (LDAPS). Contact the site IT or AD/LDAP server administrator for certificate files and configuration steps).
- **Username** – The username of the LDAP Bind account used by the **cvi42** Server to communicate with the integrated AD or LDAP server.
 - Active Directory: When configuring the username value for AD, it will be a userPrincipalName(CVI42-BIND-ACCOUNT-NAME@DOMAIN-NAME) or sAMAccountName (DOMAIN-NAME\CVI42-BIND-ACCOUNT-NAME).
 - LDAP: When configuring the username value for LDAP integrations, the format of the username will be an LDAP distinguished name: (uid=<CVI42-BIND-ACCOUNT>,ou=<specify each OU layer>,dc=<specify each DC layer>,dc=com)
- **Password** – The password of the AD/LDAP Bind account.
- **Anonymous connection** – When set, this will enable anonymous LDAP access.
- **Use Bind Account for Study Request URL Authentication**– (This is only applicable if the “shareURL” API is configured) When checked, study requests from URLs will be authenticated using the LDAP Bind Account. The LDAP Bind Account will be remembered and used to bind to an integrated AD/LDAP server for querying user accounts for each Study Request URL.
- **Check Name**– Use this button to verify that the configured AD/LDAP Bind Account authenticates.
- **Base DN** – Distinguished name of the location to search for AD or LDAP users.
- **Fetch DNs** – Use this button to fetch the DNs from the Base DN.
- **Username Attribute** – Specifies the AD/LDAP attribute used to indicate unique users.
 - Active Directory: When configuring the username attribute value for AD integrations, use a unique parameter, such as sAMAccountName.
 - LDAP: When configuring the username value for LDAP integrations, use the uid parameter.
- **Advanced** – This is an optional setting. It allows you to specify additional LDAP query syntax. For example, users may be required to be a member of a specific group to access **cvi42**, as an example:
 - memberOf=CN=cvi42, CN=Users, DC=example, DC=com
- **Use AD/LDAP groups for cvi42 role mapping** – This setting determines whether **cvi42** should use the integrated AD/LDAP server for user authentication and authorization (role mapping) or just for authentication. If this option is disabled, users logging in need to be listed in the **cvi42** user list and user permissions are determined using **cvi42**.



Configuration for AD




Configuration for LDAP

Once you are satisfied with the configuration click *Apply* to save the changes.

1.6.3. Role management


From the **cvi42** Server Configuration options, select **Server Admin -> Roles/Permission** button.

- 1 For more information on how user accounts are linked between the local **cvi42** authorization/authentication methods and an integrated AD/LDAP server refer to section 1 User Account Linking.



cvi42 defines a set of default roles that can be assigned to user accounts. The set of roles can be customized to meet your institution's needs.

By double-clicking the cell, Roles Name and Mapping String can be edited. Mapping String is pre-populated when **cvi42** is installed.



As an example, in case user is an Analyst: **cvi42_analyst** group should be assigned to the user on the AD, so when he logs in, the group the user belongs to on the AD translates to the **Analyst** role on **cvi42**. User can have multiple groups assigned to him on the AD translating to roles on **cvi42**.

If Mapping String is changed on **cvi42** configuration, then AD group name should be changed accordingly to correspond to **cvi42**.

Mapping String is only used when you have AD/LDAP integration enabled server and option **Use AD/LDAP groups for cvi42 role mapping** checked (check section 1.6.2).

- To edit the permissions of an existing role, select a role from the Roles list. The Assigned box in the bottom right half of the dialogue will display the permissions assigned the selected role:
 - Select permissions from either the **Available** list or **Assigned** list.
 - Click on the > or < buttons to assign or un-assign the selected permissions. The >> will assign all permissions to the role, and the << will un-assign all permissions from the role.
 - Click **Apply** to save the changes.
- To add a new role, click the **Add** button and enter a name for the new role. Proceed to assign the desired permissions to the new role.
- To delete a role, select a role and click the **Delete** button. A confirmation dialogue will be displayed. Click **Yes** to delete the role, or **No** to go back.



IMPORTANT: When roles/permissions of a particular user are changed, the settings will not take effect until the next time the user logs into **cvi42**.

2.5.4 User Account Linking

Below is a table outlining the User Account linking behaviour. For more information on configuring user accounts and user roles refer to section 1.6.


User in AD/LD AP	User in cvi42	User Account Linked	Password Used	Comments
Y	Y	Y	AD/LDAP	User is in both the cvi42 user list and in the integrated AD/LDAP server; uses the AD/LDAP password and is provided access.
Y	N	Y	AD/LDAP	User is in <i>only</i> in the integrated AD/LDAP server and uses the AD/LDAP password to log into cvi42 . The user will be provided access and a New User is created in the cvi42 user list and the user account is linked to the AD/LDAP user account.
Y	Y	N	AD/LDAP	User will then be converted to an AD/LDAP account
Y	Y	N	Local	This will not convert user to AD/LDAP user
N	Y	N	Local	
Y	Y	Y	Local	Needs to authenticate with AD/LDAP password
Y	N	N	Wrong	Needs to authenticate with correct AD/LDAP password
N	N	N	Any	

2.5.5 Assigning ADAS 3D User Role




IMPORTANT: ADAS 3D is *only* available for Windows platform.

If purchased, the ADAS 3D application will be installed when installing **cvi42**. To enable user access to the ADAS 3D application, add the specific `ADAS3D User` role to each applicable user account as depicted in the following screenshot:



1.6.6. Assigning the TruPlan User Role

The TruPlan User role is a convient group of permissions required to access TruPlan if a TruPlan license is present. It is not required to access TruPlan but includes all the relevant permissions.



1.7 Configure Antivirus Software

Antivirus scanning can have a significant, detrimental effect on the performance of the **cvi42** application. Typical studies can contain thousands of individual image files and the time needed to scan each of those files can be significant. Folder exclusion or process/filetype profiling should be configured to exclude these files from any antivirus on both the **cvi42** Server and client.

The paths configured in `C:\ProgramData\cvi42\cvi42serverconfig.ini` should be considered for exclusion from the designated Antivirus Software Solution in favor of system performance.

However, the recommendation is to not exclude the `\cvi42imagedb\incoming_DcmStorage\` folder as incoming DICOM traffic may not be trusted.

1.8 Configure DICOM Networking (PACS Connections)

Users with 'PACS Administrator' permissions can set up the configuration for DICOM Networking/PACS connections. The admin port (default is 49697) must be used to access the Network section of the Preferences Menu.

A remote DICOM node will need to be aware of the **cvi42** Server's DICOM AE Title, the Storage SCP Port as well as the IP address of the **cvi42** Server.

The following list presents only the most important settings of this section:

Network Settings

- **AE Title** – The Application Entity Title, is used by **cvi42** to identify itself and needs to be configured on both **cvi42** and the integrated repository. By default, the AE Title is **cvi42**. This field is case sensitive.
- **Storage SCP Port** – The network port of the **cvi42** product; this value must be defined in both **cvi42** and the integrated repository.
- **Storage SCP TLS Port** – The network port of the **cvi42** product that supports Transport Layer Security (TLS) encryption; this value must be defined in both **cvi42** and the integrated repository.
- **Database update interval** – This is the interval (measured in seconds) before **cvi42** will check for updates of incoming images. By default, **cvi42** will check for updates to the image database every 10 seconds.
- **Storage Commitment Retries** – The number of attempts to send a Storage Commitment request.
- **Storage Commitment Retry Delay (sec)** - The amount of time (in seconds) to wait between each Storage Commitment request attempts.
- **Optional fields - Default MPPS Server, Default Modality Worklist Server and Default Q/R Server**

These are optional fields that can be set depending on your needs. *Default MPPS (Modality Performed Procedure Step) Server:* When a study is opened, **cvi42** reaches out to this server to obtain the Scheduled Procedure Step attributes for the study.

MWL (Modality Worklist) Server: **cvi42** sends a message to the *Default MPPS Server* with the appropriate *Performed Procedure Step* attributes.

Default Q/R Server: When **cvi42** is opened from a third-party application, the study identifier is passed to **cvi42**. If the study is not on **cvi42** Server, it reaches out to the *Default Q/R Server* to query, retrieve and import the study

Network Options

- **Enable Storage SCP** – Configuration option that enables **cvi42** to act as a Storage SCP. **cvi42** will listen for incoming DICOM C-STORE connections on the configured **Storage SCP Port** and **AE Title**.
- **Enable Q/R SCP** – Configuration option that enables **cvi42** to act as a DICOM Query/Retrieve SCP. **cvi42** will be able to be queried on image data by remote DICOM nodes.
- **Accept Unknown AE-Titles** – Configuration option that allows **cvi42** to operate in Promiscuous Mode and accept valid DICOM associations from any AE Title / IP address. It is recommended to configure all remote DICOM nodes properly instead of using this setting. This setting can also help when testing new connections.
- **Enable Low-Level Debug Log** – Configuration option that increases the logging level/details written to the application logs. This option is disabled by default and can generate large files.
- **Enable Storage Commitment SCP and SCU** – Configuration option that enables Storage Commitment Push Model SOP Class.
- **Enable MPPS SCU** – Configuration that enables the AE to log or track procedures performed by a modality.
- **Allow anonymous TLS connection** – Configuration option that enables the acceptance of anonymous Transport Layer Security (TLS) connections without requiring client authentication. This option is disabled by default and should be used with caution as it may introduce potential security risks

Remote DICOM Nodes

Used to configure the necessary DICOM connection information for any remote DICOM node.

Minimum required information: Remote Node IP address, Remote TCP Port, Remote AE Title.

Connections to remote nodes supporting TLS encryption is supported. This can be enabled by selecting the TLS option for the node. A red “x” icon will appear next to the checkbox. Clicking on the icon will bring up a dialog to select a certificate in PEM format. Once a valid certificate has been added the icon will change to a green check icon. Clicking on the green check icon will allow the certificate to be removed or reimported.

Fields Description

- **Address** - TCP Address or HostName of remote PACS.
- **AE-Title** - Application Entity Title of remote PACS (a single server might have several stores).
- **Port** - TCP port of remote PACS.
- **Description** - Pretty name for the cvi42 client UI.
- **Timeout** - Maximum wait time for a reply from Remote DICOM node.

- **Connect-As AE-Title** - Who we identify ourselves as (usually the same as the one you set above).
- **Restrict to Role** - Which user roles should be allowed to interact with this PACS.
- **TLS** - This feature allows the user to enable or disable remote node TLS support. Additionally, a button is provided to allow the user to install the CA (Certificate Authority) certificate of the remote node. The button's status indicates whether the certificate has been installed
- **Send** - Permit users to send to this PACS.
- **Anonymized Send** - Only send studies after anonymizing them (for research or consultant PACS).
- **Send Original Study** - When sending a study to a PACS, send the whole study, not just the images generated by **cvi42**.
- **Send Workspaces** - Send **cvi42** workspaces when sending whole studies.
- **Send Reports** - Send **cvi42** | Report secondary captures when sending whole studies.
- **Report DICOM Type** - Instructs report42 whether to output DICOM reports as Secondary Capture Image Series or a DICOM Encapsulated PDF document, which is rarely supported.
- **Q/R** - Allow users to query this PACS and receive from it.
- **C-GET** - Use the older C-GET protocol for receiving images, which is better when you're using a VPN or you are behind some kind of NAT router.
- **Character Encoding** - language you claim to use when interacting with the PACS.



WARNING: It is the site's responsibility to make sure TLS is enabled on the DICOM nodes for a secure environment.

1.9 Server Configuration (`cvi42serverconfig.ini` explained)

On Windows, the `cvi42serverconfig.ini` file is stored in `C:\ProgramData\cvi42`.

This file contains a list of configuration parameters for the **cvi42** Server.

Whenever changing the `cvi42Serverconfig.ini` file, the **cvi42** Server should be stopped, a backup taken of the file and changes made before restarting **cvi42** Server.

The parameters should only be edited by a server administrator, who needs to change the defaults of a particular server installation.

A description of each parameter is given below.

1.10 General Properties

Use a text editor to change the following parameters when configuring a **cvi42** Server.

- **DataFilePath** - Path to the folder containing the data for your **cvi42** system.
example: `DataFilePath=D:/ProgramData/cvi42`

- **ImageDBPath** – Path to the folder containing the image data for your **cvi42** system.
example: ImageDBPath=D:/ProgramData/cvi42/cvi42imagedb
- **SqlDatabasePath** – Path to the cvi42server database.
example: SqlDatabasePath=D:/ProgramData/cvi42/cvi42sqldb/cvi42Db.sqlite
- **ConnectionTimeout** – The number of seconds that a connection can be idle (no activity on the server connection) before it will be automatically closed. The default is 86400 seconds (24 hours).
example: ConnectionTimeout=86400
- **FailedLoginsBeforeTempLock** – Specifies the allowable number of failed login attempts before the account is temporarily locked-out. Default is 3. The lock-out duration is specified by the `FailedLoginTempLockDuration` parameter described below. If this parameter is set to -1 then the user will be locked out of the system until the administrator re-enables their account in the Server Admin preferences page. So, the lock-out duration parameter will be ignored in this case.
example: FailedLoginsBeforeTempLock=3
- **FailedLoginTempLockDuration** – Specifies the lock-out duration in seconds when an account is temporarily locked due to exceeding the maximum number of failed login attempts. The default is 60 seconds.
example: FailedLoginTempLockDuration=60
- **ClientPort** – Specifies the port that the server listens on for incoming connections. Default is 49696.
example: ClientPort=49696
- **AdminPort** – Specifies the port that should be used when connecting to the server to perform administrative functions. Default is 49697. Users with administrator permissions have exclusive access on this port.
example: AdminPort=49697
- **ClientPortIPv6** – Specifies the port the server listens on for incoming connections when using IPv6 addresses. Default is 48696.
example: ClientPortIPv6=48696
- **AdminPortIPv6** – Specifies the port that should be used when connecting to the server to perform administrative functions when using IPv6 address. Default is 48697.
example: AdminPortIPv6=48697
- **ThreadPoolSize** – Specifies the number of threads the server uses to handle incoming requests. Default is 10.
example: ThreadPoolSize=10
- **UseSystemProxyConfiguration** – Enables the **cvi42** Server to use the platform-specific proxy settings. Default is `false`.
- **BackgroundTaskThreadCount** – Specifies the number of threads the server uses for background task processing. Default is 4.
example: BackgroundTaskThreadCount=4

- **LogFilePath** - Path to the folder containing the log files for the server.
example: LogFilePath=D:/ProgramData/cvi42/ServerLogs
- **LogArchiveIntervalType** - Specifies the automatic archive interval type. Default type is 1 (daily archive). Possible values are:
 - 1 - daily (archive of logs is created daily)
 - 2 - weekly (archive of logs is created weekly)
 - 3 - monthly (archive of logs is created monthly)
 - 4 - custom interval (archive of logs is created after a custom number of days)example: LogArchiveIntervalType=1
- **LogArchiveCustomInterval** - Specifies the number of days that will elapse before the server logs are archived. Default interval 1. The custom interval is used only when the LogArchiveIntervalType is 4.
example: LogArchiveCustomInterval=1
- **PasswordRulesEnforced** - Specifies whether the server shall enforce password length and character requirements. Default is false.
example: PasswordRulesEnforced=false

If you set this parameter to `true`, then the system will check that passwords:

 - Must be at least 6 characters in length
 - Must contain at least one lower case alpha character
 - Must contain at least one upper case alpha character
 - Must contain at least one numeric character
- **PasswordExpiryThreshold** - Specifies the number of days that will elapse before users are prompted to change their password. Default is 0 days. Users will not be prompted to change the password when the PasswordExpiryThreshold is 0.
- **RecentPasswordListSize** - Specifies the number of recent passwords that cannot be re-used when selecting a new password. Default is 0. The system will allow users to re-use any password when the RecentPasswordList size is 0.
- **PasswordChangeRequiredAfterReset** - Indicates whether users must change their password the first time they login after an administrator has assigned (or reset) the password. Default is false.
example: PasswordChangeRequiredAfterReset=false
- **DebugLog** - Specifies where debugging output from the server is to be captured. Default is 0 (debug output disabled). Possible values are:
 - 0 - none (debug output disabled)
 - 1 - save to file
 - 2 - console (displayed only if server is running in a command window)example: DebugLog=0
- **ConfigBackupInterval** - Specifies how often the server config file will be backed up in seconds.
example: ConfigBackupInterval=1200

- **TrustedHosts** – Specifies a comma separated list of trusted host servers. When configuring this value provide the IP or fully qualified hostname.
example: TrustedHosts=server1.abc.com, server2.abc.com
- **EnableLdap** – A Boolean value used specifies whether or not **cv142** should use the configured LDAP settings for user authentication/authorization. Default value is `false`.
example: EnableLdap=false
- **ForceTrustedUrlLogin** – A Boolean value parameter used to enable/disable the authentication/authorization of non-admin users with the **cv142** user list. Default value is `false`.
example: ForceTrustedUrlLogin=true

1.11 PPU Properties

- **HostName** – Specifies the pay-per-use server to connect to when using pay-per-use licensing.
example: HostName=ppu-z01.circlecvi.com
- **Port** – Specifies the port to use for connecting to a pay-per-use server.
example: Port=443
- **Scheme** – Specifies the scheme to use for connecting to a pay-per-use server
example: Scheme=https

1.12 DICOM Network

- **CompressionScpEnabled** – This identifies whether the **cvi42** provides compressed transfer syntaxes for requests. Default is **true**.
example: `CompressionScpEnabled=true`
- **CompressionScuEnabled** – If configured, **cvi42** will ask for the supported compressed transfer syntaxes from the integrated repositories. Default is **true**. Some PACS require this to be set to **false**.
example: `CompressionScuEnabled=true`
- **RemoteDicomNodes\N\<parameter>** – This entry defines the connections for DICOM nodes (entities) that the server can interact with.
example:

```
RemoteDicomNodes\1\SendReports=true RemoteDicomNodes\1\AeTitle=HOROS
RemoteDicomNodes\1\CharacterEncoding=Unicode
RemoteDicomNodes\1\SendOriginalStudy=true
RemoteDicomNodes\1\ConnectAsAeTitle=CVI2019_2
RemoteDicomNodes\1\Id=@Variant (\0\0\0\x7f\0\0\0\x6Q\Uuid\0\xaf\xc7\xbc\x92\x
44\xall\x99\xdb\xe6\xb4\xdd\x99\x8f\xbf)
RemoteDicomNodes\1\RestrictToRole= RemoteDicomNodes\1\Send=true
RemoteDicomNodes\1\SendAnonymized=false
RemoteDicomNodes\1\ReportDicomType=Encapsulated PDF
RemoteDicomNodes\1\Description=PACS RemoteDicomNodes\1\QueryRetrieve=true
RemoteDicomNodes\1\Port=11112 RemoteDicomNodes\1\AnonymizeName=Anonymized
RemoteDicomNodes\1\Timeout=30 RemoteDicomNodes\1\SendWorkspaces=true
RemoteDicomNodes\1\CGet=false RemoteDicomNodes\1\Address=10.211.55.2
```

- **LocalPacsAETitle** – Specifies the AE Title when **cvi42** Server is configured to accept study data via DICOM push.
example: LocalPacsAETitle=CVI42
- **LocalPacsPort** – Specifies the port to use when **cvi42** Server is configured to accept study data via DICOM push.
example: LocalPacsPort=104
- **IncomingDirMonitorInterval** – The interval, specified in seconds, that the **cvi42** Server will check for incoming study data that is sent to the **cvi42** Server, and update the study list. Default is 10 seconds. This does not apply to the **cvi42** client causing the change of the study list (e.g. study import, DICOM retrieve). Its study list display will be updated instantaneously.
example: IncomingDirMonitorInterval=10
- **EnableStoreScp** – Indicates whether the server will accept study data via DICOM push.
example: EnableStoreScp=true
- **EnableQueryScp** – The server acts as a Query/Retrieve SCP for study level queries.
example: EnableQueryScp=true
- **EnableCGet** – Allows the use of C-GET instead of C-MOVE DICOM protocol for supported PACS.
example: EnableCGet=false
- **AcceptUnknownAeTitles** – Enables promiscuous mode for DICOM operations.
example: AcceptUnknownAeTitles=true
- **EnableLowLevelDebug** – Enables the DICOM debug log.
example: EnableLowLevelDebug=false
- **MaximumQueryResults** – Specifies the maximum number of results accepted from DICOM queries. Default value is 1000.
example: MaximumQueryResults=1000
- **MaximumConnections** – Specifies the maximum simultaneous number of DICOM associations that **cvi42** will allow. Default value is 10.
example: MaximumConnections=10


1.13 AD/LDAP Integrated Password Authentication

- **PrimaryServer** – Specifies the location of the Active Directory/LDAP server. **cvi42** will initially contact this server when authenticating users using Active Directory/LDAP.
example: PrimaryServer=ad-master.srclookup.com
- **SecondaryServer** – Specifies the location of the Active Directory/LDAP server. **cvi42** authenticates users using Active Directory/LDAP against the server specified by primary server. When the authentication against the primary server fails, **cvi42** will authenticate users using a secondary server, specified by this parameter.
example: Secondaryserver=second.ad-master.srclookup.com

- **TLSSSLConnection** – Instructs **cvi42** to construct a secure communication channel when connecting to an Active Directory/LDAP server using TLS/SSL.
example: `TLSSSLConnection=true`
- **DomainName** – Specifies the domain name, if necessary, that the user would use during login. It is important to note that Active Directory accepts two types of domain names. Firstly, define a domain name with a trailing backslash "\\\" (for example, `srclookup\\`). Secondly define a domain name with a prepended "@" (for example `@srclookup`).
example: `DomainName=srclookup\\`
- **BaseDN** – Specifies the location of the Active Directory/LDAP tree to use for user authentication, searching for users, and looking up user information.
example: `BaseDN="DC=srclookup,DC=com"`
- **UserAttribute** – Instructs what Active Directory/LDAP attribute to use when searching for users. This is important during authentication, as Active Directory/LDAP needs to identify whether the user exists on the system.
example: `UserAttribute=sAMAccountName`
- **AdditionalUserAttribute** – Specifies an additional restriction that needs to be accounted for when authenticating against Active Directory/LDAP server. For example, the Active Directory/LDAP server administrator has created a group called "cvi42", and only users in this group are permitted access to **cvi42**. In order for **cvi42** to enforce this, this parameter needs to be specified.
example: `AdditionalUserAttribute="memberOf=CN=cvi42,CN=Users,DC=srclookup,DC=com"`

1.14 Server-side processing configuration (Node42)

- **MaxNumberOfThreads** – Max number of threads available for the Machine Learning processing. The default value when the server creates the server config is `min(max(system_threads - 2, 1), 4)`. When Node42 is started, it will take the number from the `cvi42Serverconfig.ini`.
If the configured number of threads is less than 1, it will be set to the default.
Log message that the value has been overridden, `logNode.txt`: *UNKNOWN: Using default number of threads "4", available system threads "12"*.
If it is more than `max(system_threads - 2, 1)` then it will use `system_threads - 2`.
Log message that the value has been overwritten, `logNode.txt`: *WARNING: Too many threads configured "50", using maximum "10"*.
You can check the number of system threads available in Windows by opening Task Manager:



If Node42 is already running, you should kill node42 process in the Task Manager to reload configuration. **cvi42** Server starts a new node42 process if it's killed.

- **MaxProcessingTimeSeconds** – This is the maximum number of seconds node42 will process a series before timing out, and has a default value of 600 seconds (10 minutes). When processing times out, any in progress processing will be cancelled and no server side processing data will be stored for that series. If study has other series, node42 will continue processing the remaining series.
- **ContourDetectionTriggerDelay** – This is the time it takes, in seconds, for server-side processing to be triggered, after a DICOM study is completely imported into **cvi42** or a DICOM study is completely pushed from the scanner to **cvi42** Server. By completely, it means that the last image from the DICOM study is transferred to the **cvi42** Server. Default value for this parameter is 30 seconds.

1.15 Gateway Configuration (cvi42_gateway.ini)

On Windows, the `cvi42_gateway.ini` file is stored in `D:\ProgramData\cvi42.`

This file contains a list of configuration parameters for the **cvi42** Gateway.

Whenever changing the configuration file, the **cvi42** Gateway should be restarted.

Section **[cvi42server]**:

- **cvitokenpubkey** – This is the path to the **cvi42** Server public key. This key is used to validate auth tokens generated by **cvi42** Server

Section **[cvi42_gateway]**:

- **webport** – Server configuration web interface port
- **webcvi42installerpath** – Path to the **cvi42** installer packages used by **cvi42 Client Upgrade Agent**

1.16 Webclient Service Configuration (cvi42_webclient_service.ini)

On Windows, the `cvi42_webclient_service.ini` file is stored in `D:\ProgramData\cvi42.`

This file contains a list of configuration parameters for the **cvi42** Webclient Service.

Whenever changing the configuration file file, the **cvi42** Webclient Service should be restarted.

Section [webclient_service]:

- **webfqdn** – **cvi42** Web Module UI FQDN
- **webport** – non-secure port for the **cvi42** Web Module UI
- **webtlsport** – secure port for the **cvi42** Web Module UI
- **recruiterport** – port where **cvi42** Webclient Service will listen to requests coming from **cvi42** Webclient Manager
- **rpcport** – port where **cvi42** Webclient Service will listen to requests coming from a **cvi42** worker (a **cvi42** worker is a component managed by **cvi42** Webclient Manager that handles one user session. So, for instance, if there are 5 users connected to the **cvi42** Web Module, there should be 5 instances of **cvi42** worker running)

To setup HTTPS connection to the **cvi42** Web Module, these properties must be set:

- **webtls** – (true | false), to enable/disable HTTPS connection to the **cvi42** Web Module, when setting this parameter to true, you need to setup the certificate and private key:
 - **webtlscert** – path to the TLS certificate
 - **webtlskey** – path to the TLS private key
 - or setting **webtlsautoselfsigned** to true, enabling self-signed certificate
- **webforcehttps** – (true | false), when true, will redirect the user to HTTPS connection when user tries to log into **cvi42** Web Module in the HTTP mode

1.17 Webclient Manager Configuration (cvi42_worker_manager.ini)

On Windows, the `cvi42_worker_manager.ini` file is stored in `D:\ProgramData\cvi42.`

This file contains a list of configuration parameters for the **cvi42** Webclient Manager.

Whenever changing the configuration file file, the **cvi42** Webclient Manager should be restarted.

Section [worker_manager]:

- **webclientservicehost** – FQDN of **cvi42** Webclient Service
- **webclientservicerecruiterport** – port that **cvi42** Webclient Service will be listen for connections (should be the same as **recruiterport** in the **cvi42** Webclient Service)


2 cvi42 Configuration Portal

In 5.16 and later releases we are introducing a new method to configure the **cvi42** Server named **cvi42 Configuration Portal**.




IMPORTANT: **cvi42** Configurator Portal is the web interface to configure **cvi42** Server properties. It still limited in terms of functionality; administrators can experiment it however the preferable way to configure the server is by login in the **cvi42** Server admin port.


You can access **cvi42 Configuration Portal** via a browser by the url: `http(s)://<IP or FQDN>:4299`



Default credentials: **admin** / *(password changed during installation)*



The interface is very intuitive, in the Dashboard you can check the status of the **cvi42** Server components, check licenses available, etc.



cvi42 Configuration Portal

General

Remote Client Connection Timeout: 86400 Seconds

Failed Login Temporary Lock Duration: 60 Seconds

Failed Logins Before Temporary Lock: 3

Password Expiry Threshold: 0 Days

Recent Password List Size: 0

Thread Pool Size: 10

Data Files Path: D:\ProgramData\cvi42\

Image Database Path: D:\ProgramData\cvi42\cvi42imagedb

Use System Proxy Configuration: ☐

Client Port: 49696

Admin Port: 49697

Client Port IPv6: 49696

Admin Port IPv6: 49697

Background Task Thread Count: 4

Debug Log: None


SQL Database Path: D:\ProgramData\cvi42\cvi42sqldb\cvi42Db.sqlite

Log Files Path: D:\ProgramData\cvi42\ServerLogs

Password Rules Enforced: ☐

Password Change Required After Reset: ☐

In the General option, you can change some of the server parameters, paths of data and database folders, ports, etc. You should restart the **cvi42** Server whenever these configs are changed.



cvi42 Configuration Portal

Network

Storage

All File: C:\42

Storage SCP Port: 154

Storage SCP TLS Port: 2762

Database Update Interval: 10 Seconds

Storage Commitment Retries: 0

Storage Commitment Retry Delay: 0 Seconds

Default MPPS Server:

Default Mobility Worklist Server:

Default QIP Server:

Options

Enable Storage SCP: ☐

Enable QIP SCP: ☐

Accept Untrusted All Files: ☐

Enable Low-Level Debug Log: ☐

Enable Storage Commitment SCP: ☐

Enable Storage Commitment SCU: ☐

Enable MPPS SCU: ☐


Allow anonymous TLS connection: ☐

Submit

Remove DICOM Nodes

Address	All File	Port	Description	Timeout	Connect to All File	Request to Role	TLS	QIP Port	Secret	Anonymous Secret	Secret Original Study	Secret Worklist	Secret Reports	Report DICOM Type	QIP	QIPS	Character Encoding
localhost	ANY SCP	154	PACS	30	CVI42				✓		✓	✓	✓	Reported PDF	✓		Unicode

This interface has similar functionality described in section 1.8



cvi42 Configuration Portal

Server-Side Processing

Note

Changes to Server-Side Processing settings will take effect when the cvi42® Server is restarted.

Settings


Enable Server-side processing: ☒

Server side Processing Trigger Delay after DICOM Import/Push: 600 Seconds

Server-side processing enables the server to perform AI on imported studies. To enable, toggle the **Enable Server-side-processing** switch. Server-side Processing Trigger Delay after DICOM Import/Pushes the time to wait since last image for a study was received before triggering AI processing on that study.


IMPORTANT: If **cvi42** Server is installed on a separate machine, you should open TCP/4298 port on this machine, so **cvi42** client can communicate to the server-side processing component. You should open the *Windows Defender Firewall*.

For the remaining steps of the configuration, just use the defaults and in the final screen give a name for the rule.




The screenshot shows the 'License' page in the cvi42 Configuration Portal. The left sidebar contains navigation links: Dashboard, General, Network, Server-Side Processing, License (selected), Server Admin, LDAP Admin, and Client Upgrade. The main content area is titled 'Licence' and includes a 'License Status' section stating '1 server activation license available for the current product version.' Below this is a table of 'Available Licenses' with columns: Product, Start Date, Expiry Date, Maintenance Expiry, License Holder, Status, Count, Machine ID, and Activation Key. The table lists several licenses for products like cvi42auto calcium, cvi42auto coronary, cvi42 sax 3d-function, cvi42 bi-tri-planar-function, cvi42-flow, cvi42 multiple-lax-function, and cvi42 perfusion. At the bottom, there are sections for 'License Activation' with an 'Activation Key' input field and an 'Activate' button, and 'License Renewal' with a 'Renew Current Activation' button.

The License page can be used to activate your licenses by entering an activation key or renew current activation.




The screenshot shows the 'Server Admin - Users' page in the cvi42 Configuration Portal. The left sidebar is the same as the previous screenshot, with 'Server Admin' > 'Users' selected. The main content area is titled 'Server Admin - Users' and includes a 'User Accounts' section. It displays a table with columns: Active, User ID, First Name, Last Name, Physician ID, Authentication Server, Viewer, Technician, Analyst, Reporter, Data Administrator, User Administrator, System Administrator, PACS Administrator, and ADAS3D User. Two users are listed: 'admin' (Administrator) and 'alpha_user' (User). Below the table are buttons for 'Delete', 'Reset Password...', 'Change Physician ID...', 'Enable Account', 'Unlink from LDAP', 'Add...', 'Roles/Permissions...', 'Apply', and 'Refresh'.


The **Server Admin->Users** page can be used to manage users, roles and permissions.




The **Server Admin->Logs** page can be used to view and manage the **cvi42** Server logs.




You also have several functions to manage the **cvi42** Server database.



You can setup certificate for TLS connection, this setup is also available in **cvi42** Client.



You can setup connection to AD/LDAP, this setup is also available in **cvi42** Client.



The **Client Upgrade** page can be used to schedule the deployment of installer packages saved during the install process with the **Save installer package for IT-scheduled client upgrades** server install option. When an upgrade is scheduled, client machines that have been configured with the **cvi42 Client Upgrade Agent** install option will download the selected installer package before installing a newer version of **cvi42** at the set time.



IMPORTANT: IT-scheduled client upgrades feature allows IT Administrators to update clients remotely. If you have already an automated method for updating clients, this feature is not recommended for you. Please contact Circle's Customer Support Team at support@circlecvi.com to obtain more information about **IT-scheduled client upgrades**.

3 Housekeeping

The housekeeping system is a rule-based system to automate maintenance of the **cvi42** DICOM study database. Typical use-cases are archival, routing and workflow.

3.7 Overview

All actions of the housekeeping system are defined by a list of rules. Each rule consists of a set of criteria and a list of actions. All criteria must be satisfied in order for a rule to apply to a specific DICOM study.

The housekeeping system is active according to a weekly schedule specified by the administrator. When the housekeeping system is active, it matches the list of rules against the **cvi42** DICOM study database periodically and executes resulting housekeeping actions. The matching interval is specified by the administrator.

3.7.4.1 Rule matching

The housekeeping system will periodically process the list of rules and match it against the studies present in the **cvi42** DICOM study database. For this, the system considers each study and matches its properties against the list of rules in order from top to bottom. When the criteria in a rule match, the actions specified in the rule are queued for execution. Subsequent rules will be matched against the study under consideration once the actions of the applying rule have been executed. After a rule has matched or all rules have been considered for a specific study, the next study is matched against the rule list until all studies have been processed.

Once matching has completed, the queued housekeeping actions are executed.

3.7.5 Rule execution

All queued actions are processed in order of queuing. All actions are logged. Depending on the specific action, a failed action results in the execution of the whole rule to either fail or to be suspended for retry at the point of failure. Retry is supported for actions that are likely to succeed when retried such as DICOM study export (which may fail due to temporary lack of disk space) or DICOM network transmission (which may fail due to intermittent network problems or PACS server downtime).

After all queued rules have been executed, another rule matching run is invoked because rules in general depend on study attributes that are changed by rule execution, for example, assignment/removal of study tags.

3.8 Rules

Housekeeping rules consist of:

- a name (for reference)
- a flag for enabling/disabling a rule (temporarily or permanently)
- the recurrence definition:

- "once" or "periodically" with an interval in days, weeks, months or years
- a list of criteria
- a list of actions

3.8.4 Criteria

3.8.4.1 Study Date

This criterion filters studies by the DICOM study-date attribute. Studies are filtered by their age, i.e. as "older than" or "newer than" a specified number of days, weeks, months or years.

Studies that lack the DICOM study-date are treated as "in the future" which means that rules that select studies that are i.e. "older than one year" will never match. It may make sense to use the "import date" criterion instead.

3.8.4.2 Study Description

This criterion filters studies by the DICOM "study description" attribute. The description is matched against either:

- a fixed string
- a fixed substring
- a wildcard pattern:
 - "?" matches any character
 - "*" matches zero or more arbitrary characters
 - "[...]" matches any of the characters listed inside the brackets
 - any other character matches only itself
- a regular expression:
 - Please see <http://qt-project.org/doc/qt-4.8/qregexp.html#introduction>.

Matching is set to be either case-sensitive or case-insensitive.

3.8.4.3 Institution Name

This criterion filters studies by the DICOM "institution name" attribute. The matching is done as described in section 3.8.4.2 Study Description.

3.8.4.4 Manufacturer

This criterion filters studies by the DICOM "manufacturer" attribute. The matching is done as described in section 3.8.4.2 Study Description.

3.8.4.5 Model

This criterion filters studies by the DICOM "model" attribute. The matching is done as described in section 3.8.4.2 Study Description.

3.8.4.6 Modality

This criterion filters studies by the DICOM "modality" attribute. The matching is done as described in section 3.8.4.2 Study Description.

3.8.4.7 Study Size

This criterion filters studies by their size (in MB). The studies are filtered by comparing the study size against a given size.

When upgrading from an earlier version of **cvi42** Server, the study size database field is only initialized at first use. The first run of a housekeeping rule list that contains the study size criterion will thus take significantly more time than subsequent runs because aggregating the study size from the DICOM image database causes high disk activity.

3.8.4.8 Import Date

This criterion filters studies by the import-date attribute. Studies are filtered by the age of the import date, i.e. as "older than" or "newer than" a specified number of days, weeks, months or years.

The import date is always present and is updated whenever new DICOM image data is added to a study.

3.8.4.9 Date of Last Read

This criterion filters studies by the date-of-last-read attribute. Studies are filtered by the age of this date, i.e. as "older than" or "newer than" a specified number of days, weeks, months or years.

The date of last read is initially empty and treated as "in the future" in this case. It is updated whenever the study is opened or closed. Display of the study in the patient list does not update the date of last read.

3.8.4.10 Date of Last Write

This criterion filters studies by the date-of-last-write attribute. Studies are filtered by the age of this date, i.e. as "older than" or "newer than" a specified number of days, weeks, months or years.

The date of last write is updated when the study is initially imported, images are added to or removed from the study or workspace data is saved.

3.8.4.11 Study Tags

This criterion filters studies by the tags assigned to the study. Studies are selected when the assigned tags "contain any of" or "miss any of" a given set of tags. Rules that require a study to "contain all of" or "miss all of" a given set of tags can be built by using multiple "Study Tags" criteria.

3.8.4.12 Available Disk-Space

This criterion relates to the available disk-space (in MB) of the storage media in which the DICOM image database file system resides. This value is not a study attribute and therefore enables or disables the rule altogether depending on the available disk-space. The available disk-space is compared to a specified value.

3.8.5 Actions

3.8.5.1 Assign Study Tags

This action assigns a given set of tags to the study. Assigning a tag that is already present is not an error. Other tags that are assigned to the study are kept.

3.8.5.2 Remove Study Tags

This action removes a given set of tags from the study. Removing a tag that is not present is not an error.

3.8.5.3 Convert Workspace Data to DICOM

This action converts all workspace data of the study to DICOM workspace format. Workspace data of all users is converted. This action is useful to run before 3.8.5.4 Store DICOM Data on PACS or 3.8.5.5 Export DICOM Data to filesystem such that the corresponding workspace data is transferred alongside the DICOM image data.

This action has the option to use the "Secondary Capture Image Storage" DICOM SOP class instead of "Multiframe Grayscale Byte Secondary Capture Image Storage" or "Multiframe True Color Secondary Capture Image Storage" DICOM SOP class if necessary.

3.8.5.4 Store DICOM Data on PACS

This action stores DICOM data of the study on a specific DICOM node. This action can either store all DICOM data or can be limited to only store DICOMs generated by **cvi42** . In the latter case, the action can be further limited to only store workspace DICOMs, report DICOMs and/or other DICOMs generated by **cvi42** (i.e. reformatted images).

As this action can potentially cause data to be sent to unintended destinations, special care must be taken when using this action. Please, refer to section 3.9.4 Simulation for steps on verifying that the rule matches only the desired studies.

Please note that if PACS names have been changed or added in the configuration dialogue but not yet saved to the server, the Housekeeping configuration UI will still show the names as configured on the server.

3.8.5.5 Export DICOM Data to filesystem

This action exports DICOM data to filesystem. The type of DICOM data that is exported can be limited as described in section 3.8.5.4 Store DICOM Data on PACS. The directory path specified as export target may contain the following placeholders which allow to automatically build up a chronological directory structure:

- "{YYYY}" is replaced by the 4-digit year
- "{YY}" is replaced by the 2-digit year
- "{MM}" is replaced by the 2-digit month
- "{DD}" is replaced by the 2-digit day of the month

Placeholders may occur multiple times. Example: "E:\DicomArchive\{YYYY}\{YYYY}-{MM}\\" will export to:

- "E:\DicomArchive\2014\2014-12\\"
- "E:\DicomArchive\2015\2015-01\\"
- "E:\DicomArchive\2015\2015-02\\"
- ...

Each study will be placed into an individual sub-directory of the specified export directory.

3.8.5.6 Delete Study

This action removes all DICOM data and workspaces of the given study from the database. As this action is not revertible, special care must be taken when using this action. Please, refer to section 3.9.4 Simulation for steps on verifying that the rule matches only the desired studies.

Alternatively, refer to section 3.8.5.1 Assign Study Tags in order to assign a "trash bin" tag instead of directly deleting the studies. This allows to review which studies are assigned to the "trash bin" tag and then delete those manually from the patient list.

3.8.5.7 Stop processing subsequent rules

This action causes the subsequent rules in the rule list not to be considered for the matched study. The stop is active as long as the study still matches the criteria, i.e. independently of rule recurrence.


3.8.6 Recurrence

Recurrence defines whether a rule is applied repeatedly to the same study. Recurrence is defined as either of:

- "once" – the rule is only applied once to each matching study. Even if the rule criteria/actions are changed later, studies that have been processed by the rule once, are not considered again. (If it is intended that the rule shall be applied again to all matching studies once, i.e. because the criteria or actions have been changed, the rule can be duplicated, and the original rule be deleted. The duplicated rule is considered unrelated by the Housekeeping system and all studies will be considered for the rule again.)
- "periodically every N days/weeks/months/years" – the rule is considered again for a previously processed study after the specified time has elapsed after queuing of the last rule execution on the study.

Rule recurrence can be changed later. After switching from "once" to "periodically", studies that have been processed before are considered again (after elapse of the period interval). Likewise, after switching from "periodically" to "once" all studies that have ever been processed are not considered anymore.

3.9 Rule Editor



The rule editor is located in the **Rules** tab of the Housekeeping section of the configuration dialogue. The Housekeeping section is only enabled when connected to the server administrator port. In the upper part of the rule editor, the rule list is displayed. For each rule, the name, recurrence, criteria and actions are listed. The names of disabled rules are written in *italic*.

The top/up/down/bottom buttons to the right of the rule list are used to move the currently selected rule to the top/bottom or up/down in the list. The new/duplicate/delete buttons below the rule list are used to create, duplicate or delete rules.

The "display log" button is used to open the log and control interface (refer to section 3.10.4.1 Log and Control). To the right of the "display log button", the effect of the edited (unsaved) rule list can be simulated, refer to section 3.9.4 Simulation.

In the lower part of the rule editor, the currently selected rule can be edited. This section starts with the field for the rule name, the "enabled" checkbox and the specification of the recurrence. Below, there are two panes in which the criteria and actions are composed.

The criteria are composed by clicking "and . . ." and selecting the desired criterion (repeatedly). For each criterion, a line is added to the criteria pane for editing the specific properties of the criterion. A criterion can be removed again by clicking the "x" button at the start of the line. As all criteria are combined by a logical "and", the order is insignificant and cannot be changed.

The actions are composed by clicking "and then . . ." and selecting the desired action (repeatedly). For each action, a line is added to the actions pane for editing the specific properties of the action. An action can be removed again by clicking the "x" button at the start of the line. As the order of actions is significant, actions can be reordered using the "move up" and "move down" buttons next to the "x" button.

Please note that new rules are initially set as "disabled" such that the "enabled" checkbox needs to be ticked manually after the rule has been composed.

Please note that when a rule is deleted, executions of the rule which have already been queued but have not yet been processed are cancelled.


3.9.4 Simulation

The currently edited rule list can always be simulated against the current **cvi42** DICOM study database. Only rules that are marked as "enabled" are active in simulation as in execution. A simulation is started by specifying a number of simulation iterations, a time interval for each iteration and clicking the "start" button. As many rules include ages (i.e. age since study import, age since last read, ...) it is important to cover a relevant time-span for simulation. For example, when working on a rule that archives data after a year, selecting a simulation of 24 iterations with an interval of one month would be appropriate while in contrast 10 iterations with an interval of one day wouldn't give meaningful results.

Apart from the effect of the lapsed time, simulation also handles the effects of tag assignment/removal and the stop action. This can be used to simulate workflow rule sets. Simulation also handles study deletion and will not match rules against studies that are simulated as deleted again.

Other actions are merely logged for the simulation results, i.e. when simulating "convert workspace data to DICOM", "store DICOM data on PACS" or "export DICOM data to filesystem" actions, no further simulation such as checking DICOM node connectivity or checking for available disk-space is carried out.

While simulation is running, a progress indicator is shown in the "simulation" section of the rule editor. Once finished, the results are displayed in a separate "Housekeeping simulation results" window.




Housekeeping simulation results		
iterations	24	
interval	1 month(s)	
▼ statistics		
studies affected	15	
studies deleted	15	
tagging operations	0	
workspace conversions	15	
DICOM store operations	0	
DICOM export operations	15	
▼ iteration 1	2014-11-27T17:35:17 2 rule(s) applied	
▼ Archive	unknownunknown1.2.276.0.7230010.3.1.4.83... Checkerboard	
converting workspace data to DICOM (using secondary capture image storage)		
exporting DICOM data (all images) to E:\Archive\2014\2014-11\unknownunknown1.2.2...		
deleting study		
finished successfully		
▼ Archive	unknownunknown1.2.276.0.7230010.3.1.2.83... Check 2	
converting workspace data to DICOM (using secondary capture image storage)		
exporting DICOM data (all images) to E:\Archive\2014\2014-11\unknownunknown1.2.2...		
deleting study		
finished successfully		
▼ iteration 2	2014-12-27T17:35:18 0 rule(s) applied	
no actions		
▼ iteration 3	2015-01-27T17:35:19 0 rule(s) applied	
no actions		
▼ iteration 4	2015-02-27T17:35:20 0 rule(s) applied	
no actions		
▼ iteration 5	2015-03-27T17:35:21 5 rule(s) applied	
▼ Archive	unknownunknown1.2.276.0.7230010.3.1.4.22... Kor (CTA)	
converting workspace data to DICOM (using secondary capture image storage)		
exporting DICOM data (all images) to E:\Archive\2015\2015-03\unknownunknown1.2.2...		
deleting study		
finished successfully		
▼ Archive	200612190000101.3.6.1.4.1.5962.1.2.5017.1... Brain Functional	
converting workspace data to DICOM (using secondary capture image storage)		
exporting DICOM data (all images) to E:\Archive\2015\2015-03\200612190000101.3.6...		
deleting study		
finished successfully		

The result first lists the selected number of iterations and interval. Then a statistical summary of the simulation is given, counting the total number of affected studies and how often actions of different classes were executed (studies deleted, tagging operations, workspace conversions, DICOM store operations, DICOM export operations).

Next, the individual simulation iterations are listed: The first line lists the simulated date and how many rules applied in total. Then, each rule application is listed by the rule name, the study that the rule applied to (including the DICOM study instance UID and the patient name for reference) and the list of actions that were simulated.

Please take care to review the simulation results carefully to make sure the rule list behaves as intended. This is particularly important for rule lists that include the "delete study" action which can lead to irrevocable data loss and for rule lists that include the "store DICOM data on PACS" action which can potentially lead to sending data to unintended destinations.

3.10 Settings



In the "Settings" tab of the Housekeeping section in the configuration dialogue, parameters for the overall behaviour of the Housekeeping system are specified.


The first setting is the interval in which the housekeeping system processes its rule list during hours of operation. Smaller values put a higher load on the server but may be desirable when using rule lists for workflow organization.

The second setting specifies how long the server will retain log entries inside the database. These log entries are displayed in the 3.10.4.1 Log and Control. Only log entries that are not needed for the system anymore (i.e. for keeping track of which studies a rule has already been applied to) are removed from the database after the specified period of time. Apart from the logs kept in the database, the

Housekeeping system also logs all actions to the `logHousekeeping.txt` file to which this setting does not apply.

Below this, the Housekeeping system schedule can be defined as a list of timespans per weekday. Buttons are provided to copy the data entered for Monday to all week or all weekdays and to copy the data entered for Saturday to all weekend. The schedule can be used to ensure, the Housekeeping system activities do not interfere with day-time usage of the system.

3.10.4.1 Log and Control



The log and control interface displays the most recent activities of the Housekeeping system. For each applied rule, the study (including DICOM study instance UID and patient name for reference), the rule name, the status and the date of the entry are displayed.

While the rule is queued for execution, it is marked with a blue button. If rule execution has failed, it is marked with a red button. If it is suspended for retry, it is marked with a yellow button. Each entry can be expanded by clicking on the triangle icon to the left in order to display the specific actions.

At the bottom of the window, the retry/cancel buttons can be used to retry or cancel selected suspended rules. As studies that have a suspended rule are not considered for other rules, it is important to review the log periodically. Queued rule executions cannot be cancelled manually but are cancelled when the rule is deleted.

The reload button reloads the log from the server. The spin-box next to it is used to specify the timespan to display the log for. After changing the timespan, the list is reloaded automatically.

4 cvi42 Default Roles

Role	Permissions
Viewer	Able to view study data and existing workspaces.
Technician	Able to import study data and enter patient biometric data.
Analyst	Able to save analysis on study data in workspaces or copy other user workspaces.
Reporter	Able to report on study data.
Data Administrator	Able to clean up the database and unlock user accounts.
User Administrator	Able to create, edit, and delete users accounts.
System Administrator	Able to alter system properties and administrate logs.
PACS Administrator	Able to manage PACS server connection properties
ADAS3D User	Able to open studies in ADAS3D

5 cvi42 Network Communications Matrix

Category	Source	Destination	Default Port	Comment
Mandatory	cvi42 clients	cvi42 Server	tcp/49696	User port with no encryption
Mandatory	cvi42 clients	cvi42 Report Server	tcp/4280 (http, websocket)	Report Web Interface
Mandatory	cvi42 clients	cvi42 Server	tcp/4298 (http)	Server-side processing
Mandatory	cvi42 clients	cvi42 Server	tcp/4299 (http)	Server configuration web interface
Mandatory	PACS / Scanners	cvi42 Server	tcp/104 (DICOM)	DICOM listener
Mandatory	cvi42 Server	https://rlm.circlecvi.com	tcp/443 (https)	Online License Activation
Mandatory	cvi42 Web Viewer	cvi42 WebClient Service	tcp/4293 (http ws)	User port with no encryption
Mandatory	cvi42 Web Viewer	cvi42 WebClient Service	tcp/4287 (http ws)	Web reverse-proxy port to cvi42 report webserver (Apache)
Optional	PACS / Scanners	cvi42 Server	tcp/2762 (DICOM)	DICOM listener with TLS encryption
Optional	cvi42 clients	cvi42 Server	tcp/49697	Admin port with no encryption
Optional	cvi42 clients	cvi42 Server	tcp/4390	User port with TLS encryption
Optional	cvi42 clients	cvi42 Server	tcp/4391	Admin port with TLS encryption
Optional	cvi42 Server	https://ppu-a02.circlecvi.com	tcp/443 (https)	Pay Per Use (PPU) license only
Optional	cvi42 Server	https://ppu-d01.circlecvi.com (EMEA region)	tcp/443 (https)	Pay Per Use (PPU) license only
Optional	cvi42 clients	cvi42 Server	tcp/5053	ADAS floating license only
Optional	cvi42 clients	cvi42 Server	tcp/5117	ADAS floating license only
Optional	cvi42 Web Viewer	cvi42 WebClient Service	tcp/443 (https wss)	User port with TLS encryption
Optional	cvi42 Web Viewer	cvi42 WebClient Service	tcp/4288 (https wss)	Web reverse-proxy port to cvi42 report webserver (Apache)
Optional	cvi42 Worker Manager	cvi42 WebClient Service	tcp/4292	
Optional	cvi42 Worker	cvi42 WebClient Service	tcp/4289	

6 cvi42 and TruPlan client installation

6.7 Silent installation of cvi42 client

You can install **cvi42** client silently via command line.

First, make sure you open the command prompt on Windows with administrative privileges.

To install **cvi42** with all default options, you can run this command:

```
msiexec /I "<msi file>" CVI42_LICENSE_AGREEMENT=true APPDIR="C:\Program Files\cvi42"  
SERV_ADDR=<IP or FQDN where cvi42 Server is installed> SERV_NAME="cvi42 Server"  
SERV_PORT=49696 /qn /Li tmp.log
```

- /i - installs the product
- /qn - installs the product in quiet mode with no user interaction
- /Li <logfile> - outputs the progress in a file name



IMPORTANT: Besides /i /qn /Li commands to instrument MSI installation, you can consult this link for additional options:

<https://learn.microsoft.com/en-us/windows-server/administration/windows-commands/msiexec>

To see if installation completed, you can check in the log file for the text: *Windows Installer installed the product.*

You can also uninstall the product through command line:

```
msiexec /uninstall "<msi file>" /qn /Li tmp.log
```

To see if product has been uninstalled, look for this text in the log file: *Windows Installer removed the product.*

6.8 Client Installation (including TruPlan)




IMPORTANT: System Requirements can be accessed from this link:
https://www.circlecvi.com/docs/product-support/cvi42_System_Requirements_6.1.pdf



IMPORTANT: If you are upgrading **cvi42** client on a macOS environment from a 5.x version, you should first uninstall **cvi42** before installing the new version. This rule does not apply for Windows environment.

To install **cvi42**, you should download and run the setup program, which will automatically perform all the necessary configuration steps.


You will need to log in to an account with administrator privileges on the machine you are installing to.




The included cvi42 and TruPlan build and versions numbers are shown on each installer page. Click **Next** to continue.



You should read, accept the **License Agreement**, and click **Next** to continue.



Select **cvi42 Client Only** option and click **Next** to continue.




The TruPlan client can be optionally installed, accessing TruPlan will require an additional license. TruPlan clients before version 3.2.3 cannot connect to the **cvi42** Server, previous TruPlan 2.x and 3.x installations should be uninstalled before proceeding with the **cvi42** 6.2.x install. Image data from previous TruPlan installations can be imported to the **cvi42** Server with the SendTo Utility or the client image import features.


Leave **cvi42 Client Upgrade Agent** checked if you want to use **IT-scheduled client upgrades** feature, and click **Next**



IMPORTANT: *IT-scheduled client upgrades* feature is newly introduced in 5.17, it allows IT Administrators to update clients remotely. If you have already an automated method for updating clients, this feature is not recommended for you. Please contact Circle's Customer Support Team at support@circlecvi.com to obtain more information about **IT-scheduled client upgrades**.



Select the installation folder and click **Next**



The image shows a Windows-style window titled "cvi42 Setup". Inside the window, the title "Server Connection Settings" is displayed in bold, followed by the instruction "Configure the cvi42 Enterprise Server's connection info". The cvi42 logo is visible in the top right corner. The main area contains five configuration fields: "cvi42 Server Name" with the value "cvi42 Server", "cvi42 Server Address" with the value "cvi42-server.remote", "cvi42 Server Client Port" with the value "49696", "cvi42 Configurator Port" with the value "4299", and "Enable Secure Connection" with an unchecked checkbox. At the bottom right, there are three buttons: "< Back", "Next >" (which is highlighted with a blue border), and "Cancel".

Server Connection Settings
Configure the cvi42 Enterprise Server's connection info

cvi42 Server Name: cvi42 Server

cvi42 Server Address: cvi42-server.remote

cvi42 Server Client Port: 49696


cvi42 Configurator Port: 4299

Enable Secure Connection: ☐


< Back Next > Cancel

Configure the **cvi42** remote server connection.

You can now access **cvi42** from Windows Start menu:




If the TruPlan client was selected, it will also be available in the start menu:




6.9 Configure cvi42 client to connect to the Server


The login dialogue will be configured by default to connect to a local server. This information will be shared with the TruPlan client if it's installed. Additional connection setup can also be done from the TruPlan client.



To configure additional servers, click the **Setup** button.



Initially there will only be a Local Server connection in the list. Click **Add...** to add a new server connection.



In the Add **cvi42** Server Connection dialogue, fill in the necessary fields.

- **Server Name** – This is any name you choose to identify the server.
- **Server Address** – This is the IP address or host name of the **cvi42** Server you are connecting to.
- **Server Port** – This is the communication port the server uses for connections. The default port is 49696. If the target server is configured to listen on a different port, enter the new value here.



IMPORTANT: Before configuring a secure server connection, the certificate and private keys must first be imported to the **cvi42** Server. For more information on Enabling TLS in **cvi42** refer to section 1.4 below.


- **Server Port for Administration** – If you are required to administrate **cvi42** Server, e.g. setup DICOM nodes, you will need to create a server connection pointing to port 49697. For setting up a secure connection, the default port is 4931 (secure). You will also need to log in as an admin user.



IMPORTANT: The Server Port and TLS Server Port values specified here must match the port number that is configured for the server that you want to connect to.

- **Connect as TLS** – This configuration option allows a user to connect to a secure port on the server. If enabled, the TLS Server Port field will be editable and used to specify the secure port. If disabled, the Server Port field will be editable and used to specify an unsecure port.
- **TLS Server Port** – This is the communication port the server uses for secure connections. The default port is 4390. If the target server is configured to listen on a different port, enter the new value here.
- **Validate Server Certificate** – This option is unchecked by default. When checked it means that the server should have a valid certificate, otherwise trying to login into the server via TLS will fail.

For most deployments, you can now click **OK** to finish.



To change the parameters of an existing server connection definition, select the desired server from the list and click the **Edit...** button.

To delete an existing server connection definition, select the desired server from the list and click the **Delete** button.

The **Top**, **Move Up**, **Move Down** and **Bottom** buttons are used to change the order of the servers in the list. This affects the order of the servers listed in the drop-down box in the Login Dialogue.

7 cvi42 Web Module

7.7 Overview

cvi42 includes a browser-based client that allows a user to review images and reports when logged in on a browser without client software installed.

This **cvi42** Web Module workflow requires the **cvi42 Gateway**, **cvi42 Webclient Manager**, and **cvi42 Webclient Service** services to be installed and configured in addition to the regular cvi42 Server components. The **cvi42 WebClient Worker** component must also be installed during the setup process. The reporting connection settings for the **cvi42** Web Module should be configured through the installer, but can also be changed through the editing of configuration files (see sections 1.17, 1.18, and 1.19) for advanced configurations.

By default the **cvi42** Web Module can be accessed via the url: `http(s)://<IP or FQDN>:4293`. Using a supported web browser (latest Edge, Chrome, or Safari), go the URL for your **cvi42** Server and enter your cvi42 account username and password.

7.8 Setting up TLS support

By default, the webviewer will listen on port 4293 using standard HTTP. It is recommended that it be configured to use TLS. To do this a certificate and keypair will be required in crt/key format matching the hostname of the **cvi42** Server. Please get this from your system administrator.

1. Certificate files should be placed into the cvi42 data directory
2. The following lines should be set in the `cvi42_webclient_service.ini`:
`webtls=true`
`webtlscompatibility=intermediate`
`webtlsport=443`
`webtlscert=C:/ProgramData/cvi42/<name of crt file.crt>`
`webtlskey=C:/ProgramData/cvi42/<name of key file.key>`
3. Ensure that port 443 is allowed through the firewall.
4. Connections will now be allowed with HTTPS on port 443, or the port set in `webtlsport`.


To improve security of the TLS enabled web connection, HTTP Strict Transport Security (HSTS) can be enabled. This prevents man-in-the-middle attacks by ensuring that only TLS secured resources can be interacted with. This mode will also allow connections to the report server to be proxied through the same HTTPS connection. This is enabled by setting `webforcehttps=true` in `cvi42_webclient service.ini`.

Please consult the User Manual for more details.

8 Command-line Integration

8.7 Overview

The Client & Server-based **cvi42** integration model provides an interface for integrating **cvi42** into third party products, using command line arguments. **cvi42** shall access studies from its own DICOM database or via DICOM Q/R to PACS/VNA.



8.8 Client and Server Integration Workflow

In a client and server-based integration, the expected user workflow is as follows:

1. User opens a study on a 3rd party vendor application (e.g., PACS, workstation etc.).
2. User launches **cvi42** within the application. **cvi42** is launched with command line arguments (e.g., Study Instance UID, Accession Number, Username, full screen etc.) provided by the application.
3. User logs on to **cvi42**.



IMPORTANT: Username is populated into the login dialogue. For security reasons, password is never passed as an argument.

4. **cvi42** client requests to **cvi42** Server to load the study with a specific Study Instance UID or Accession Number.
 - a. If the study does not exist in **cvi42** Server, the server sends a DICOM Q/R request to a designated DICOM Q/R SCP. A progress bar indicates study loading status to the user.
 - b. Once the study is retrieved and imported, the server sends back a signal that triggers the client to load the study.
 - c. If the study does not exist and cannot be retrieved, the user is prompted with a message and returned to the patient list, allowing them to continue to use **cvi42** with regular workflow.
5. User generates reports or secondary captures in **cvi42**.
 - a. **cvi42** client uploads generated DICOM files to **cvi42** Server.
 - b. All files that are uploaded can then be sent to the third-party system via DICOM Storage operation either manually or using housekeeping rules.
6. User closes study and returns to patient list, or user closes **cvi42**.

8.9 Command Line Parameters

Command Line	Activity	Argument
-accession <accession_number>	Load study that matches <accession_number>	Accession Number
-studyuid <study_instance_uid>	Load study that matches <study_instance_uid>	Study Instance UID
-unload-study	Unloads the current study	None
-username <username>	Sets <username> in login dialogue.	Username
-appname <appname>	Launches <appname> after login to cvi42 *Only applicable when used together with - <i>disable-patient-liat</i>	"CORECT"
-disable-quit-dialog	Disables dialogue message box when exiting cvi42	None
-disable-patient-list	Disables patient list. (cvi42 is locked to the current study)	None
-single-instance	Forces to run only a single instance of cvi42	None
-multi-instance	Forces to run multiple instances of cvi42	None
-quit	Closes cvi42 application immediately	None
-quit-with-delay	Closes cvi42 application after a 15 second timeout *This is not applicable if cvi42 was launched with -disable-quit-dialog	None
-study-request-url <URL>	Attempts to authenticate and load a study from the given URL (Cannot be used with "-accession" or "- studyuid" parameters)	URL that provides Username and Study identifier (Accession Number or Study Instance UID) as a response object

8.10 Launching cvi42

In order to launch **cvi42** from a third-party software, the vendor shall run **cvi42** with proper command line arguments.

As an example, the following command will launch **cvi42**, set username in the login dialogue with "-username" argument value and load the appropriate study with "accession" argument. If **cvi42** has already been launched, **cvi42** will close the current study and switch to the study specified in "accession". Also, if a different username is passed as an argument, **cvi42** will close the current study, disconnect from current session, and present a login dialogue.

```
>> cvi42.exe -username="admin" -accession="ABC123456" -single-instance
```

If a study was closed or patient was changed in the vendor's software, it can pass the following arguments to **cvi42**.

```
>> cvi42.exe -unload-study -single-instance
```

This command will launch a **cvi42** process in the background, pass the arguments to the existing **cvi42** process and terminate itself. It is recommended to always pass "-single-instance" to avoid popup messages asking for launching **cvi42** in multi-instance mode.