PARKRAY()



you're home.



Warmth With Purpose – Designed for Australian Living.

Shake off the winter chill and enjoy the welcoming warmth of a Parkray wood heater designed to suit the way you live and relax. With a clean, contemporary look and powerful performance, Parkray wood heaters are ideal for open-plan spaces or as a stylish feature in any room.

BACKED BY THE TRUSTED EXPERTISE OF HUNTER STOVES, A
LEADING BRITISH MANUFACTURER WITH OVER 40 YEARS OF
EXPERIENCE, PARKRAY BRINGS TOGETHER THOUGHTFUL
DESIGN, EFFICIENT HEATING, AND QUALITY CRAFTSMANSHIP.

EVERY PARKRAY WOOD HEATER FEATURES TRIPLEBURN®

TECHNOLOGY FOR A CLEANER, MORE EFFICIENT BURN, ALONG
WITH SIMPLE, INTUITIVE CONTROLS THAT MAKE IT EASY TO

MAINTAIN THE PERFECT TEMPERATURE. BUILT TO MEET HIGH
ENVIRONMENTAL STANDARDS, YOU CAN ENJOY LONG-LASTING
WARMTH WITH CONFIDENCE THAT YOUR WOOD HEATER IS
SUPPORTING A CLEANER, HEALTHIER FUTURE.



HIGHLY CONTROLLABLE AND BUILT FOR REAL-LIFE COMFORT, THE ASPECT 5 GIVES YOU INSTANT COMMAND OVER YOUR HOME'S WARMTH. EASILY ADJUSTABLE, THE WOOD HEATER CAN SHIFT FROM HIGH TO LOW OUTPUT IN A MATTER OF SECONDS, ALLOWING YOU TO CREATE THE PERFECT ATMOSPHERE AT ANY TIME OF DAY.

Despite its generous maximum heat output, the Aspect 5 maintains impressively low emissions of just 0.7g/kg, offering an eco-conscious solution that keeps you warm while minimising environmental impact.

2030 COMPLIANT





PEAK HEAT OUTPUT	9.6kW
MAXIMUM AVERAGE HEAT OUTPUT	6.6kW
PEAK EFFICIENCY	73%

aspect 5 FEATURES

Peak heat output (kW)	
Maximum average heat output (kW)	6.6
Peak Efficiency (%)	73
Emission Factor (g/Kg)	0.7
Log lengths (mm)	
Weight (kg)	79



aspect 5 OPTIONS

BENCH

Aspect models have the option of being fitted on a bench. There is a choice of two lengths, 800mm and 1,195mm long. Both are at a height of 345mm and a depth of 415mm.



PLINTH

You can choose to have your Aspect wood heater fitted on a low or high log plinth, which raises it up off the floor and provides a handy place to store your wood.* The plinth can be installed on a 12mm non-combustible hearth and reduces hearth depth to 300 in front of your wood heater.

HEIGHT DEPTH WIDTH 150/225 362 494


* Ensure a gap of 50mm remains, at all times, between the fuel and heat shield of the log plinth.



WALL CLEARANCES

Clearance distances to	Rear: 125
combustible materials with	Side: 550
additional flue & appliance heat shield install	
Clearance distances to	Rear: 250
combustible materials without	Side: 550
flue & appliance heat shield installed (mm)	Corner: 325
Clearance distances to	Rear: 50
non-combustible materials (mm)	Side: 50
	Corner: 50

HEARTH REQUIREMENTS



Hearth Thickness - (Compressed FC Sheet) 42mm If on Legs or 12mm If Plinth / Bench

FLUE REQUIREMENTS

APPROVED FLUE SYSTEM

6" triple skin flue kit with 8" solid casing conforming to joint AS/NZS 2918:2018, Appendix B.

FOR REDUCED REAR WALL CLEARANCE AN ADDITIONAL HEAT SHIELD IS REQUIRED AS PER BELOW:

(a) 900mm high x 180° stainless steel rear flue shield fitted between the solid 8° casing and the 6° active pipe

(b) Double half heat shield for first 900mm of default kit

(c) Additional half heat shield in conjunction with 8" solid insulated flue kit

DIRECT AIR

The Aspect 5 wood heater comes with the option of a direct air kit.

DEEPER LOG RETAINER


Available on Aspect 5 model.

BRUSHED STAINLESS STEEL HANDLE

A black chrome handle is supplied as standard with an optional brushed stainless steel upgrade available (as pictured above).

DIMENSIONS





PLEASE NOTE: All measurements are in millimetres (mm). All imagery is for illustrative purposes only.





HUNTER STOVES AUSTRALIA

DISTRIBUTED IN AUSTRALIA BY DRAGON WHOLESALING PTY LTD

UNIT 4 16 LEXINGTON DRIVE BELLA VISTA NSW 2153

PH. 1800 064 234 / (02) 8824 9122

