



SINCE 1980 ISO 9001/14001

The Best Solution for Overheating
When it comes to overheating, SEKI is always on standby!

 (주)세기컨트롤
SEKI CONTROLS CO.,LTD.

THERMAL PROTECTOR

ST-12



• FEATURE

Snap Action. Automatic Reset Bimetals.
Superior Heat Response.

• APPLICATION

Overheat protection for Hair Dryer, Electric Fan Heaters,
Popcorn Machines, Electric Ovens, Dish Dryers etc.

• TEMPERATURE SETTING RANGE (at no load)

65°C to 150°C in increments of 5°C

• TOLERANCE

Indicated temp. $\pm 5^\circ\text{C}$

• ON-OFF DIFFERENTIAL TEMP.(general)

$30 \pm 15\text{K}$

• HEAT ENDURANCE

Open temp. $+50^\circ\text{C}$ /continuity, $200^\circ\text{C}/1\text{min}$

• CYCLE LIFE(Resistive Load)

15A/125V 6,000 cycles, 13A/250V 6,000 cycles


• CONTACT CAPACITY

Min. Current 100mA/repeatedly, Max. Current 30A/5 cycles


• CONTACT SYSTEM

Normally closed


www.sekicon.com



OPEN TEMP. DROP / CURRENT



TRIP TIME / CURRENT (AT 25°C)



APPROVAL/RATINGS

Agency	Standard	Category	Electrical Ratings	Max Temp.	File No.
c-UL	UL 873 CSA C22.2 No.24-93	Appliance Control	15A/125V AC, 10A/250V AC Resistive 6,000 Cycles	150°C	E162183
VDE	EN60730-2-9	Thermal Cut-Out	13A(5A)/250V AC Resistive (Inductive) 6,000 Cycles	150°C	1916600-4510-0004
CQC	GB14536.1-2008	Thermal Cut-Out	13A(5A)/250V AC Resistive (Inductive)	150°C	CQC08002022429
	GB14536.10-2008				
KC	K-60730-1 K60730-2-9	Thermal Protector	13A/250V AC	150°C	ZH02003-10002A

WARNING

You may happen to encounter FAKEs of SEKI products in the market, which might cause a big damage to your products. Therefore it's strongly recommended to purchase SEKI products from our AUTHORIZED agents.



SINCE 1980 ISO 9001/14001

The Best Solution for Overheating
When it comes to overheating, SEKI is always on standby!

 (주)세기컨트롤
SEKI CONTROLS CO.,LTD.

THERMAL PROTECTOR

ST-22



• FEATURE

Snap Action. Automatic Reset Bimetals.
Moisture-Proof, Dust-Proof
Superior Heat Response.
PBT Resin Case with Epoxy Seal.

• APPLICATION

Overheat protection for Electric Motors, Battery Chargers,
Transformers, Heating Pads, Fluorescent Ballasts,
OA-Machines, Solenoids, etc.

• TEMPERATURE SETTING RANGE (at no load)

50°C to 150°C in increments of 5°C

• TOLERANCE

Indicated temp. $\pm 5^\circ\text{C}$

• ON-OFF DIFFERENTIAL TEMP.(general)

$30 \pm 15\text{K}$

• HEAT ENDURANCE

Open temp. $+50^\circ\text{C}$ /continuity, $200^\circ\text{C}/1\text{min}$

• CYCLE LIFE(Resistive Load)



8A/125V AC 10,000 cycles, 5A/250V AC 10,000 cycles
3A/48V DC 6,000 cycles

• CONTACT CAPACITY

Min. Current 50mA/repeatedly, Max. Current 30A/5 cycles

• CONTACT SYSTEM

Normally closed



APPROVAL/RATINGS

Agency	Standard	Category	Electrical Ratings	Max °C	File No.
UL	UL 2111	Motor Protector	125V/250V AC 1/2 HP	150 °C	E162232
	UL 873	Regulating	8A/125V AC, 5A/250V AC (Resistive) 10,000 cycles	130 °C	E162183
		Incandescent Lamp	3A/48V DC 6,000 cycles		
		Fluorescent Lamp - Ballast	4A/125V AC, 2A/250V AC 10,000 cycles		
CSA	CSA C22.2 No.77	Motor Protectors	250V AC 1/2HP	150 °C	203757
	CSA C22.2 No.24	Appliance Type	250V AC 1/2HP 6,000 cycles		
VDE	EN-60730-2-2	Thermal Motor Protector	250V AC	150 °C	1916600-4510-0003
	EN-60730-2-3	Fluorescent Lamp - Ballast	1A 250V AC	130 °C	
	EN-60730-2-9	Thermal Cut-Out	7A(4A)/250V AC Resistive(Inductive) 6,000 cycles	150 °C	
CQC	GB14536.1-2008 GB14536.3-2008	Motor Protector	125V/250V AC 1/2HP 8A(4A)/125V AC, 5A(2.5A)/250V AC Resistive(Inductive)	150 °C	CQC08002022430
KC	K60730-1(2009-12) K60730-2-9(2009-12)	Thermal protector	5A/250V AC	150 °C	ZH02003-10001B

LEAD WIRE SPECIFICATION

- W-Type : UL3266 AWG22 Stranded. Standard Length : 70mm long with 7mm stripped
- P - Type : Ø0.7 Tinned Lead. Standard Length : 25mm

* The length can be adjustable on demand.

WARNING

You may happen to encounter FAKES of SEKI products in the market, which might cause a big damage to your products. Therefore it's strongly recommended to purchase SEKI products from our AUTHORIZED agents.