

DECLARATION OF PERFORMANCE

No13-SC-K01

Product Type/Identification: Hydraulically pressed Half Battered Kerb

Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas

Manufacturer: Stowell Concrete Ltd
Arnolds Way
Yatton
North Somerset
BS49 4QN



Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable

AVCP: System 4

Harmonised Standard: EN1340:2003

ETA: Not relevant

Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length	913mm	EN1340:2003
	Widths	150mm 125mm	
	Heights	300mm 255mm 150mm	
Bending strength		5.0Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:

Vincent Stowell

Managing Director 8th September 2026

DECLARATION OF PERFORMANCE

No13-SC-K02

Product Type/Identification: Hydraulically pressed Bullnose Kerb (including X-Text)
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas
Manufacturer: Stowell Concrete Ltd

Arnolds Way
Yatton
North Somerset
BS49 4QN


Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable
AVCP: System 4
Harmonised Standard: EN1340:2003
ETA: Not relevant
Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length	913mm	EN1340:2003
	Widths	150mm 125mm	
	Heights	300mm 255mm 150mm	
Bending strength		5.0Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:


Vincent Stowell
Managing Director 8th September 2026



DECLARATION OF PERFORMANCE

No13-SC-K011

Product Type/Identification: Hydraulically pressed Square Top and Bullnose Edgings
(Including X-Tex)
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas
Manufacturer: Stowell Concrete Ltd

Arnolds Way
Yatton
North Somerset
BS49 4QN


Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable
AVCP: System 4
Harmonised Standard: EN1340:2003
ETA: Not relevant
Declared Performance:

Essential	Characteristics	Performance	Harmonised Technical Specification
Dimensions	Lengths	910mm 913mm	EN1340:2003
	Width	50mm	
	Heights	150mm 200mm 255mm	
Bending strength		5.0Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:


Vincent Stowell
Managing Director 8th September 2026.



DECLARATION OF PERFORMANCE

No13-SC-K08

Product Type/Identification: Hydraulically pressed Transition Kerb
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas
Manufacturer: Stowell Concrete Ltd

Arnolds Way
Yatton
North Somerset
BS49 4QN


Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable
AVCP: System 4
Harmonised Standard: EN1340:2003
ETA: Not relevant
Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length	913mm	EN1340:2003
	Width	125mm	
	Height	255mm	
Bending strength		5.0Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:


Vincent Stowell
Managing Director 8th September 2026

DECLARATION OF PERFORMANCE

No13-SC-K012

Product Type/Identification: Vibrated Quadrants
 Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas
 Manufacturer: Stowell Concrete Ltd

Arnolds Way
 Yatton
 North Somerset
 BS49 4QN

Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable
 AVCP: System 4
 Harmonised Standard: EN1340:2003
 ETA: Not relevant
 Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length	455mm Radius	EN1340:2003
	Width	N/a	
	Height	255mm	
Bending strength		Not applicable	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:

Vincent Stowell
 Managing Director 8th September 2026



DECLARATION OF PERFORMANCE

No13-SC-K09

Product Type/Identification: Hydraulically pressed Quadrants (Including X-Tex)
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas
Manufacturer: Stowell Concrete Ltd

Arnolds Way
Yatton
North Somerset
BS49 4QN


Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable
AVCP: System 4
Harmonised Standard: EN1340:2003
ETA: Not relevant
Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length	305mm Radius	EN1340:2003
	Width	N/a	
	Height	255mm	
Bending strength		Not applicable	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:


Vincent Stowell
Managing Director 8th September 2026.

DECLARATION OF PERFORMANCE

No13-SC-K07



Product Type/Identification: Hydraulically pressed Left Hand and Right Hand Tapered Kerb (Including X-Text)
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas
Manufacturer: Stowell Concrete Ltd

Arnolds Way
Yatton
North Somerset
BS49 4QN


Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable
AVCP: System 4
Harmonised Standard: EN1340:2003
ETA: Not relevant
Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length	913mm	EN1340:2003
	Width	125mm	
	Heights	255mm to 150mm	
Bending strength		5.0Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:


Vincent Stowell
Managing Director 8th September 2026



DECLARATION OF PERFORMANCE

No13-SC-K010

Product Type/Identification: Hydraulically pressed Internal and External Angles (Including X-Tex)
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas

Manufacturer: Stowell Concrete Ltd
Arnolds Way
Yatton
North Somerset
BS49 4QN


Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable
AVCP: System 4
Harmonised Standard: EN1340:2003
ETA: Not relevant
Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length	305mm/305mm	EN1340:2003
	Width	125mm	
	Height	255mm	
Bending strength		Not Applicable	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:


Vincent Stowell

Managing Director 8th September 2026.

DECLARATION OF PERFORMANCE

No13-SC-K03



Product Type/Identification: Hydraulically pressed Full Battered Kerb
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas

Manufacturer: Stowell Concrete Ltd

Arnolds Way
Yatton
North Somerset
BS49 4QN

Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable

AVCP: System 4

Harmonised Standard: EN1340:2003

ETA: Not relevant

Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length	913mm	EN1340:2003
	Width	125mm	
	Heights	255mm 150mm	
Bending strength		5.0Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:

Vincent Stowell

Managing Director 8th September 2026

DECLARATION OF PERFORMANCE

No13-SC-K04

Product Type/Identification: Hydraulically pressed Square Channel
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas
Manufacturer: Stowell Concrete Ltd

Arnolds Way
Yatton
North Somerset
BS49 4QN

Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable
AVCP: System 4
Harmonised Standard: EN1340:2003
ETA: Not relevant
Declared Performance:



Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length	913mm	EN1340:2003
	Widths	255mm 150mm	
	Heights	125mm 100mm	
Bending strength		5.0Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:

Vincent Stowell
Managing Director 8th September 2026



DECLARATION OF PERFORMANCE

No13-SC-K05

Product Type/Identification: Hydraulically pressed Dished Channel
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas
Manufacturer: Stowell Concrete Ltd

Arnolds Way
Yatton
North Somerset
BS49 4QN

Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable
AVCP: System 4
Harmonised Standard: EN1340:2003
ETA: Not relevant
Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length	913mm	EN1340:2003
	Widths	255mm 150mm	
	Heights	125mm 100mm	
Bending strength		5.0Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:

Vincent Stowell

Managing Director 8th September 2026

DECLARATION OF PERFORMANCE

No13-SC-K06

Product Type/Identification: Hydraulically pressed Fluted Channel
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas

Manufacturer: Stowell Concrete Ltd
Arnolds Way
Yatton
North Somerset
BS49 4QN

Email: sales@stowellconcrete.co.uk


Authorised Representative: Not Applicable
AVCP: System 4
Harmonised Standard: EN1340:2003
ETA: Not relevant

Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Length	913mm	EN1340:2003
	Width	255mm	
	Height	75mm	
Bending strength		5.0Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:


Vincent Stowell
Managing Director 8th September 2026



DECLARATION OF PERFORMANCE

No13-SC-K013

Product Type/Identification: Hydraulically pressed Half Battered Internal and External Radius Kerb
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas

Manufacturer: Stowell Concrete Ltd

Arnolds Way
Yatton
North Somerset
BS49 4QN

Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable

AVCP: System 4

Harmonised Standard: EN1340:2003


ETA: Not relevant

Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Lengths	Various face lengths	EN1340:2003
	Width	125mm	
	Height	255mm	
Bending strength		5.0Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:


Vincent Stowell
Managing Director 8th September 2026



DECLARATION OF PERFORMANCE

No13-SC-K014

Product Type/Identification: Hydraulically pressed Bullnose Internal and External Radius Kerb (Including Xtex)
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas
Manufacturer: Stowell Concrete Ltd
Arnolds Way
Yatton
North Somerset
BS49 4QN

Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable

AVCP: System 4

Harmonised Standard: EN1340:2003

ETA: Not relevant

Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Lengths	Various face lengths	EN1340:2003
	Width	125mm	
	Heights	255mm 150mm	
Bending strength		5.0Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:

Vincent Stowell
Managing Director 8th September 2026



DECLARATION OF PERFORMANCE

No13-SC-K015

Product Type/Identification: Hydraulically pressed Full Battered External Radius Kerb
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas
Manufacturer: Stowell Concrete Ltd

Arnolds Way
Yatton
North Somerset
BS49 4QN


Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable
AVCP: System 4
Harmonised Standard: EN1340:2003
ETA: Not relevant
Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Lengths	Various face lengths	EN1340:2003
	Width	125mm	
	Height	255mm	
Bending strength		5.0Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:


Vincent Stowell
Managing Director 8th September 2026



DECLARATION OF PERFORMANCE

No13-SC-K016

Product Type/Identification: Hydraulically pressed Radius Taper External Kerb
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas
Manufacturer: Stowell Concrete Ltd

Arnolds Way
Yatton
North Somerset
BS49 4QN

Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable
AVCP: System 4
Harmonised Standard: EN1340:2003
ETA: Not relevant
Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Lengths	Various face lengths	EN1340:2003
	Width	125mm	
	Heights	255mm to 150mm	
Bending strength		5.0Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:

Vincent Stowell
Managing Director 8th September 2026



DECLARATION OF PERFORMANCE

No13-SC-K017

Product Type/Identification: Vibrated Half Battered Internal Radius Kerb
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas
Manufacturer: Stowell Concrete Ltd

Arnolds Way
Yatton
North Somerset
BS49 4QN

Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable

AVCP: System 4

Harmonised Standard: EN1340:2003

ETA: Not relevant

Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Lengths	Various face lengths	EN1340:2003
	Width	125mm	
	Height	255mm	
Bending strength		3.5Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:

Vincent Stowell
Managing Director 30th June 2023.



DECLARATION OF PERFORMANCE

No13-SC-K018

Product Type/Identification: Vibrated Bullnose External Radius Kerb
Intended Use: For external uses and road finishes to cover external pedestrian and vehicular circulation areas
Manufacturer: Stowell Concrete Ltd

Arnolds Way
Yatton
North Somerset
BS49 4QN


Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable
AVCP: System 4
Harmonised Standard: EN1340:2003
ETA: Not relevant
Declared Performance:

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions	Lengths	Various face lengths	EN1340:2003
	Width	125mm	
	Height	150mm	
Bending strength		3.5Mpa	
Slip/skid resistance		Satisfactory	
Reaction to fire		A1	
External fire performance		Satisfactory	
Thermal conductivity		1.52 ($\lambda_{10, dry}$)W/mK	
Durability		Pass	
Emission of Asbestos		No content	

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:


Vincent Stowell
Managing Director 30th June 2023.