DECLARATION OF PERFORMANCE

No13-SC-S09

Product Type/Identification: Hydraulically pressed tactile slabs

Intended Use: Trafficked paving area and roof coverings

Manufacturer Stowell Concrete Ltd

Arnolds Way Yatton North Somerset BS49 4QN

Email: sales@stowellconcrete.co.uk

Authorised Representative: Not Applicable

AVCP: System 4
Harmonised Standard: EN1339:2003
ETA: Not relevant

Declared Performance:

| Essential Characteristics | | Performance | | Harmonised Technical |
|---------------------------|--------------------|-----------------------|-----------|-------------------------|
| | Lengths | 450mm | 400mm | Specification |
| | Lengths | 43011111 | 400111111 | |
| Dimensions | Widths | 450mm | 400mm | |
| | Thickness | 65mm | 50mm | |
| | Tolerance category | 2 | | |
| Bending strength | | 3.5Mpa | | |
| Slip/skid resistance | | Satisfactory | | EN1339:2003 |
| Reaction to fire | | A1 | | |
| External fire performance | | Satisfactory | | |
| Thermal conductivity | | 1.52 (λ 10, dry)W/mK | | |
| Durability | | Pass | | |
| Emission of Asbestos | | No content | | |

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:

Vincent Stowell

Managing Director 16th August 2021.